



## OFFICE OF ENVIRONMENTAL SERVICES

### **Minor Source Air General Permit Crude Oil and Natural Gas Production**

#### **MODIFICATION**

AGENCY INTEREST NO. 158873  
ACTIVITY NO. PER20240001

In accordance with the Louisiana Environmental Quality Act, as amended (La. R.S. 30:2001, *et seq.*: “the Act”) and the rules and regulations effective or promulgated under the authority of the Act (LAC 33:III.501 and LAC 33:III.513), this Air General Permit is hereby issued. This permit authorizes persons who meet the requirements set forth herein and have been approved by this Office to construct, operate, and modify crude oil and natural gas production facilities in accordance with the emissions limitations, monitoring requirements, and other conditions of this permit.

This general permit first became effective on September 15, 2010, and was modified on May 17, 2011; November 15, 2012; July 9, 2013; and October 28, 2016. This general permit was renewed and modified on April 7, 2020, with an effective date of September 16, 2020.

This modification shall become effective upon issuance (except as noted herein) and shall expire on **September 16, 2030**. Modified terms and conditions are summarized in Section XV.

Issued on October 7, 2024

*Amanda Vincent*

Amanda Vincent, Ph.D., PMP  
Assistant Secretary  
Office of Environmental Services



**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

**I. STATEMENT OF AUTHORITY – LAC 33:III.513.A**

1. The permitting authority may issue a general permit intended to cover numerous similar sources or activities. General permits shall be issued in accordance with LAC 33:III.519 and, prior to issuance, shall undergo public notice. Each general permit shall incorporate terms and conditions applicable to sources that would qualify for the general permit. Any general permit shall identify criteria by which sources may qualify for the general permit and may provide for applications which deviate from the requirements of LAC 33:III.517.
2. The owner or operator of any source that would qualify for the general permit may apply for authorization to operate under the general permit. The application must include all information necessary to determine qualification for and to assure compliance with the general permit.
3. The permitting authority may approve an owner or operator's application for authorization to operate under the general permit without repeating the public participation procedures. Such an approval shall not be a final permit action for purposes of judicial review regarding the terms and conditions of the general permit.
4. Any source which is issued the general permit shall be subject to enforcement action for operation without a permit if the source is later determined not to qualify for the general permit.

**II. ELIGIBILITY**

This minor source air general permit authorizes construction, operation, and modification of crude oil and natural gas production facilities that meet the eligibility requirements outlined herein.

Facilities eligible for coverage under this general permit include:

- crude oil and natural gas production and field facilities classified under Standard Industrial Classification (SIC) Code 1311—Crude Petroleum and Natural Gas [North American Industry Classification System (NAICS) 211120 or 211130]; and
- “midstream” facilities (i.e., contracted facilities which generally compress and/or process natural gas between the producing property and a natural gas processing plant or sales gas pipeline compressor station). Such facilities may be classified under SIC Code 1389—Oil and Gas Field Services, Not Elsewhere Classified (NAICS 213112).

This general permit does not address operations engaged in the transmission and/or storage of natural gas under SIC Code 4922—Natural Gas Transmission (NAICS 486210) or those engaged in the processing of natural gas under SIC Code 1321—Natural Gas Liquids (NAICS 211112), unless a facility is classified as such only by its use of Joule-Thomson (J-T) equipment as part of a “forced” process to extract natural gas liquids (NGL). See Section V of this general permit for more information.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

Facilities must maintain eligibility to operate under this permit. This permit does **not** authorize operations that are not compliant with the established eligibility conditions. Prior to initiating any modification to a facility that would prohibit it from being covered under this general permit, the permittee must request a site-specific air permit. If a modification rendering the facility ineligible for this general permit is effected without a site-specific permit in place, the modification will be deemed unauthorized from the date construction commenced, and the owner or operator will be subject to enforcement action.

**Facilities Excluded from Coverage**

This general permit cannot be used to authorize construction and operation of:

1. “Part 70 Sources” as defined in LAC 33:III.502.
2. Except as described in LAC 33:III.501.B.3.a-b, facilities subject to regulatory requirements promulgated **on or before August 29, 2010**, not addressed by this general permit.

If a federal or state regulation promulgated or modified after August 29, 2010, is applicable to a facility eligible for coverage under this general permit, the permittee shall comply with the new or modified regulation by the compliance date(s) established therein. The new or modified regulation shall not render a facility ineligible for coverage under this general permit.

3. Facilities subject to LAC 33:III.Chapter 59 (Chemical Accident Prevention) or 40 CFR Part 68 (Chemical Accident Prevention Provisions).
4. Facilities with equipment specifically excluded as described in Section V – Equipment Specifications and Calculation Methodologies.
5. Facilities that formerly operated as major sources if Best Available Control Technology (BACT) or Lowest Achievable Emission Rate (LAER) controls were installed and are being maintained on an existing emissions unit.
6. Facilities located in Calcasieu or Pointe Coupee Parish with equipment subject to the control requirements of LAC 33:III.2115 (Waste Gas Disposal).
7. Facilities with glycol dehydration unit process vents subject to the control requirements specified in 40 CFR 63.765(b) or (c) of 40 CFR 63 Subpart HH.
8. Facilities using a condenser or carbon adsorption system to comply with the provisions of 40 CFR 60 Subpart OOOO (Standards of Performance for Crude Oil and Natural Gas Facilities for Which Construction, Modification, or Reconstruction Commenced After August 23, 2011, and on or Before September 18, 2015); 40 CFR 60 Subpart OOOOa (Standards of Performance for Crude Oil and Natural Gas Facilities for Which Construction, Modification or Reconstruction Commenced After September 18, 2015 and On or Before December 6, 2022); or 40 CFR 60 Subpart OOOOb (Standards of Performance for Crude Oil and Natural Gas Facilities for Which Construction, Modification or Reconstruction Commenced After December 6, 2022).

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

9. Facilities that include centrifugal compressors.
10. Facilities that utilize steam-assisted flares.
11. Facilities that comply with an alternative means of emission limitation (AMEL) approved by the United States Environmental Protection Agency (EPA).

**III. FACILITY-WIDE EMISSIONS LIMITATIONS**

**Baton Rouge Area**

For facilities located in the parishes of Ascension, East Baton Rouge, Iberville, Livingston, and West Baton Rouge (i.e., the Baton Rouge Area), potential emissions of criteria pollutants and toxic air pollutants (TAPs) from the facility (or grouping of “contiguous or adjacent” facilities) must be less than the following amounts, in tons per year:

<u>Pollutant</u>	<u>Emissions</u>
PM <sub>10</sub>	15
SO <sub>2</sub>	40
NO <sub>x</sub>	20
CO	90
Total VOC	20
Total TAPs	20
Any Individual TAP	8

**All Other Areas**

For facilities located in any other parish, potential emissions of criteria pollutants and TAPs from the facility (or grouping of “contiguous or adjacent” facilities) must be less than the following amounts, in tons per year:

<u>Pollutant</u>	<u>Emissions</u>
PM <sub>10</sub>	15
SO <sub>2</sub>	40
NO <sub>x</sub>	90
CO	90
Total VOC	90
Total TAPs	20
Any Individual TAP	8

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

The above limitations shall include aggregate emissions from *all* sources at the facility, including emissions from all insignificant activities set forth under LAC 33:III.501.B.5; those from activities traditionally classified under General Condition XVII (e.g., sampling); and those from activities that may occur at the facility on an infrequent basis, such as pigging operations at a “midstream” facility.

Re-designation of an Attainment Area to a Nonattainment Area

If, during the term of this permit, any parish outside of the Baton Rouge Area is designated as a “**serious**” or “**severe**” ozone nonattainment area, the owner or operator of a facility located in any such parish:

1. may retain this permit and comply with the limits applicable to facilities located in the Baton Rouge Area as set forth above; or
2. if the facility cannot comply or the owner or operator chooses not to comply with the Baton Rouge Area limits, the owner or operator shall apply for a site-specific air permit no later than 90 days after the effective date of the “**serious**” or “**severe**” nonattainment designation by the EPA.

**IV. CONTIGUOUS OR ADJACENT SURFACE SITES**

Groupings of “contiguous or adjacent” oil and gas surface sites (under common control) may be covered under this general permit provided that aggregate emissions from the grouping do not exceed the emissions thresholds listed in Section III. Guidance on evaluating “contiguous or adjacent” facilities can be accessed on LDEQ’s website at <https://deq.louisiana.gov/page/-contiguous-or-adjacent-properties-in-the-oil-and-natural-gas-sector>.

A separate application must be submitted for each facility in a “contiguous or adjacent” grouping. However, it is not necessary for each facility in a “contiguous or adjacent” grouping to seek coverage under this permit.

**V. EQUIPMENT SPECIFICATIONS, CALCULATION METHODOLOGIES, AND ALTERNATIVE TEST METHODS**

Terms used in Section V are defined in the Statement of Basis (SOB) accompanying this permit.

**A. Joule-Thomson (J-T) Equipment**

Facilities using J-T equipment as part of a “forced” process are eligible for coverage under this general permit, provided:

1. the operation is a non-fractionating plant that does not have the design capacity to process 10 million standard cubic feet per day or more of field gas;
2. if the facility commenced construction, reconstruction, or modification after January 20, 1984, and on or before August 23, 2011, the owner or operator complies with all

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

applicable requirements of 40 CFR 60 Subpart KKK (Standards of Performance for Equipment Leaks of VOC From Onshore Natural Gas Processing Plants for Which Construction, Reconstruction, or Modification Commenced After January 20, 1984, and on or Before August 23, 2011); and

3. the owner does not comply with Subpart KKK by routing emissions to a control device.

Forced extraction processes include Cryogenic-Joule-Thomson, Refrigerated Absorption and Cryogenic-Joule-Thomson, Refrigeration and Cryogenic-Joule-Thomson, Cryogenic-Joule-Thomson and Expander, and similar processes.

J-T equipment that relies on existing gas pressure and temperature and that does not require additional gas compression to remove condensates from the gas stream or to move hydrocarbon liquids or remaining gas from the process is also allowed. This process does *not* trigger any requirements under 40 CFR 60 Subpart KKK.

**B. Amine Sweetening Units**

Amine sweetening units eligible to be covered under this permit must have a design capacity less than 2 long tons per day (LT/D) of H<sub>2</sub>S expressed as sulfur. Amine sweetening units primarily used to remove CO<sub>2</sub> from a produced gas stream are eligible for coverage under this general permit.

**C. Marine Loading Operations**

Marine loading operations eligible to be covered under this permit must not employ a control device to restrict VOC emissions from marine loading in order to comply with LAC 33:III.2108.

**D. Glycol Dehydration Units**

Emissions from the gas-condensate-glycol (GCG) separator (flash tank) on all glycol dehydration units shall be controlled via a combustion device or by recycle/recompression, except where the owner or operator can demonstrate that total uncontrolled VOC emissions from *both* the glycol dehydration unit reboiler vent and the vent from the flash tank, in total, are not in excess of 9 tons per year. Terms are defined in the Statement of Basis.

For triethylene glycol (TEG) dehydration units, the:

- actual annual average flowrate of natural gas to the glycol dehydration unit must be less than 85 thousand standard cubic meters [ $\sim 3$  MM scf] per day as determined by the procedures specified in 40 CFR 63.772(b)(1) of 40 CFR 63 Subpart HH; **or**
- actual average emissions of benzene from the glycol dehydration unit process vent (the glycol dehydration unit reboiler vent *and* the vent from the GCG separator (flash tank), if present) to the atmosphere must be less than 0.90 megagram per year [ $\sim 1$  TPY] as determined by the procedures specified in 40 CFR 63.772(b)(2) of 40 CFR 63 Subpart HH.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

**E. Internal Combustion Engines (ICEs)**

ICEs must be fueled by natural gas or diesel (or fuel oil no. 2). Stationary ICEs fueled by gasoline or liquefied petroleum gas (LPG) are not eligible for coverage under this permit.

ICEs subject to LAC 33:III.2201 are eligible for coverage under this permit provided that a chemical reagent (e.g., ammonia) is **not** used for the reduction of NO<sub>x</sub> and the facility does **not** comply with Chapter 22 by means of a ton per day or pound per hour cap as allowed by LAC 33:III.2201.D.4 or a facility-wide averaging plan as described in LAC 33:III.2201.E.1.

**F. All Storage Vessels**

Storage vessels storing a liquid with a maximum true vapor pressure less than 0.5 psia are eligible for coverage under this general permit. Storage vessels storing a liquid with a maximum true vapor pressure of 0.5 psia or greater are subject to the following restrictions:

1. Each storage vessel located prior to lease custody transfer containing any material other than crude oil, condensate, or produced water shall have a capacity less than or equal to 19,800 gallons; each vessel storing crude oil, condensate, or produced water shall have a capacity less than or equal to 420,000 gallons.
2. Each storage vessel located after lease custody transfer shall have a capacity less than or equal to 19,800 gallons.

For more information on lease custody transfer, see *Louisiana Guidance for Air Permitting Actions* available at <https://deq.louisiana.gov/page/air-permits-division>.

**G. Storage Vessels/Tank Batteries for Which Construction, Modification, or Reconstruction Commenced after December 6, 2022**

This subsection applies to storage vessels/tank batteries that contain an accumulation of crude oil, condensate, intermediate hydrocarbon liquids, or produced water. A tank battery is a group of storage vessels that are manifolded together for liquid transfer. A tank battery may consist of a single storage vessel if only one storage vessel is present.

***Determination of Potential VOC and Methane Emissions***

The potential for VOC and methane emissions must be calculated as the cumulative emissions from *all* storage vessels within the tank battery.

***Storage Vessels/Tank Batteries Located at Well Sites or Centralized Production Facilities***

In accordance with 40 CFR 60.5365b(e)(2)(ii), the permittee shall determine potential VOC and methane emissions within 30 days after startup of production and within 30 days after reconstruction or modification as specified in 40 CFR 60.5365b(e)(3)(i) and (ii). The permittee shall also determine a tank battery's potential for VOC emissions within 30 days of removal of an apparatus that recovers and routes vapor to a process or any operation that is inconsistent with the conditions specified in 40 CFR 60.5365b(e)(5)(i) and (ii).

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

The potential for VOC and methane emissions must be determined using a generally accepted model or calculation methodology that accounts for flashing, working, and breathing losses and be based on the maximum average daily throughput to the tank battery determined for a 30-day period of production. This determination can account for legally and practicably enforceable emission limits.<sup>1</sup>

*Storage Vessels/Tank Batteries Located at Compressor Stations*

In accordance with 40 CFR 60.5365b(e)(2)(iii), the permittee shall determine potential VOC and methane emissions prior to startup of the compressor station and within 30 days after reconstruction or modification as specified in 40 CFR 60.5365b(e)(3)(i) and (ii).

The potential for VOC and methane emissions must be determined using a generally accepted model or calculation methodology that accounts for flashing, working, and breathing losses and be based on the throughput to the tank battery established in a legally and practicably enforceable limit.

Alternatively, potential VOC and methane emissions may be determined using a generally accepted model or calculation methodology that accounts for flashing, working, and breathing losses and be based on the projected maximum average daily throughput. Maximum average daily throughput shall be determined using a generally accepted engineering model (e.g., volumetric condensate rates from the tank battery based on the maximum gas throughput capacity of each producing facility) to project the maximum average daily throughput for the tank battery.

*Storage Vessels/Tank Batteries that Are Not “Storage Vessel Affected Facilities” and that Do Not Employ a Control Device to Restrict Potential VOC and Methane Emissions*

For storage vessels/tank batteries that are not “storage vessels affected facilities” as described in 40 CFR 60.5365b(e) and that do not employ a control device to restrict potential VOC and methane emissions, the permittee shall keep records of the “potential for emissions” calculation for the life of the storage vessel or until such time the tank battery becomes a “storage vessel affected facility” because the potential for emissions meets or exceeds 6 tons per year of VOC and/or 20 tons per year of methane.

If the permittee seeks to restrict throughput by means of a legally and practicably enforceable limit, the permittee shall:

1. Comply with the monitoring, recordkeeping, and reporting requirements in Table 1; and
2. Report the information described in Table 1 annually. The report shall be certified by a responsible official and submitted to the Office of Environmental Services by April 30 for the preceding calendar year.<sup>2</sup>

---

<sup>1</sup> “Small Entity Compliance Guide For Oil and Natural Gas Sector: Emission Standards for New, Reconstructed, and Modified Sources, 40 CFR Part 60, Subpart OOOOb” (p. 103)

([https://www.epa.gov/system/files/documents/2024-05/final-nspsoooob-secg\\_20240517\\_v2.0-508\\_1.pdf](https://www.epa.gov/system/files/documents/2024-05/final-nspsoooob-secg_20240517_v2.0-508_1.pdf))

<sup>2</sup> Compliance with Table 1 is not required where potential VOC and methane emissions are calculated in accordance

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

***Storage Vessels/Tank Batteries that Are Not “Storage Vessel Affected Facilities” Because They Employ a Control Device to Restrict Potential VOC and Methane Emissions Below 6 and 20 Tons Per Year, Respectively***

For storage vessels/tank batteries that are not “storage vessels affected facilities” as described in 40 CFR 60.5365b(e) because they employ a control device to restrict potential VOC and methane emissions, the permittee shall comply with the following requirements:

1. The permittee shall keep records of the “potential for emissions” calculation for the life of the storage vessel or until such time the tank battery becomes a “storage vessel affected facility” because the potential for emissions meets or exceeds 6 tons per year of VOC and/or 20 tons per year of methane.
2. The permittee shall conduct an initial performance test of the control device in accordance with the provisions of 40 CFR 60.5413b unless the model of the control device has been demonstrated to meet the performance requirements of 40 CFR 60.5412b(a)(1)(i) through a performance test conducted by the manufacturer as specified in 40 CFR 60.5413b(d).
3. The permittee shall operate each control device following the manufacturer’s written operating instructions, procedures, and maintenance schedule to ensure good air pollution control practices for minimizing emissions. Flares shall be designed and operated in accordance with 40 CFR 60.18.
4. The permittee shall comply with the monitoring, recordkeeping, and reporting requirements in Table 1 and in Table 2, 3, or 4, as applicable.

For non-catalytic enclosed combustion devices (Table 2), the permittee must monitor 1.) either combustion zone temperature or VOC outlet concentration; 2.) inlet flow (via either option 1 or 2); and 3.) visible emissions.

For catalytic vapor incinerators (Table 3), the permittee must monitor 1.) either catalyst bed inlet temperature and temperature differential or VOC outlet concentration; 2.) inlet flow (via either option 1 or 2); and 3.) visible emissions.

For flares (Table 4), the permittee must monitor 1.) the presence of a pilot flame; 2.) minimum inlet flow (via either option 1 or 2); 3.) net heating value of the gas being combusted; and 4.) visible emissions.

5. The permittee shall report the information described in Table 1 and the information described in Table 2, 3, or 4, as applicable, annually. The report shall be certified by a responsible official and submitted to the Office of Environmental Services by April 30 for the preceding calendar year.

**MINOR SOURCE AIR GENERAL PERMIT  
AGENCY INTEREST NO. 158873  
ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

***Requests to Restrict Throughput by Means of a Legally and Practicably Enforceable Limit***

Should a permit applicant seek to restrict throughput by means of a legally and practicably enforceable limit, the requested limit must be disclosed in the General Permit Applicability Questionnaire accompanying the “Application for Approval of Emissions of Air Pollutants from Minor Sources.”

***Effective Dates***

The permittee shall comply with the terms and conditions of Table 1 (where applicable) as soon as practicable, but by no later than December 1, 2024. The permittee shall comply with the terms and conditions of Table 2, 3, or 4, as applicable, as soon as practicable, but by no later than February 1, 2025.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

**TABLE 1: PRODUCTION AND OPERATING CONDITIONS**

<b>Indicator</b>	<b>Monitoring and Recordkeeping</b>	<b>Minimum Frequency</b>	<b>Reporting</b>
Throughput	Record the throughput of crude oil/condensate and produced water to the tank battery.	Once per calendar week <sup>3</sup>	Report the actual average daily throughput for each rolling 4-week period. Report the average daily throughput (4-week average) on which VOC and methane emissions are based. If the average daily throughput for any 4-week period exceeds that upon which VOC and methane emissions are based, the report shall include a demonstration that actual VOC and methane emissions from the tank battery did not exceed 6 tons per year and 20 tons per year, respectively. <sup>4</sup>
Operating Conditions	Record changes in operational conditions (e.g., additional throughput from the addition of a new well or the hydraulic fracturing or refracturing of an existing well) which could increase VOC and/or methane emissions from the tank battery.	Upon occurrence of each event	Report the nature of any changes in operational conditions. For changes that may increase VOC and/or methane emissions, the report shall include a demonstration that potential VOC and methane emissions remain below 6 tons per year and 20 tons per year, respectively.

<sup>3</sup> Here and elsewhere in this permit, where the permit establishes a minimum frequency of once per calendar week, each monitoring event must be separated by at least 4 days.

<sup>4</sup> Consistent with General Condition III of LAC 33:III.537 as modified in Section XIV of this general permit, if emissions from a tank battery are determined to be greater than those disclosed in the permit application for the facility, the owner/operator shall submit a revised application in accordance with Section VII as soon as practicable, but no later than 30 calendar days after discovery of the discrepancy.

MINOR SOURCE AIR GENERAL PERMIT  
 AGENCY INTEREST NO. 158873  
 ACTIVITY NO. PER20240001

CRUDE OIL AND NATURAL GAS PRODUCTION

TABLE 2: ENCLOSED COMBUSTION DEVICES (NON-CATALYTIC)

<b>Indicator</b>	<b>Monitoring and Recordkeeping</b>	<b>Minimum Frequency</b>	<b>Reporting</b>
Option 1: Combustion Zone Temperature	Measure and record the temperature in the combustion chamber or immediately downstream of the combustion chamber. Operate the enclosed combustion device such that the minimum combustion temperature is greater than or equal to that established during the most recent performance test demonstrating potential VOC and methane emissions are less than 6 tons per year and 20 tons per year, respectively. The temperature sensor shall be maintained in accordance with manufacturer's specifications.	Once per calendar week	Report the temperature in the combustion chamber or immediately downstream of the combustion chamber for each monitoring event, and the date of each monitoring event, the date of each monitoring event, and the minimum combustion temperature established during the most recent performance test demonstrating potential VOC and methane emissions are less than 6 tons per year and 20 tons per year, respectively.
Option 2: VOC and Methane Outlet Concentrations	Measure and record the VOC and methane concentrations at the outlet of the enclosed control device using a properly calibrated portable analyzer. The monitoring device shall meet the requirements of 40 CFR 60, Appendix A, Method 21. <sup>5</sup> The maximum VOC and methane concentrations shall be established during the most recent performance test demonstrating potential VOC and methane emissions are less than 6 tons per year and 20 tons per year, respectively. The portable analyzer shall be maintained, calibrated, and operated in accordance with manufacturer's specifications.	Once per calendar week	Report the VOC and methane concentrations at the outlet of the enclosed combustion device for each monitoring event, the date of each monitoring event, and the maximum VOC and methane concentrations established during the most recent performance test demonstrating potential VOC and methane emissions are less than 6 tons per year and 20 tons per year, respectively.
Inlet Flow Rate: Option 1	Measure and record the inlet flow rate. Operate the enclosed combustion device at or above the minimum inlet gas flow rate and at or below the maximum inlet gas flow rate specified by the manufacturer. The monitoring instrument shall be maintained, calibrated, and operated in accordance with manufacturer's specifications.	Once per calendar week	Report the inlet gas flow rate for each monitoring event, the date of each monitoring event, and the minimum and maximum inlet gas flow rate specified by the manufacturer.

<sup>5</sup> Here and elsewhere in this permit, alternate methods may be used with the prior approval of LDEQ.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

**TABLE 2: ENCLOSED COMBUSTION DEVICES (NON-CATALYTIC)**

<b>Indicator</b>	<b>Monitoring and Recordkeeping</b>	<b>Minimum Frequency</b>	<b>Reporting</b>
Inlet Flow Rate: Option <sub>2</sub>	Comply with 40 CFR 60.5417(b)(d)(8)(iv)(C).	Once per calendar year (for the backpressure regulator) <sup>6</sup>	Report the date that the backpressure regulator valve set point was confirmed to be correct and consistent with the engineering evaluation and manufacturer specifications and that the valve fully closes when not in the open position.
Visible Emissions	Monitor for and record the presence or absence of visible emissions. Operate the enclosed combustion device with no visible emissions, except for periods not to exceed a total of 1 minute during any 15-minute period. Perform visible emissions tests using section 11 of Method 22 of 40 CFR 60, Appendix A. The observation period shall be 15 minutes or once the amount of time visible emissions are present has exceeded 1 minute, whichever time period is less. If the enclosed combustion device fails the visible emissions test, the permittee must follow manufacturer's repair instructions, if available, or best combustion engineering practices as outlined in the permittee's maintenance plan for the unit to return it to compliant operation. All repair and maintenance activities must be recorded in a maintenance and repair log and made be available for inspection.	Once per calendar month <sup>7</sup>	Report the presence or absence of visible emissions for each monitoring event, the duration of visible emissions if detected, and the date of each monitoring event. For enclosed combustion devices failing the visible emissions test, report the repairs and/or maintenance activities conducted.

<sup>6</sup> Here and elsewhere in this permit, where the permit establishes a minimum frequency of once per calendar year, each monitoring event must be separated by at least 6 months.

<sup>7</sup> Here and elsewhere in this permit, where the permit establishes a minimum frequency of once per calendar month, each monitoring event must be separated by at least 15 days.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

**TABLE 3: CATALYTIC VAPOR INCINERATOR**

<b>Indicator</b>	<b>Monitoring and Recordkeeping</b>	<b>Minimum Frequency</b>	<b>Reporting</b>
Option 1: Catalyst Bed Inlet Temperature and Temperature Differential	<p>Measure and record the temperature at the catalyst bed inlet and at the catalyst bed outlet. Install one temperature sensor in the vent stream at the nearest feasible point to the catalyst bed inlet and a second temperature sensor in the vent stream at the nearest feasible point to the catalyst bed outlet. Operate the catalytic vapor incinerator at or above the minimum temperature of the catalyst bed inlet <i>and</i> at or above the minimum temperature differential between the catalyst bed inlet and the catalyst bed outlet established during the most recent performance test demonstrating potential VOC and methane emissions are less than 6 tons per year and 20 tons per year, respectively. The temperature sensors shall be maintained in accordance with manufacturer's specifications.</p>	Once per calendar week	<p>Report the temperature at the catalyst bed inlet, at the catalyst bed outlet, and the differential between the two for each monitoring event; the date of each monitoring event; and the minimum temperature of the catalyst bed inlet and the minimum temperature differential between the catalyst bed inlet and the catalyst bed outlet established during the most recent performance test demonstrating potential VOC and methane emissions are less than 6 tons per year and 20 tons per year, respectively.</p>
Option 2: VOC and Methane Outlet Concentrations	<p>Measure and record the VOC and methane concentrations at the outlet of the catalytic vapor incinerator using a properly calibrated portable analyzer. The monitoring device shall meet the requirements of 40 CFR 60, Appendix A, Method 21. The maximum VOC and methane concentrations shall be established during the most recent performance test demonstrating potential VOC and methane emissions are less than 6 tons per year and 20 tons per year, respectively. The monitoring instrument shall be maintained and operated in accordance with manufacturer's specifications.</p>	Once per calendar week	<p>Report the VOC and methane concentrations at the outlet of the catalytic vapor incinerator for each monitoring event, the date of each monitoring event, and the maximum VOC and methane concentrations established during the most recent performance test demonstrating potential VOC and methane emissions are less than 6 tons per year and 20 tons per year, respectively.</p>

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

**TABLE 3: CATALYTIC VAPOR INCINERATOR**

<b>Indicator</b>	<b>Monitoring and Recordkeeping</b>	<b>Minimum Frequency</b>	<b>Reporting</b>
Inlet Flow Rate: Option 1	Measure and record the inlet flow rate. Operate the catalytic vapor incinerator at or above the minimum inlet gas flow rate and at or below the maximum inlet gas flow rate specified by the manufacturer. The monitoring instrument shall be maintained, calibrated, and operated in accordance with manufacturer's specifications.	Once per calendar week	Report the inlet gas flow rate for each monitoring event, the date of each monitoring event, and the minimum and maximum inlet gas flow rate specified by the manufacturer.
Inlet Flow Rate: Option 2	Comply with 40 CFR 60.5417(b)(8)(iv)(C).	Once per calendar year (for the backpressure regulator)	Report the date that the backpressure regulator valve set point was confirmed to be correct and consistent with the engineering evaluation and manufacturer specifications and that the valve fully closes when not in the open position.
Visible Emissions	Monitor for and record the presence or absence of visible emissions. Operate the catalytic vapor incinerator with no visible emissions, except for periods not to exceed a total of 1 minute during any 15-minute period. Perform visible emissions tests using section 11 of Method 22 of 40 CFR 60, Appendix A. The observation period shall be 15 minutes or once the amount of time visible emissions are present has exceeded 1 minute, whichever time period is less. If the catalytic vapor incinerator fails the visible emissions test, the permittee must follow manufacturer's repair instructions, if available, or best combustion engineering practices as outlined in the permittee's maintenance plan for the unit to return it to compliant operation. All repair and maintenance activities must be recorded in a maintenance and repair log and made be available for inspection.	Once per calendar month	Report the presence or absence of visible emissions for each monitoring event, the duration of visible emissions if detected, and the date of each monitoring event. For catalytic vapor incinerators failing the visible emissions test, report the repairs and/or maintenance activities conducted.

MINOR SOURCE AIR GENERAL PERMIT  
 AGENCY INTEREST NO. 158873  
 ACTIVITY NO. PER20240001

CRUDE OIL AND NATURAL GAS PRODUCTION

TABLE 4: FLARE

<b>Indicator</b>	<b>Monitoring and Recordkeeping</b>	<b>Minimum Frequency</b>	<b>Reporting</b>
Pilot Flame	Monitor for the presence of a pilot flame using a thermocouple, ultraviolet beam sensor, or infrared sensor at all times that gas may be directed to the flare for combustion. The monitoring instrument shall be maintained and operated in accordance with manufacturer's specifications. An alert must be sent to the nearest control room whenever the pilot is not lit and gas may be directed to the flare for combustion.	Once per 15 minutes	Report the date and time of all periods when there is no indication of the presence of a pilot flame and gas may have been directed to the flare for combustion.
Minimum Inlet Flow Rate: Option 1	Measure and record the inlet flow rate. Operate the flare at or above the minimum inlet gas flow rate specified by the manufacturer. The monitoring instrument shall be maintained, calibrated, and operated in accordance with manufacturer's specifications.	Once per calendar week	Report the inlet gas flow rate for each monitoring event, the date of each monitoring event, and the minimum inlet gas flow rate specified by the manufacturer.
Minimum Inlet Flow Rate: Option 2	Comply with 40 CFR 60.5417(b)(d)(8)(iv)(B).	Once per calendar year (for the backpressure regulator)	Report the date that the backpressure regulator valve set point was confirmed to be correct and consistent with the engineering evaluation and manufacturer specifications and that the valve fully closes when not in the open position.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

**TABLE 4: FLARE**

<b>Indicator</b>	<b>Monitoring and Recordkeeping</b>	<b>Minimum Frequency</b>	<b>Reporting</b>
Net Heating Value	Calculate and record the net heating value (NHV) of the gas being combusted using the procedures and specifications of 40 CFR 60.18(f)(3). <sup>8</sup> The sample points should be installed in the vent stream as near as possible to the flare inlet such that the total vent stream to the flare is measured and analyzed. The minimum net heating value of the gas being combusted shall be 300 Btu/scf for air-assisted flares, 200 Btu/scf for unassisted flares, and 800 Btu/scf for pressure-assisted flares.	Once per calendar year	Report the net heating value for each monitoring event and the date of each monitoring event.
Visible Emissions	Monitor for and record the presence or absence of visible emissions. Operate the flare with no visible emissions, except for periods not to exceed a total of 1 minute during any 15-minute period. Perform visible emissions tests using section 11 of Method 22 of 40 CFR 60, Appendix A. The observation period shall be 15 minutes or once the amount of time visible emissions are present has exceeded 1 minute, whichever time period is less. If the flare fails the visible emissions test, the permittee must follow manufacturer's repair instructions, if available, or best combustion engineering practices as outlined in the permittee's maintenance plan for the unit return it to compliant operation. All repair and maintenance activities must be recorded in a maintenance and repair log and made be available for inspection.	Once per calendar month	Report the presence or absence of visible emissions for each monitoring event, the duration of visible emissions if detected, and the date of each monitoring event. For flares failing the visible emissions test, report the repairs and/or maintenance activities conducted.

<sup>8</sup> Alternate methods may be used with the prior approval of LDEQ.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

**H. Flash Gas Emissions**

Acceptable flash gas calculation methods are outlined at <https://deq.louisiana.gov/page/flash-gas-calculation-methods>.

For purposes of this permit, the alternative calculation methods described on the above webpage are acceptable for 1.) new fields or facilities not yet in production for which testing cannot be performed; and 2.) existing vessels that do not meet the definition of “storage vessel with the potential for flash emissions.” Calculations should be performed so as to represent the “worst case” (i.e., highest emissions) scenario.

**I. Gasoline Dispensing Facilities**

Gasoline dispensing facilities (GDFs) eligible to be covered under this permit must have a monthly throughput of less than 10,000 gallons of gasoline.

Monthly throughput means the total volume of gasoline that is loaded into, or dispensed from, all gasoline storage tanks at each GDF during a month. Monthly throughput is calculated by summing the volume of gasoline loaded into, or dispensed from, all gasoline storage tanks at each GDF during the current day, plus the total volume of gasoline loaded into, or dispensed from, all gasoline storage tanks at each GDF during the previous 364 days, and then dividing that sum by 12.

Per 40 CFR 63.11111(h), monthly throughput is the total volume of gasoline loaded into, or dispensed from, all the gasoline storage tanks located at a *single* affected GDF. If a facility has two or more GDFs at separate locations, each GDF is treated as a separate affected source.

**J. Alternative Test Methods and Operating Parameters**

The permittee may not employ an alternative test method for methane detection technology as described in 40 CFR 60.5398b(d) unless EPA has deemed such alternative test method “broadly applicable.”

The permittee may not employ an alternative test method to demonstrate that a flare or enclosed combustion device reduces methane and VOC in the gases vented to the device by 95.0 percent by weight or greater as described in 40 CFR 60.5412b(d) unless EPA has deemed such alternative test method “broadly applicable.”

The permittee may not monitor an operating parameter other than those specified in 40 CFR 60.5417b(d)(1) through (3), (7), and (8), where applicable.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

**VI. REQUESTING COVERAGE UNDER THIS GENERAL PERMIT**

In order to request coverage under this general permit, an applicant should submit a completed “Application for Approval of Emissions of Air Pollutants from Minor Sources,” a completed “General Permit Applicability Questionnaire,” and the appropriate new permit application fee to the Office of Environmental Services. The application forms and instructions are available on LDEQ’s website at <https://www.deq.louisiana.gov/page/air-permit-applications>; the General Permit Applicability Questionnaire is available at <https://www.deq.louisiana.gov/page/minor-source-general-permits>.

An application to modify a site-specific air permit may also be used to request coverage under this general permit, provided that the “General Permit Applicability Questionnaire” accompanies the application.

Where facility-wide potential emissions of the following pollutants are less than or equal to the thresholds set forth in the table below, an applicant is authorized to construct and operate under the terms and conditions of this permit fourteen (14) days after the date the application is either postmarked or hand-delivered, or upon notification by LDEQ that coverage has been extended, whichever is earlier.

<u>Pollutant</u>	<u>Emissions (TPY)</u>
NO <sub>x</sub>	47.1
acrolein	2.1
benzene	1.7
formaldehyde	5.9

Authorization to construct and operate is not automatically granted if the application is materially incomplete (e.g., required information omitted, the application is unsigned, etc.); if the facility in question is not eligible for coverage under this permit; or if the applicant is specifically notified of this fact by LDEQ.

Permit Application Fees

Fee number 0040 shall apply except as follows:

1. For those facilities employing J-T equipment as part of a “forced” process as described in Subsection V.A of this general permit, fee number 0050 shall apply.
2. Fees for “midstream” facilities classified under SIC Code 1389 shall be as follows:
  - If total facility-wide horsepower<sup>9</sup> is less than 5000, fee number 1710 shall apply, and the fee shall be calculated in accordance with the table below.

---

<sup>9</sup> In determining facility-wide horsepower, exclude emergency generators and “back-up” units that cannot be operated simultaneously with a primary unit.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

Fee Number	Description	Annual Maintenance Fee	New Permit Application	Modified Permit Fees	
				Major	Minor
1710	Negotiated Fee for Minor Sources	291.00	1452.00	872.00	500.00

- If total facility-wide horsepower equals or exceeds 5000, fee number 1460 shall apply. It is presumed that if facility-wide horsepower exceeds 20,000, the facility will not qualify for this general permit.

Fee Number	Description	Annual Maintenance Fee	New Permit Application	Modified Permit Fees	
				Major	Minor
1460	Recip. Nat Gas Comp Per 100 H.P.: C) 5.000 to 20,000 H.P.	49.92	249.61	149.73	49.92

## VII. MODIFYING A FACILITY OPERATING UNDER THIS GENERAL PERMIT

As described in Section II, this general permit authorizes modification of crude oil and natural gas production facilities.

### A. Modifications: Situations Where Pre-Construction Approval Is Not Required

Where facility-wide potential emissions of the following pollutants (including the planned modifications) are less than or equal to the thresholds set forth in the table below, the owner or operator may modify the facility without prior approval of LDEQ, provided that the facility remains compliant with the established eligibility conditions.

Pollutant	Emissions (TPY)
NOx	47.1
acrolein	2.1
benzene	1.7
formaldehyde	5.9

Notwithstanding facility-wide potential emissions of the aforementioned pollutants, modifications which do not increase hourly or annual potential emissions of said pollutants may also be effected without prior approval of LDEQ.

Except as specified in Subsections VII.C and VII.D, within ten (10) calendar days after effecting any modification (generally commencement of construction) to a facility authorized to operate under this general permit, the permittee shall submit a completed "Application for Approval of Emissions of Air Pollutants from Minor Sources" and the appropriate modified permit fee to the Air Permits Division. The completed "Application for Approval of Emissions of Air Pollutants from Minor Sources" need only address the modifications effected at the facility.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

**B. Modifications: Situations Where Pre-Construction Approval Is Required**

Except as specified in Subsections VII.C or VII.D, **prior to** effecting any modification (generally commencement of construction) *not* described in Subsection VII.A, the permittee shall submit a completed “Application for Approval of Emissions of Air Pollutants from Minor Sources” and the appropriate modified permit fee to the Air Permits Division. The modification shall not be effected until approved by LDEQ.

The completed “Application for Approval of Emissions of Air Pollutants from Minor Sources” need only address the proposed modifications.

**C. Special Provisions for Certain Equipment Types**

Notwithstanding Subsection VII.B, addition or replacement of line heaters and heater treaters that do not represent a source of flash gas emissions, pneumatic pumps, pneumatic valves, blowcase vessels, fugitive components, and any insignificant activity based on size or emission rate (LAC 33:III.501.B.5, List A) not already listed in the facility’s permit application shall not require submittal of a completed “Application for Approval of Emissions of Air Pollutants from Minor Sources” to LDEQ, provided:

1. such modifications are disclosed in the next “Application for Approval of Emissions of Air Pollutants from Minor Sources” submitted pursuant to Subsection VII.A or VII.B;
2. the facility remains compliant with the established eligibility conditions; and
3. records of such modifications are retained on site or at another approved location for a minimum of two (2) years and made available for review by the Office of Environmental Compliance, Surveillance Division. Records of the addition or replacement of pneumatic valves and fugitive components shall not be required.

**D. “In Kind” Replacement of Equipment**

Notwithstanding Subsections VII.A and VII.B, replacement of an existing emissions unit not identified in Subsection VII.C with an “in-kind” unit shall not require submittal of a completed “Application for Approval of Emissions of Air Pollutants from Minor Sources” to LDEQ, provided:

1. the new unit does not result in an increase in hourly or annual potential emissions of any regulated pollutant;
2. the new unit is not subject to federal or state regulations to which the replaced emissions unit was not subject;
3. the new unit is an identical or functionally equivalent unit. A “functionally equivalent unit” means a component that serves the same purpose as the replaced component;
4. the replaced emissions unit is permanently removed from the facility or otherwise permanently disabled;
5. such modifications are disclosed in the next “Application for Approval of Emissions of Air Pollutants from Minor Sources” submitted pursuant to Subsection VII.A or VII.B; and

**MINOR SOURCE AIR GENERAL PERMIT  
AGENCY INTEREST NO. 158873  
ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

6. records of such modifications are retained on site or at another approved location for a minimum of two (2) years and made available for review by the Office of Environmental Compliance, Surveillance Division.

**VIII. REQUESTING TERMINATION OF COVERAGE UNDER THIS PERMIT**

The permittee shall notify the Air Permits Division using the “Application for Approval of Miscellaneous Permitting Actions” if operations at the facility permanently cease during the permit term. The application form and instructions are available on LDEQ’s website at <https://deq.louisiana.gov/page/air-permit-applications>.

If, in accordance with Section II, the permittee seeks permission to effect a modification rendering the facility ineligible for coverage under this general permit, it is *not* necessary to request termination of this general permit once a site-specific air permit is obtained.

**IX. RENEWAL OF COVERAGE UNDER THE GENERAL PERMIT**

Unless otherwise provided by LDEQ, coverage under the any renewed Minor Source Air General Permit for Crude Oil and Natural Gas Production shall automatically be extended to those facilities for which coverage under the general permit has previously been approved. A permit application to renew coverage as described in LAC 33:III.503.C.3 shall not be required.

**X. NAME/OWNER/OPERATOR CHANGES**

In the event of a name, owner, or operator change, the permittee shall notify the Office of Environmental Services in accordance with LAC 33:I.Chapter 19 using the “Louisiana Notification of Change Form (NOC-1).” The form and instructions are available on LDEQ’s website at <https://deq.louisiana.gov/page/public-participation-permit-support>.

In accordance with LAC 33:I.1903.A, the previous owner retains responsibility for compliance with all permit terms and conditions until the permit has been transferred.

**XI. EMISSIONS INVENTORY**

Notwithstanding the applicability provisions of LAC 33:III.919, the owner or operator of a facility located in one of the following parishes shall submit an annual Emissions Inventory (EI) as described in LAC 33:III.919 by the date set forth in the rule or as otherwise specified by LDEQ.

Ascension	Iberia	St. Helena	Tangipahoa
Assumption	Iberville	St. James	West Feliciana
East Baton Rouge	Livingston	St. John the Baptist	West Baton Rouge
East Feliciana	Pointe Coupee	St. Martin	

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

Re-designation of an Attainment Area to a Nonattainment Area

Notwithstanding the applicability provisions of LAC 33:III.919, if, during the term of this permit, any parish outside of the Baton Rouge Area is designated as an ozone nonattainment area by EPA, the owner or operator of a facility located in any such parish, or in any parish that adjoins such parish, shall submit an annual EI. In this event, the initial EI will be due in the year following the first *full* year of re-designation. For example, if a parish is designated as an ozone nonattainment area in August 2025 (the effective date as established by EPA), the initial EI shall be submitted in 2027 and disclose actual emissions during calendar year 2026.

Re-designation of a Nonattainment Area to an Attainment Area

If, during the term of this permit, any parish is re-designated as an ozone attainment area or otherwise ceases to adjoin an ozone nonattainment area, the need to submit an annual EI shall be dictated by LAC 33:III.919.

**XII. LABORATORY ANALYSES**

Laboratory procedures and analyses performed by commercial laboratories shall be conducted in accordance with the requirements set forth under the Laboratory Accreditation procedures established by LAC 33:I.Chapters 45-59. LDEQ will not accept data generated by commercial laboratories that are not accredited under this program for acceptable analytical methods to determine speciated analytes, and retesting will be required by an accredited laboratory. Information on the Environmental Laboratory Accreditation Program and a list of accredited labs is available on the LDEQ's website at <https://deq.louisiana.gov/page/la-lab-accreditation>.

**XIII. GENERAL COVERAGE**

**Continuation of an Expired General Permit**

If this permit is not reissued or replaced prior to the expiration date, it shall be administratively continued and remain in force and effect for permittees that were covered prior to its expiration. Any permittee who was granted coverage prior to the expiration date will automatically remain covered by the continued permit until the earlier of:

1. reissuance or replacement of this permit, at which time the permittee must comply with the requirements for obtaining coverage under the new permit;
2. issuance of a site-specific air permit to the facility; or
3. a formal decision by LDEQ not to reissue this general permit, at which time the permittee must seek coverage under a site-specific air permit. In any such notice not to reissue the general permit, LDEQ will establish a deadline for the submittal of an application for a site-specific air permit. LDEQ may grant additional time to

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

submit the application upon request of the applicant. Coverage under this general permit shall continue until such time as a site-specific air permit is approved. If a permittee fails to submit in a timely manner a site-specific air permit application as required by LDEQ, then the applicability of this permit to the individual permittee will be automatically terminated at the end of the day specified by LDEQ for application submittal.

**Requirement for a Site-Specific Permit**

Eligibility for this permit does not confer a vested right to coverage under the permit. LDEQ may require any person authorized by this permit to apply for and/or obtain a site-specific air permit. If LDEQ requires a permittee authorized to emit under this permit to apply for a site-specific air permit, LDEQ will notify the permittee in writing that a permit application is required. This notification will include a brief statement of the reasons for this decision, a statement setting a deadline for the permittee to submit the application, and a statement that on the effective date of issuance or denial of the site-specific air permit, coverage under this permit will automatically terminate. LDEQ may grant additional time to submit the application upon request of the applicant. If a permittee fails to submit in a timely manner a site-specific air permit application as required by LDEQ, then the applicability of this permit to the individual permittee will be automatically terminated at the end of the day specified by LDEQ for application submittal.

LDEQ's notification that coverage under a site-specific permit is required does not imply that the facility does not meet the eligibility requirements of this permit.

**Severability**

The provisions of this permit are severable, and if any provision of this permit, or the application of any provision of this permit to any circumstance, is held invalid, the application of such provision to other circumstances and the remainder of this permit shall not be affected thereby.

**Modification, Revocation and Reissuance, or Termination of Permit**

This permit may be modified, revoked and reissued, or terminated for cause. Upon modification or reissuance of this permit, the permittee shall comply with any new or modified requirements by any compliance dates established in the modified or reissued permit.

If there is evidence indicating that the air emissions authorized by this permit cause or have the reasonable potential to cause or contribute to a violation of a National Ambient Air Quality Standard (NAAQS) or Louisiana Ambient Air Standard (AAS), the facility may be required to obtain a site-specific permit or this permit may be modified to include more stringent limitations and/or requirements.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

**XIV. GENERAL CONDITIONS**

The following general conditions from LAC 33:III.537 apply, except as modified below.

<b>General Condition</b>	<b>Applicable</b>	<b>Comments</b>
I.	Yes.	Maximum facility-wide emissions authorized by this general permit are set forth in Section III of the permit. Site-specific emissions limitations are established by the permittee's application requesting coverage under this general permit. Exceedances of any limitations defined therein are addressed in General Condition III.
II.	Yes.	
III.	Yes.	This permit does not contain sections entitled "Emission Rates for Criteria Pollutants" and "Emission Rates for TAP/HAP and Other Pollutants." If emissions from an emissions unit are subsequently determined to be greater than those disclosed in a permit application, but facility-wide emissions remain within the limits set forth in Section III of this general permit, the owner or operator shall submit a revised application in accordance with Section VII of this general permit as soon as practicable, but no later than 30 calendar days after discovery of the discrepancy. In such situations, the owner or operator is not required to submit a report pursuant to General Condition XI <b>unless</b> an underlying federal or state standard has been violated. If a facility-wide emission limitation has been exceeded, a report must be submitted pursuant to General Condition XI.
IV.	Yes.	
V.	No.	
VI.	Yes.	
VII.	Yes.	
VIII.	No.	Testing and reporting deadlines are established by the Specific Requirements of this permit.
IX.	No.	See Section VII of this general permit and General Condition III.
X.	Yes.	
XI.	Yes.	See comment associated with General Condition III.
XII.	Yes.	
XIII.	Yes.	
XIV.	Yes.	
XV.	No.	
XVI.	Yes.	See Section X of this general permit.
XVII.	Yes.	Only General Condition XVII activities disclosed in the permit application are considered authorized discharges.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

General Condition	Applicable	Comments
XVIII.	See comment.	General Condition XVIII applies to the master general permit itself, but does not extend to the action of granting coverage under this general permit. According to LAC 33:III.513.A.3, LDEQ may "approve an owner or operator's application for authorization to operate under the general permit without repeating the public participation procedures. Such an approval shall not be a final permit action for purposes of judicial review regarding the terms and conditions of the general permit."
XIX.	No.	
XX.	Yes.	

In addition, the following additional general conditions apply:

- XXI. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.
- XXII. No person shall knowingly falsify, tamper with, or render inaccurate any monitoring device or method required to be maintained under this permit.
- XXIII. The permittee must take all reasonable steps to minimize or prevent any emissions in violation of this permit which have a reasonable likelihood of adversely affecting human health or the environment. The permittee shall also take all reasonable steps to minimize or correct any adverse impact on the environment resulting from noncompliance with the permit, including accelerated or additional monitoring as necessary to determine the nature and impact of the noncomplying emissions.
- XXIV. The permittee shall furnish to the Department, within a reasonable time to be specified by the Department of not less than 30 days, any information which the Department may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit or to determine compliance with this permit. The permittee shall also furnish to the Department, upon request, copies of records required to be kept by this permit.
- XXV. Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any applicable federal or state law or regulation. No condition of this permit shall release the permittee from any responsibility or requirements under other environmental statutes or regulations.

**MINOR SOURCE AIR GENERAL PERMIT**  
**AGENCY INTEREST NO. 158873**  
**ACTIVITY NO. PER20240001**

**CRUDE OIL AND NATURAL GAS PRODUCTION**

**XV. MODIFICATIONS TO MASTER GENERAL PERMIT**

With this action, LDEQ proposes to modify the general permit to:

- add the requirements of 40 CFR 60 Subpart OOOOb (Standards of Performance for Crude Oil and Natural Gas Facilities for Which Construction, Modification or Reconstruction Commenced After December 6, 2022), which was promulgated by EPA on March 8, 2024;
- establish legally and practically enforceable limits such that storage vessels for which construction, modification, or reconstruction commenced after December 6, 2022, with potential VOC and methane emissions of less than 6 and 20 tons per year, respectively, are not subject to 40 CFR 60 Subpart OOOOb;
- exclude facilities with centrifugal compressors, steam-assisted flares, and those that comply with an alternative means of emission limitation (AMEL) approved by EPA from being eligible for coverage under this general permit;
- add Subsection V.J to address alternative test methods and operating parameters; and
- update the verbiage of Specific Requirements to reflect the current wording of the referenced federal regulation.

Previous modifications to this general permit are addressed in Section VI of the SOB.

**XVI. PUBLIC NOTICE**

Request for public comment on this renewal and modification of the Minor Source Air General Permit for Crude Oil and Natural Gas Production was published on the department's website on July 31, 2024. On July 30, 2024, copies of the public notice were mailed to the individuals who have requested to be placed on the mailing list maintained by the Office of Environmental Services (OES). All public comments were considered prior to a final permit decision.

As specified in LAC 33:III.513.A.3, the permitting authority may approve an owner or operator's application for authorization to operate under this general permit without repeating the public participation procedures.

Modifications to this general permit made solely to reflect new or revised federal and/or state regulations to which eligible facilities may be subject do not require public notice.

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### **PCS 0001 Fugitive Emissions**

#### **FUG 0001 - Fugitive Emissions - All Facilities**

1 [LAC 33:III.1305]

Prevent particulate matter from becoming airborne by taking all reasonable precautions. These precautions shall include, but not be limited to, those specified in LAC 33:III.1305.A.1-7.

2 [LAC 33:III.2111]

Equip all rotary pumps and compressors handling volatile organic compounds having a true vapor pressure of 1.5 psia or greater at handling conditions with mechanical seals or other equivalent equipment.

#### **FUG 0002 - Fugitive Emissions - Facilities Extracting Natural Gas Liquids from Field Gas by a "Forced" J-T Process and Subject to NSPS KKK**

3 [40 CFR 60.632(a)]

Comply with the requirements specified in 40 CFR 60.482-1(a), (b), and (d) and 40 CFR 60.482-2 through 60.482-10, except as provided in 40 CFR 60.633, as soon as practicable, but no later than 180 days after initial startup. Subpart KKK. [40 CFR 60.632(a)]

4 [40 CFR 60.632(d)]

Comply with the provisions of 40 CFR 60.485 except as provided in 40 CFR 60.632(f) and 60.633(h). Subpart KKK. [40 CFR 60.632(d)]

5 [40 CFR 60.632(e)]

Comply with the provisions of 40 CFR 60.486 and 60.487 except as provided in 40 CFR 60.633, 60.635, and 60.636. Subpart KKK. [40 CFR 60.632(e)]

6 [40 CFR 60.632(f)]

Demonstrate that a piece of equipment is not in VOC service or in wet gas service by using the specified methods. Subpart KKK. [40 CFR 60.632(f)]

7 [40 CFR 60.635(c)]

Compressors: Equipment/operational data recordkeeping by logbook at the approved frequency. Record and keep information and data used to demonstrate that a reciprocating compressor is in wet gas service in a readily accessible location for use in determining exemptions as provided in 40 CFR 60.633(f). Subpart KKK. [40 CFR 60.635(c)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit

Air - Minor Gen Permit Oil and Gas Mod

## **PCS 0002 Miscellaneous Fuel Burning Equipment**

### **EQT\_0011 - Heater Treaters**

8 [LAC 33:III.1313.C]

Total suspended particulate  $\leq 0.6 \text{ lb/MMBTU}$  of heat input (Complies by using sweet natural gas as fuel).  
Which Months: All Year Statistical Basis: None specified

### **EQT\_0012 - Line Heaters**

9 [LAC 33:III.1313.C]

Total suspended particulate  $\leq 0.6 \text{ lb/MMBTU}$  of heat input (Complies by using sweet natural gas as fuel).  
Which Months: All Year Statistical Basis: None specified

**SPECIFIC REQUIREMENTS**

AI ID: 158873 - Minor Source Air General Permit for Crude Oil &amp; Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
 Air - Minor Gen Permit-Oil and Gas Mod

**PCS 0003 Amine Sweetening Units****EQT 0008 - Amine Sweetening Units - Regenerator Vents**

10 [40 CFR 60.647(c)]

Constructed, Reconstructed, or Modified After January 20, 1984, and on or Before August 23, 2011: To certify that a facility is exempt from the control requirements of Subpart L.L.I., each owner or operator of a facility with a design capacity less than 2 LT/D of H<sub>2</sub>S in the acid gas (expressed as sulfur) shall keep, for the life of the facility, an analysis demonstrating that the facility's design capacity is less than 2 LT/D of H<sub>2</sub>S expressed as sulfur. [40 CFR 60.647(c)]

Record and retain at the site sufficient data to show annual potential sulfur dioxide emissions.

Facilities located in Pointe Coupee or Calcasieu Parish: Maintain records to demonstrate that the criteria are being met for any exemption claimed. Maintain records on the premises for at least two years and make such information available to representatives of the Louisiana Department of Environmental Quality upon request. This requirement shall be applicable even if potential VOC emissions are less than 50 tons per year.

**EQT 0013 - Amine Reboilers**

13 [LAC 33.III.1513.C]

12 [LAC 33.III.2115.K]

Total suspended particulate <= 0.6 lb/MMBTU of heat input (Complies by using sweet natural gas as fuel).  
 Which Months: All Year Statistical Basis: None specified

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

## **PCS 0004 Glycol Dehydration Units**

### **EQT 0003 - Glycol Dehydration Unit Process Vents Constructed Prior to October 20, 1994 Subject to LAC 33:III.2116**

14 [LAC 33:III.2116.B.1.a] VOC, Total  $\geq$  70 % reduction. If the control device is a condenser, annually achieve an average final exhaust temperature less than 110 degrees F. Percent reduction shall be demonstrated by using the methods found in LAC 33:III.2116.D.

Which Months: All Year Statistical Basis: None specified

Glycol dehydration units (using a flare to control emissions): Ensure destruction of emissions to the flare stack by maintaining the heat content of the flare gas above 300 BTU/scf and by documenting daily visual observations of the continuous presence of a flame. Perform a gas analysis representative of the flare stream, showing the heat content, annually and make available for inspection.

15 [LAC 33:III.2116.B.3] Glycol dehydration units (using a condenser to control emissions): Maintain a record of the final exhaust temperature and time observed recorded twice a week on different days during daylight hours; and maintain a record of all temperature exceedances greater than or equal to 120 degrees F, the date of each temperature exceedance, and a brief explanation describing the circumstances of the temperature exceedance.

Glycol dehydration units: Keep records of the results of any testing conducted in accordance with LAC 33:III.2116.D, and keep records of the date of any maintenance and repair of the required control device and the duration of uncontrolled emissions during such activities. As an alternative to documenting daily visual observations of a flame as described in LAC 33:III.2116.B.3, the permittee may install, maintain, and operate according to manufacturer's specifications a heat sensing device to detect the continuous presence of a flame.

### **EQT 0014 - Glycol Reboilers**

19 [LAC 33:III.1101.B] Opacity  $\leq$  20 percent, except that such emissions may have an average opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes.

Which Months: All Year Statistical Basis: Six-minute average

Total suspended particulate  $\leq$  0.6 lb/MMBTU of heat input.

Which Months: All Year Statistical Basis: None specified

### **EQT 0021 - Glycol Dehydration Unit Process Vents Constructed On or After October 20, 1994, Subject to LAC 33:III.2116**

21 [LAC 33:III.2116.B.2] VOC, Total  $\geq$  85 % reduction using a control device. Demonstrate percent reduction using the methods found in LAC 33:III.2116.D.

Which Months: All Year Statistical Basis: None specified

Glycol dehydration units (using a flare to control emissions): Ensure destruction of emissions to the flare stack by maintaining the heat content of the flare gas above 300 BTU/scf and by documenting daily visual observations of the continuous presence of a flame. Perform a gas analysis representative of the flare stream, showing the heat content, annually and make available for inspection.

22 [LAC 33:III.2116.B.3] Glycol dehydration units: Keep records of the results of any testing conducted in accordance with LAC 33:III.2116.D, and keep records of the date of any maintenance and repair of the required control device and the duration of uncontrolled emissions during such activities. As an alternative to documenting daily visual observations of a flame as described in LAC 33:III.2116.B.3, the permittee may install, maintain, and operate according to manufacturer's specifications a heat sensing device to detect the continuous presence of a flame.

### **EQT 0023 - Glycol Dehydration Unit Process Vents - Exempt from LAC 33:III.2116**

25 [LAC 33:III.2116.C.2] Glycol dehydration units (requesting exemption from LAC 33:III.2116): Demonstrate to DEQ, using method or methods found in LAC 33:III.2116.D, that the total uncontrolled VOC emissions from the glycol dehydrator are not in excess of nine tons per year.

**EQT 0023 - Glycol Dehydration Unit Process Vents - Exempt from LAC 33:III.2116**

26 [LAC 33:III.2116.F.4]  
Glycol dehydration units (requesting exemption from LAC 33:III.2116): Keep records of total hours of operation on an annual basis if claiming an exemption from LAC 33:III.2116 under LAC 33:III.2116.C.1; OR keep records of the actual throughput per day and the glycol circulation rate if claiming an exemption from LAC 33:III.2116 under LAC 33:III.2116.C.2.

**EQT 0026 - All Glycol Dehydration Unit Process Vents**

27 [40 CFR 63.774(d)]  
Equipment/operational data recordkeeping by electronic or hard copy at the approved frequency. Keep records of the information specified in 40 CFR 63.774(d)(i) or (d)(1)(ii), as applicable. Subpart HH. [40 CFR 63.774(d)]

28 [LAC 33:III.501.C.6]  
Glycol dehydration units for which construction commenced after September 15, 2010, ONLY: No later than 180 days after operations commence, the owner or operator shall recalculate emissions from the glycol dehydration unit using a site-specific wet gas analysis from a sample collected upstream of the dehydration system. These records shall be retained on site and made available for inspection by the Office of Environmental Compliance, Surveillance Division. If emissions are in excess of previous estimates, the owner of operator shall follow the appropriate procedures described in General Condition III of the general permit.

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

## PCS 0005 Natural Gas Internal Combustion Engines

### EQT\_0001 - Natural Gas ICEs - Engines Subject to Chapter 22

- 29 [LAC 33:III.2201.D.1]      Lean burn engines  $\geq$  1500 hp: Nitrogen oxides  $\leq$  4 g/BHP-hr.  
Which Months: May-Sep Statistical Basis: Thirty-day rolling average
- 30 [LAC 33:III.2201.D.1]      Rich burn engines  $\geq$  300 hp: Nitrogen oxides  $\leq$  2 g/BHP-hr.  
Which Months: May-Sep Statistical Basis: Thirty-day rolling average
- 31 [LAC 33:III.2201.G.2]      Perform NOx emissions testing for all point sources that are subject to the emission limitations of LAC 33:III.2201.D or used in one of the alternative plans of LAC 33:III.2201.E, as specified in LAC 33:III.2201.G.2 through G.7. Test results must demonstrate that actual NOx emissions are in compliance with the appropriate limits of LAC 33:III.2201.E. Chapter 22. Also measure CO, SO2, PM10, and VOC if modifications could cause an increase in emissions of any of these compounds.
- 32 [LAC 33:III.2201.H.10]      Test NOx emissions after each occurrence of catalyst replacement. Maintain documentation on-site, if practical, of the date, the person doing the test, and the test results. Make documentation available for inspection upon request.
- Option 1: Fuel monitored by totalizer continuously. Monitor fuel usage with a totalizing fuel meter.  
Which Months: May-Sep Statistical Basis: None specified
- Option 1: Operate the engine within the fuel limits established during the initial compliance run.
- Option 1: Perform annual testing for NOx and CO with an approved portable analyzer.
- Option 1: Perform triennial stack testing for NOx and CO in accordance with the methods specified in LAC:III.2201.G.5.
- Option 2: Carbon monoxide monitored by the regulation's specified method(s) continuously. Monitor carbon monoxide using a CO monitor.  
Which Months: May-Sep Statistical Basis: None specified
- Option 2: Fuel monitored by totalizer continuously. Monitor fuel usage with a totalizing fuel meter.  
Which Months: May-Sep Statistical Basis: None specified
- Option 2: Nitrogen oxides monitored by continuous emission monitor (CEM) continuously.  
Which Months: May-Sep Statistical Basis: None specified
- Option 2: Diluent - either Oxygen or Carbon dioxide monitored by the regulation's specified method(s) continuously. Monitor oxygen or carbon dioxide using a diluent monitor in accordance with the requirements of LAC 33:III.2201.H.1.b.ii.  
Which Months: May-Sep Statistical Basis: None specified
- Option 3: Nitrogen oxides monitored by the regulation's specified method(s) continuously. Predict NOx, diluent (O<sub>2</sub> or CO<sub>2</sub>), and CO emissions for each affected point source using a PEMS. Operate PEMS in accordance with the requirements of LAC 33:III.2201.H.1.b.v.  
Which Months: May-Sep Statistical Basis: None specified
- Submit Notification: Due at least 30 days prior to any compliance testing conducted under LAC 33:III.2201.G and any CEMS or PEMS performance evaluation conducted under LAC 33:III.2201.H in order to give DEQ an opportunity to conduct a pretest meeting and observe the emission testing.
- 43 [LAC 33:III.2201.I.1]      Submit test results: Due within 60 days after completing the emission testing required in LAC 33:III.2201.I.1.
- 44 [LAC 33:III.2201.I.2]      Submit report: Due within 90 days of the end of each quarter for any noncompliance of the applicable emission limitations of LAC 33:III.2201.D or E. Include the information specified in LAC 33:III.2201.I.2.a through I.2.d.
- 45 [LAC 33:III.2201.I.]      Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Maintain records of the information specified in LAC 33:III.2201.I.3 and I.4 as applicable.

**SPECIFIC REQUIREMENTS**  
**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**  
Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

**EQT 0001 - Natural Gas ICEs - Engines Subject to Chapter 22**

- 46 [LAC 33:III.2201.J.2] Complete all initial compliance testing, specified by LAC 33:II.2201.G, for equipment modified with NOx reduction controls or a NOx monitoring system to meet the provisions of LAC 33:II. Chapter 22 within 60 days of achieving normal production rate or after the end of the shake down period, but in no event later than 180 days after initial start-up, except as provided in LAC 33:III.2202.
- Option 1: The owner or operator shall include NOx emitted during periods of start-up and shutdown for purposes of determining compliance with the emission factors set forth in Subsection D.
- Option 2: The owner or operator shall operate and maintain each affected point source, including any associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions.
- Option 2: Minimize the start-up time of stationary internal combustion engines to a period needed for the appropriate and safe loading of the engine, not to exceed 30 minutes.
- Option 2: Maintain records of the calendar date, time, and duration of each start-up and shutdown.
- Option 2: Maintain records of the type(s) and amount(s) of fuels used during each start-up and shutdown.
- Option 2: The records required by Subparagraphs K.3.e and f of this Section shall be kept for a period of at least five years and shall be made available upon request by authorized representatives of the department.

**EQT 0015 - Natural Gas ICEs - Engines Subject to NSPS JJJJ**

- 53 [40 CFR 60.4233(a)] Stationary SI ICE with a maximum engine power less than or equal to 25 HP manufactured on or after July 1, 2008. Comply with the emission standards in 40 CFR 60.4231(a) for the stationary SI ICE. [40 CFR 60.4233(a)]
- 54 [40 CFR 60.4233(d)] Owners and operators of stationary SI ICE with a maximum engine power greater than 25 HP and less than 100 HP must comply with the emission standards for field testing in 40 CFR 1048.101(c) for their non-emergency stationary SI ICE and with the emission standards in Table 1 to Subpart JJJJ for their emergency stationary SI ICE. Owners and operators of stationary SI ICE with a maximum engine power greater than 25 HP and less than 100 HP manufactured prior to January 1, 2011, that were certified to the standards in Table 1 to Subpart JJJJ applicable to engines with a maximum engine power greater than or equal to 100 HP and less than 500 HP, may optionally choose to meet those standards. [40 CFR 60.4233(d)]
- 55 [40 CFR 60.4233(e)] Owners and operators of stationary SI ICE with a maximum engine power greater than or equal to 100 HP must comply with the emission standards in Table 1 to Subpart JJJJ for their stationary SI ICE. For owners and operators of stationary SI ICE with a maximum engine power greater than or equal to 100 HP manufactured prior to January 1, 2011, that were certified to the certification emission standards in 40 CFR part 1048 applicable to engines that are not severe duty engines, if such stationary SI ICE was certified to a carbon monoxide (CO) standard above the standard in Table 1 to Subpart JJJJ, then the owners and operators may meet the CO certification (not field testing) standard for which the engine was certified. [40 CFR 60.4233(e)]
- 56 [40 CFR 60.4233(f)] Owners and operators of any modified or reconstructed stationary SI ICE subject to Subpart JJJJ must meet the requirements as specified in 40 CFR 60.4233(f)(1)-(5). [40 CFR 60.4233(f)]
- 57 [40 CFR 60.4233(g)] Owners and operators of stationary SI wellhead gas ICE engines may petition the Administrator for approval on a case-by-case basis to meet emission standards no less stringent than the emission standards that apply to stationary emergency SI engines greater than 25 HP and less than 130 HP due to the presence of high sulfur levels in the fuel, as specified in Table 1 to Subpart JJJJ. The request must, at a minimum, demonstrate that the fuel has high sulfur levels that prevent the use of aftertreatment controls and also that the owner has reasonably made all attempts possible to obtain an engine that will meet the standards without the use of aftertreatment controls. The petition must request the most stringent standards reasonably applicable to the engine using the fuel. [40 CFR 60.4233(g)]
- 58 [40 CFR 60.4233(h)] Owners and operators of stationary SI ICE that are required to meet standards that reference 40 CFR 1048.101 must, if testing their engines in use, meet the standards in that section applicable to field testing, except as indicated in 40 CFR 60.4233(e). [40 CFR 60.4233(h)]

**SPECIFIC REQUIREMENTS**  
**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**

Activity Number: PER2024001  
Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

**EQT 0015 - Natural Gas ICEs - Engines Subject to NSPS JJJ**

- 59 [40 CFR 60.4234] Owners and operators of stationary SI ICE must operate and maintain stationary SI ICE that achieve the emission standards as required in 40 CFR 60.4233 over the entire life of the engine.  
After July 1, 2010, owners and operators may not install stationary SI ICE with a maximum engine power of less than 500 HP that do not meet the applicable requirements in 40 CFR 60.4233. [40 CFR 60.4236(a)]
- 61 [40 CFR 60.4236(b)] After July 1, 2009, owners and operators may not install stationary SI ICE with a maximum engine power of greater than or equal to 500 HP that do not meet the applicable requirements in 40 CFR 60.4233, except that lean burn engines with a maximum engine power greater than or equal to 500 HP and less than 1350 HP that do not meet the applicable requirements in 40 CFR 60.4233 may not be installed after January 1, 2010. [40 CFR 60.4236(b)]
- For emergency stationary SI ICE with a maximum engine power of greater than 25 HP, owners and operators may not install engines that do not meet the applicable requirements in 40 CFR 60.4233 after January 1, 2011. [40 CFR 60.4236(c)]
- In addition to the requirements specified in 40 CFR 60.4231 and 60.4233, it is prohibited to import stationary SI ICE less than or equal to 25 HP that do not meet the applicable requirements specified in 40 CFR 60.4236(a), (b), and (c), after the date specified in 40 CFR 60.4236 (a), (b), and (c). [40 CFR 60.4236(d)]
- The requirements of 40 CFR 60.4236 do not apply to owners and operators of stationary SI ICE that have been modified or reconstructed, and they do not apply to engines that were removed from one existing location and reinstalled at a new location. [40 CFR 60.4236(e)]
- Starting on July 1, 2010, if the emergency stationary SI internal combustion engine that is greater than or equal to 500 HP that was built on or after July 1, 2010, does not meet the standards applicable to non-emergency engines, the owner or operator must install a non-resettable hour meter. [40 CFR 60.4237(a)]
- Starting on January 1, 2011, if the emergency stationary SI internal combustion engine that is greater than or equal to 130 HP and less than 500 HP that was built on or after January 1, 2011, does not meet the standards applicable to non-emergency engines, the owner or operator must install a non-resettable hour meter upon startup of your emergency engine. [40 CFR 60.4237(c)]
- If you are an owner or operator of a stationary SI internal combustion engine that is manufactured after July 1, 2008, and must comply with the emission standards specified in 40 CFR 60.4233(a)-(c), you must comply by purchasing an engine certified to the emission standards in 40 CFR 60.4231(a)-(c), as applicable, for the same engine class and maximum engine power. In addition, you must meet one of the requirements specified in 40 CFR 60.4243(a)(1) and (2). [40 CFR 60.4243(a)]
- If you are an owner or operator of a stationary SI internal combustion engine and must comply with the emission standards specified in 40 CFR 60.4233(d) or (e), you must demonstrate compliance according to one of the methods specified in 40 CFR 60.4243(b)(1) and (2). [40 CFR 60.4243(b)]
- If you are an owner or operator of a stationary SI internal combustion engine that must comply with the emission standards specified in 40 CFR 60.4233(f), you must demonstrate compliance according to 40 CFR 60.4243(b)(2)(i) or (ii), except that if you comply according to 40 CFR 60.4243(b)(2)(i), you demonstrate that your non-certified engine complies with the emission standards specified in 40 CFR 60.4233(f). [40 CFR 60.4243(c)]

**SPECIFIC REQUIREMENTS****AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
 Air - Minor Gen Permit-Oil and Gas Mod

**EQT\_0015 - Natural Gas ICEs - Engines Subject to NSPS JJJJ**

71 [40 CFR 60.4243(d)]

If you own or operate an emergency stationary ICE, operate the emergency stationary ICE according to the requirements in 40 CFR 60.4243(d)(1), (d)(2)(i), and (d)(3). In order for the engine to be considered an emergency stationary ICE under Subpart JJJ, any operation other than emergency operation, maintenance and testing, and operation in non-emergency situations for 50 hours per year, is prohibited. If you do not operate the engine according to these requirements, the engine will not be considered an emergency engine under Subpart JJJ and must meet all requirements for non-emergency engines.

(1) There is no time limit on the use of emergency stationary ICE in emergency situations.

(2) Emergency stationary ICE may be operated for maintenance checks and readiness testing for a maximum of 100 hours per calendar year, provided that the tests are recommended by federal, state or local government, the manufacturer, the vendor, or the insurance company associated with the engine. The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or operator maintains records indicating that federal, state, or local standards require maintenance and testing of emergency ICE beyond 100 hours per calendar year.

(3) Emergency stationary ICE may be operated for up to 50 hours per calendar year in non-emergency situations. The 50 hours of operation in non-emergency situations are counted as part of the 100 hours per calendar year for maintenance and testing. [40 CFR 60.4243(d)]

Owners and operators of stationary SI natural gas fired engines may operate their engines using propane for a maximum of 100 hours per year as an alternative fuel solely during emergency operations, but must keep records of such use. If propane is used for more than 100 hours per year in an engine that is not certified to the emission standards when using propane, the owners and operators are required to conduct a performance test to demonstrate compliance with the emission standards of 40 CFR 60.4233. [40 CFR 60.4243(e)] If you are an owner or operator of a stationary SI internal combustion engine that is less than or equal to 500 HP and you purchase a non-certified engine or you do not operate and maintain your certified stationary SI internal combustion engine and control device according to the manufacturer's written emission-related instructions, you are required to perform initial performance testing as indicated in 40 CFR 60.4243, but you are not required to conduct subsequent performance testing unless the stationary engine undergoes rebuild, major repair or maintenance. Engine rebuilding means to overhaul an engine or to otherwise perform extensive service on the engine (or on a portion of the engine or engine system). For the purpose of 40 CFR 60.4243(f), perform extensive service means to disassemble the engine (or portion of the engine or engine system), inspect and/or replace many of the parts, and reassemble the engine (or portion of the engine or engine system) in such a manner that significantly increases the service life of the resultant engine. [40 CFR 60.4243(f)] It is expected that air-to-fuel ratio controllers will be used with the operation of three-way catalysts/non-selective catalytic reduction. The AFR controller must be maintained and operated appropriately in order to ensure proper operation of the engine and control device to minimize emissions at all times. [40 CFR 60.4243(g)]

If you are an owner/operator of an stationary SI internal combustion engine with maximum engine power greater than or equal to 500 HP that is manufactured after July 1, 2007 and before July 1, 2008, and must comply with the emission standards specified in 40 CFR 60.4233(b) or (c), you must comply by one of the methods specified in 40 CFR 60.4243(h)(1)-(4). [40 CFR 60.4243(h)] If you are an owner or operator of a modified or reconstructed stationary SI internal combustion engine and must comply with the emission standards specified in 40 CFR 60.4243(i), you must demonstrate compliance according to one of the methods specified in 40 CFR 60.4243(h)(1) or (2). [40 CFR 60.4243(i)]

Owners and operators of stationary SI ICE who conduct performance tests must follow the procedures in 40 CFR 60.4244(a)-(f). [40 CFR 60.4245(a)] Owners and operators of all stationary SI ICE must keep records of the information in 40 CFR 60.4245(a)(1)-(4). [40 CFR 60.4245(a)]

**SPECIFIC REQUIREMENTS**  
**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

**EQT\_0015 - Natural Gas ICEs - Engines Subject to NSPS JJJ**

79 [40 CFR 60.4245(b)]  
For all stationary SI emergency ICE greater than or equal to 500 HP manufactured on or after July 1, 2010, that do not meet the standards applicable to non-emergency engines, the owner or operator of must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. For all stationary SI emergency ICE greater than or equal to 130 HP and less than 500 HP manufactured on or after July 1, 2011, that do not meet the standards applicable to non-emergency engines, the owner or operator of must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. For all stationary SI emergency ICE greater than 25 HP and less than 130 HP manufactured on or after July 1, 2008, that do not meet the standards applicable to non-emergency engines, the owner or operator of must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. The owner or operator must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. [40 CFR 60.4245(b)]

80 [40 CFR 60.4245(c)]  
Owners and operators of stationary SI ICE greater than or equal to 500 HP that have not been certified by an engine manufacturer to meet the emission standards in 40 CFR 60.4231 must submit an initial notification as required in 40 CFR 60.7(a)(1). The notification must include the information in 40 CFR 60.4245(c)(1)-(5). [40 CFR 60.4245(c)]

81 [40 CFR 60.4245(d)]  
Owners and operators of stationary SI ICE that are subject to performance testing must submit a copy of each performance test as conducted in 40 CFR 60.4244 within 60 days after the test has been completed. Performance test reports using EPA Method 18, EPA Method 320, or ASTM D6348-03 (incorporated by reference—see 40 CFR 60.17) to measure VOC require reporting of all QA/QC data. For Method 18, report results from sections 8.4 and 11.1.1.4; for Method 320, report results from sections 8.6.2, 9.0, and 13.0; and for ASTM D6348-03 report results of all QA/QC procedures in Annexes 1-7. [40 CFR 60.4245(d)]

82 [40 CFR 60.4246]  
(a) Table 3 to Subpart JJJ shows which parts of the General Provisions in 40 CFR 60.1 through 60.19 apply to you  
(b) The provisions of 40 CFR 1068.10 and 1068.11 apply for engine manufacturers. For others, the general confidential business information (CBI) provisions apply as described in 40 CFR part 2.

**EQT\_0016 - Natural Gas ICEs >= 500 hp & Operating > 720 Hours in Any 6-Month Period and Not Subject to NSPS JJJ or Chapter 22**

83 [LAC 33:III.501.C.6]  
Conduct a performance/emissions test: Due within 180 days after initial startup (or restart-up after modification), or within 60 days after achieving normal production rate or end of the shakedown period, whichever is earliest. The stack test's purpose is to verify potential emissions of the emissions unit. Repeat the test after each major engine overhaul. Test methods and procedures shall be in accordance with New Source Performance Standards. 40 CFR 60, Appendix A, Method 7E - Determination of Nitrogen Oxides Emissions from Stationary Sources and Method 10 - Determination of Carbon Monoxide Emissions from Stationary Sources. Conduct each test run within 80 percent of maximum permitted load, or within 10 percent of 100 percent maximum achievable load. Use alternate stack test methods only with the prior approval of the Office of Environmental Services. As required by LAC 33:III.913, provide necessary sampling ports in stacks or ducts and such other safe and proper sampling and testing facilities for proper determination of the emission limits.

84 [LAC 33:III.501.C.6]  
Equipment/operational data recordkeeping by electronic or hard copy semianually (annually if the ICE is equipped with catalytic controls). Recorded parameters are NOx, CO, and O2 concentrations in the stack gas obtained during semianual (or annual) testing.  
Stack gas concentration: Carbon monoxide monitored by portable analyzer semianually (six months after the stack test or previous semianual test, plus or minus 30 days). Maintain concentrations of CO in a range that demonstrates compliance with permit limits.

Calibrate portable analyzers before each test using a known reference gas sample. CO may be monitored annually (twelve months after the stack test or previous annual test, plus or minus 30 days) if the ICE is equipped with catalytic controls.  
Which Months: All Year Statistical Basis: None specified

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### **EQT 0016 - Natural Gas ICEs >= 500 hp & Operating > 720 Hours in Any 6-Month Period and Not Subject to NSPS JJJJ or Chapter 22**

86 [LAC 33.III.501.C.6]

Stack gas concentration: Nitrogen oxides monitored by portable analyzer semiannually (six months after the stack test or previous semiannual test, plus or minus 30 days). Maintain concentrations of NOx in a range that demonstrates compliance with permit limits. Calibrate portable analyzers before each test using a known reference gas sample. NOx may be monitored annually (twelve months after the stack test or previous annual test, plus or minus 30 days) if the ICE is equipped with catalytic controls.

Which Months: All Year Statistical Basis: None specified

Stack gas concentration: Oxygen monitored by portable analyzer semiannually (six months after the stack test or previous semiannual test, plus or minus 30 days). Maintain concentrations of O<sub>2</sub> in the same range as during the initial stack test. Calibrate portable analyzers before each test using a known reference gas sample. O<sub>2</sub> may be monitored annually (twelve months after the stack test or previous annual test, plus or minus 30 days) if the ICE is equipped with catalytic controls.

Which Months: All Year Statistical Basis: None specified

Submit notification: Due at least 30 days prior to any LDEQ required performance/emissions test to the Office of Environmental Services, to provide the opportunity to conduct a pretest meeting and observe the emission testing.

Submit report: Due within 60 days after performance/emissions test. Submit emissions test results to the Office of Environmental Services.

The test results summary shall include any necessary conversion into the units of any applicable standard (e.g., lb/hr, g/hp-hr).

### **EQT 0019 - All Natural Gas ICEs**

90 [LAC 33.III.1311.C]

Opacity <= 20 percent, except emissions may have an average opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes (Complies by using sweet natural gas as fuel).

Which Months: All Year Statistical Basis: Six-minute average

### **EQT 0031 - All Natural Gas ICEs for Which Construction or Reconstruction Commenced On or After June 12, 2006**

91 [40 CFR 63.6590(c)(1)]

Meet the requirements of 40 CFR 63 by meeting the requirements 40 CFR Subpart JJJJ. No further requirements apply to such engines under 40 CFR 63. Subpart ZZZZ. [40 CFR 63.6590(c)(1)]

### **EQT 0036 - Natural Gas ICEs for Which Construction or Reconstruction Commenced Before June 12, 2006**

92 [40 CFR 63.6595(a)(1)]

If you have an existing stationary SI RICE located at an area source of HAP emissions, you must comply with the applicable emission limitations, operating limitations, and other requirements no later than October 19, 2013. [40 CFR 63.6595(a)(1)]  
If you own or operate an affected source, you must meet the applicable notification requirements in 40 CFR 63.6645 and in 40 CFR part 63, subpart A. [40 CFR 63.6595(c)]

Comply with the requirements in Table 2d to Subpart ZZZZ that apply to you. [40 CFR 63.6603(a)]

An existing non-emergency SI 4SLB and 4SRB stationary RICE with a site rating of more than 500 HP located at area sources of HAP must meet the definition of remote stationary RICE in 40 CFR 63.6675 on the initial compliance date for the engine, October 19, 2013, in order to be considered a remote stationary RICE under Subpart ZZZZ. Owners and operators of existing non-emergency SI 4SLB and 4SRB stationary RICE with a site rating of more than 500 HP located at area sources of HAP that meet the definition of remote stationary RICE in 40 CFR 63.6675 as of October 19, 2013, must evaluate the status of their stationary RICE every 12 months. Owners and operators must keep records of the initial and annual evaluation of the status of the engine. If the evaluation indicates that the stationary RICE no longer meets the definition of remote stationary RICE in 40 CFR 63.6675 of Subpart ZZZZ, the owner or operator must comply with all of the requirements for existing non-emergency SI 4SLB and 4SRB stationary RICE with a site rating of more than 500 HP located at area sources of HAP that are not remote stationary RICE within 1 year of the evaluation. [40 CFR 63.6603(f)]

**SPECIFIC REQUIREMENTS**  
**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**

**Activity Number: PER2024001**  
**Permit Number: MSOG Master Gen Permit**  
**Air - Minor Gen Permit-Oil and Gas Mod**

**EQT\_0036 - Natural Gas ICEs for Which Construction or Reconstruction Commenced Before June 12, 2006**

96 [40 CFR 63.6605]

You must be in compliance with the emission limitations, operating limitations, and other requirements in Subpart ZZZZ that apply to you at all times. At all times you must operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require you to make any further efforts to reduce emissions if levels required by this standard have been achieved. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.

97 [40 CFR 63.6612]

You must conduct any initial performance test or other initial compliance demonstration according to Tables 4 and 5 to Subpart ZZZZ that apply to you within 180 days after the compliance date that is specified for your stationary RICE in 40 CFR 63.6595 and according to the provisions in 40 CFR 63.7(a)(2). An owner or operator is not required to conduct an initial performance test on a unit for which a performance test has been previously conducted, but the test must meet all of the conditions described in 40 CFR 63.6612(b)(1)-(4).

98 [40 CFR 63.6615]

If you must comply with the emission limitations and operating limitations, you must conduct subsequent performance tests as specified in Table 3 of Subpart ZZZZ.

99 [40 CFR 63.6620(a)]

You must conduct each performance test in Tables 3 and 4 of Subpart ZZZZ that applies to you. [40 CFR 63.6620(a)]  
Each performance test must be conducted according to the requirements that Subpart ZZZZ specifies in Table 4. If you own or operate a non-operational stationary RICE that is subject to performance testing, you do not need to start up the engine solely to conduct the performance test. Owners and operators of a non-operational engine can conduct the performance test when the engine is started up again. [40 CFR 63.6620(b)]

100 [40 CFR 63.6620(b)]

Conduct three separate test runs for each performance test required in 40 CFR 63.6620, as specified in 40 CFR 63.7(e)(3). Each test run must last at least 1 hour, unless otherwise specified in Subpart ZZZZ. [40 CFR 63.6620(d)]

101 [40 CFR 63.6620(d)]

Use Equation 1 of 40 CFR 63.6620(e)(1) to determine compliance with the percent reduction requirement. Normalize the CO, THC, or formaldehyde concentrations at the inlet and outlet of the control device to a dry basis and to 15 percent oxygen, or an equivalent percent carbon dioxide (CO2). If pollutant concentrations are to be corrected to 15 percent oxygen and CO2 concentration is measured in lieu of oxygen concentration measurement, a CO2 correction factor is needed. Calculate the CO2 correction factor as described in 40 CFR 63.6620(e)(2)(i)-(iii). [40 CFR 63.6620(e)]

102 [40 CFR 63.6620(e)]

If you comply with the emission limitation to reduce CO and you are not using an oxidation catalyst, if you comply with the emission limitation to reduce formaldehyde and you are not using NSCR, or if you comply with the emission limitation to limit the concentration of formaldehyde in the stationary RICE exhaust and you are not using an oxidation catalyst or NSCR, you must petition the Administrator for operating limitations to be established during the initial performance test and continuously monitored thereafter; or for approval of no operating limitations. You must not conduct the initial performance test until after the petition has been approved by the Administrator. [40 CFR 63.6620(f)]

103 [40 CFR 63.6620(f)]

If you petition the Administrator for approval of operating limitations, your petition must include the information described in 40 CFR 63.6620(g)(1)-(5). [40 CFR 63.6620(g)]  
If you petition the Administrator for approval of no operating limitations, your petition must include the information described in 40 CFR 63.6620(h)(1)-(7). [40 CFR 63.6620(h)]

**SPECIFIC REQUIREMENTS****AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit

Air - Minor Gen Permit-Oil and Gas Mod

**EQT\_0036 - Natural Gas ICEs for Which Construction or Reconstruction Commenced Before June 12, 2006**

106 [40 CFR 63.6620(i)]

The engine percent load during a performance test must be determined by documenting the calculations, assumptions, and measurement devices used to measure or estimate the percent load in a specific application. A written report of the average percent load determination must be included in the notification of compliance status. The following information must be included in the written report: the engine model number, the engine manufacturer, the year of purchase, the manufacturer's site-rated brake horsepower, the ambient temperature, pressure, and humidity during the performance test, and all assumptions that were made to estimate or calculate percent load during the performance test must be clearly explained. If measurement devices such as flow meters, kilowatt meters, beta analyzers, stain gauges, etc. are used, the model number of the measurement device, and an estimate of its accurate in percentage of true value must be provided. [40 CFR 63.6620(i)]

107 [40 CFR 63.6625(b)]

If you are required to install a continuous parameter monitoring system (CPMS) as specified in Table 5 of Subpart ZZZZ, install, operate, and maintain each CPMS according to the requirements in 40 CFR 63.6625(b)(1)-(6). [40 CFR 63.6625(b)]

108 [40 CFR 63.6625(e)]

If you own or operate any of the following stationary RICE, operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions:

- (1) An existing emergency stationary RICE located at an area source of HAP emissions; or
  - (2) An existing non-emergency 2SLB stationary RICE located at an area source of HAP emissions;
  - (3) An existing non-emergency 4SLB stationary RICE with a site rating less than or equal to 500 HP located at an area source of HAP emissions;
  - (4) An existing non-emergency 4SRB stationary RICE with a site rating less than or equal to 500 HP located at an area source of HAP emissions;
  - (5) An existing, non-emergency 4SLB stationary RICE with a site rating greater than 500 HP located at an area source of HAP emissions that is operated 24 hours or less per calendar year; or
  - (6) An existing, non-emergency 4SRB stationary RICE with a site rating greater than 500 HP located at an area source of HAP emissions that is operated 24 hours or less per calendar year. [40 CFR 63.6625(e)]
- If you own or operate an existing emergency stationary RICE located at an area source of HAP emissions, install a non-resettable hour meter if one is not already installed. [40 CFR 63.6625(f)]
- Minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all times other than startup in Table 2d to Subpart ZZZZ apply. [40 CFR 63.6625(h)]

109 [40 CFR 63.6625(f)]

110 [40 CFR 63.6625(h)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### EQT\_0036 - Natural Gas ICEs for Which Construction or Reconstruction Commenced Before June 12, 2006

111 [40 CFR 63.6625(j)]

If you own or operate a stationary SI engine that is subject to the work, operation or management practices in items 5, 6, 7, 8, 10, or 11 of Table 2d to Subpart ZZZZ, you have the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Table 2d. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2d. The analysis program must at a minimum analyze the following three parameters: Total Acid Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Acid Number increases by more than 3.0 milligrams of potassium hydroxide (KOH) per gram from Total Acid Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 business days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 business days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63.6625(j)]

Demonstrate initial compliance with each emission limitation, operating limitation, and other requirement that applies to you according to Table 5 of Subpart ZZZZ. [40 CFR 63.6630(a)]

Submit the Notification of Compliance Status containing the results of the initial compliance demonstration according to the requirements in 40 CFR 63.6645. [40 CFR 63.6630(c)]

The initial compliance demonstration required for existing non-emergency 4SLB and 4SRB stationary RICE with a site rating of more than 500 HP located at an area source of HAP that are not remote stationary RICE and that are operated more than 24 hours per calendar year must be conducted according to the requirements in 40 CFR 63.6630(e)(1)-(6). [40 CFR 63.6630(e)]

If you must comply with emission and operating limitations, you must monitor and collect data according to 40 CFR 63.6635. Except for monitor malfunctions, associated repairs, required performance evaluations, and required quality assurance or control activities, you must monitor continuously at all times that the stationary RICE is operating. A monitoring malfunction is any sudden, infrequent, not reasonably preventable failure of the monitoring to provide valid data. Monitoring failures that are caused in part by poor maintenance or careless operation are not malfunctions. You may not use data recorded during monitoring malfunctions, associated repairs, and required quality assurance or control activities in data averages and calculations used to report emission or operating levels. You must, however, use all the valid data collected during all other periods.

Demonstrate continuous compliance with each emission limitation, operating limitation, and other requirements in Table 2d to Subpart ZZZZ that apply to you according to methods specified in Table 6 to Subpart ZZZZ. [40 CFR 63.6640(a)]

Report each instance in which you did not meet each emission limitation or operating limitation in Table 2d to Subpart ZZZZ that apply to you. These instances are deviations from the emission and operating limitations in Subpart ZZZZ. These deviations must be reported according to the requirements in 40 CFR 63.6650. If you change your catalyst, reestablish the values of the operating parameters measured during the initial performance test. When you reestablish the values of your operating parameters, also conduct a performance test to demonstrate that you are meeting the required emission limitation applicable to your stationary RICE. [40 CFR 63.6640(b)]

The annual compliance demonstration required for existing non-emergency 4SLB and 4SRB stationary RICE with a site rating of more than 500 HP located at an area source of HAP that are not remote stationary RICE and that are operated more than 24 hours per calendar year must be conducted according to the requirements in 40 CFR 63.6640(c)(1)-(7). [40 CFR 63.6640(c)]

Report each instance in which you did not meet the requirements in Table 8 to Subpart ZZZZ that apply to you. [40 CFR 63.6640(e)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### **EQT 0036 - Natural Gas ICEs for Which Construction or Reconstruction Commenced Before June 12, 2006**

If you own or operate an emergency stationary RICE, operate the emergency stationary RICE according to the requirements in 40 CFR 63.6640(f)(1), (f)(2)(i), and (f)(4). In order for the engine to be considered an emergency stationary RICE under Subpart ZZZZ, any operation other than emergency operation, maintenance and testing, and operation in non-emergency situations for 50 hours per year, is prohibited. If you do not operate the engine according to these requirements, the engine will not be considered an emergency engine under Subpart ZZZZ and must meet all requirements for non-emergency engines.

(1) There is no time limit on the use of emergency stationary RICE in emergency situations.

(2) Emergency stationary RICE may be operated for maintenance checks and readiness testing for a maximum of 100 hours per calendar year, provided that the tests are recommended by federal, state or local government, the manufacturer, the vendor, or the insurance company associated with the engine. The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or operator maintains records indicating that federal, state, or local standards require maintenance and testing of emergency RICE beyond 100 hours per calendar year.

(3) Emergency stationary RICE located at area sources of HAP may be operated for up to 50 hours per calendar year in non-emergency situations. The 50 hours of operation in non-emergency situations are counted as part of the 100 hours per calendar year for maintenance and testing. [40 CFR 63.6640(f)]

You must submit all of the notifications in 40 CFR 63.7(b) and (c), 63.8(e), (f)(4) and (f)(6), 63.9(b)-(e), and (g) that apply to you by the dates specified. This requirement does not apply if you own or operate an existing stationary RICE less than 100 HP, an existing stationary emergency RICE, or an existing stationary RICE that is not subject to any numerical emission standards. [40 CFR 63.6645(a)]

If you are required to conduct a performance test, you must submit a Notification of Intent to conduct a performance test at least 60 days before the performance test is scheduled to begin as required in 40 CFR 63.7(b)(1). [40 CFR 63.6645(g)]

If you are required to conduct a performance test or other initial compliance demonstration as specified in Tables 4 and 5 to Subpart ZZZZ, you must submit a Notification of Compliance Status according to 40 CFR 63.9(h)(2)(ii). For each initial compliance demonstration required in Table 5 to Subpart ZZZZ that does not include a performance test, you must submit the Notification of Compliance Status before the close of business on the 30th day following the completion of the initial compliance demonstration. For each initial compliance demonstration required in Table 5 to Subpart ZZZZ that includes a performance test conducted according to the requirements in Table 3 to Subpart ZZZZ, you must submit the Notification of Compliance Status, including the performance test results, before the close of business on the 60th day following the completion of the performance test according to 40 CFR 63.10(d)(2). [40 CFR 63.6645(h)]

You must submit each report in Table 7 of Subpart ZZZZ that applies to you. [40 CFR 63.6650(a)] Unless the Administrator has approved a different schedule for submission of reports under 40 CFR 63.10(a), you must submit each report by the date in Table 7 of Subpart ZZZZ and according to the requirements in 40 CFR 63.6650(b)(1)-(9). [40 CFR 63.6650(b)]

The Compliance report must contain the information in 40 CFR 63.6650(c)(1)-(6). [40 CFR 63.6650(c)]

For each deviation from an emission or operating limitation that occurs for a stationary RICE where you are not using a CMS to comply with the emission or operating limitations in Subpart ZZZZ, the Compliance report must contain the information in 40 CFR 63.6650(c)(1)-(4) and the information in 40 CFR 63.6650(d)(1) and (2). [40 CFR 63.6650(d)]

For each deviation from an emission or operating limitation occurring for a stationary RICE where you are using a CMS to comply with the emission and operating limitations in Subpart ZZZZ, you must include information in 40 CFR 63.6650(c)(1)-(4) and (e)(1)-(12). [40 CFR 63.6650(e)]

If you must comply with the emission and operating limitations, you must keep the records described in 40 CFR 63.6655(a)(1)-(5) and (b)(1)-(3). [40 CFR 63.6655(a)]

For each CEMS or CMMS, you must keep the records listed in 40 CFR 63.6655(b)(1)-(3). [40 CFR 63.6655(b)]

**SPECIFIC REQUIREMENTS**  
AI ID: 1588873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001  
Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

**EQT\_0036 - Natural Gas ICEs for Which Construction or Reconstruction Commenced Before June 12, 2006**

131 [40 CFR 63.6655(d)] You must keep the records required in Table 6 of Subpart ZZZZ to show continuous compliance with each emission or operating limitation that applies to you. [40 CFR 63.6655(d)]

132 [40 CFR 63.6655(e)] You must keep records of the maintenance conducted on the stationary RICE in order to demonstrate that you operated and maintained the stationary RICE and after-treatment control device (if any) according to your own maintenance plan if you own or operate an existing stationary emergency RICE or an existing stationary RICE located at an area source of HAP emissions subject to management practices as shown in Table 2d to Subpart ZZZZ. [40 CFR 63.6655(e)]

If you own or operate an existing emergency stationary RICE located at an area source of HAP emissions that does not meet the standards applicable to non-emergency engines, keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. The owner or operator must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. [40 CFR 63.6655(f)]

Your records must be in a form suitable and readily available for expeditious review according to 40 CFR 63.10(b)(1). As specified in 40 CFR 63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record. You must keep each record readily accessible in hard copy or electronic form for at least 5 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to 40 CFR 63.10(b)(1).

133 [40 CFR 63.6660]

Table 8 to Subpart ZZZZ shows which parts of the General Provisions in 40 CFR 63.1 through 63.15 apply to you.

134 [40 CFR 63.6665]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

## **PCS 0006 Diesel Internal Combustion Engines**

### **EQT 0002 - Diesel ICEs - Engines Subject to NSPS III**

136 [40 CFR 60.4204(a)]

137 [40 CFR 60.4204(a)]

138 [40 CFR 60.4204(b)]

139 [40 CFR 60.4204(c)(1)]

140 [40 CFR 60.4204(c)(2)]

141 [40 CFR 60.4204(c)(3)]

142 [40 CFR 60.4204(c)(4)]

143 [40 CFR 60.4204(d)]

144 [40 CFR 60.4204(e)]

145 [40 CFR 60.4204(f)]

Pre-2007 model year non-emergency stationary CI ICE with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder: Comply with the Tier 1 emission standards in 40 CFR Part 1042, appendix I. [40 CFR 60.4204(a)]  
Pre-2007 model year non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder: Comply with the emission standards in table 1 to Subpart III. [40 CFR 60.4204(a)]

Owners and operators of 2007 model year and later non-emergency stationary CI ICE with a displacement of less than 30 liters per cylinder must comply with the emission standards for new CI engines in 40 CFR 60.4201 for their 2007 model year and later stationary CI ICE, as applicable. [40 CFR 60.4204(b)]

Non-emergency stationary CI engines with a displacement of greater than or equal to 30 liters per cylinder: For engines installed prior to January 1, 2012, limit the emissions of NOx in the stationary CI internal combustion engine exhaust to the following:

- (i) 12.7 grams per horsepower-hour (g/HP-hr) when maximum engine speed is less than 130 revolutions per minute (rpm);  
(ii)  $34 \times n^{0.2}$  g/HP-hr when maximum engine speed is 130 or more but less than 2000 rpm, where n is maximum engine speed; and  
(iii)  $7.3 \times n^{0.23}$  g/HP-hr when maximum engine speed is 2000 rpm or more. [40 CFR 60.4204(c)(1)]

Non-emergency stationary CI engines with a displacement of greater than or equal to 30 liters per cylinder: For engines installed on or after January 1, 2012 and before January 1, 2016, limit the emissions of NOx in the stationary CI internal combustion engine exhaust to the following:

- (i) 10.7 g/HP-hr when maximum engine speed is less than 130 rpm;  
(ii)  $33 \times n^{0.23}$  g/HP-hr when maximum engine speed is greater than or equal to 130 but less than 2000 rpm and where n is maximum engine speed; and  
(iii) 5.7 g/HP-hr when maximum engine speed is greater than or equal to 2000 rpm. [40 CFR 60.4204(c)(2)]

Non-emergency stationary CI engines with a displacement of greater than or equal to 30 liters per cylinder: For engines installed on or after January 1, 2016, limit the emissions of NOx in the stationary CI internal combustion engine exhaust to the following:

- (i) 2.5 g/HP-hr when maximum engine speed is less than 130 rpm;  
(ii)  $6.7 \times n^{0.20}$  g/HP-hr where n (maximum engine speed) is 130 or more but less than 2000 rpm; and  
(iii) 1.5 g/HP-hr where maximum engine speed is greater than or equal to 2000 rpm. [40 CFR 60.4204(c)(3)]

Non-emergency stationary CI engines with a displacement of greater than or equal to 30 liters per cylinder: Reduce particulate matter (PM) emissions by 60 percent or more, or limit the emissions of PM in the stationary CI internal combustion engine exhaust to 0.11 g/HP-hr. [40 CFR 60.4204(c)(4)]

Owners and operators of non-emergency stationary CI ICE with a displacement of less than 30 liters per cylinder who conduct performance tests in-use must meet the not-to-exceed (NTE) standards as indicated in 40 CFR 60.4212. [40 CFR 60.4204(d)]

Owners and operators of any modified or reconstructed non-emergency stationary CI ICE subject to Subpart III must meet the emission standards applicable to the model year, maximum engine power, and displacement of the modified or reconstructed non-emergency stationary CI ICE that are specified in 40 CFR 60.4204(a)-(d). [40 CFR 60.4204(e)]

Owners and operators of stationary CI ICE certified to the standards in 40 CFR 1039 and equipped with auxiliary emission control devices (AECDs) as specified in 40 CFR 1039.665 must meet the Tier 1 certification emission standards for new nonroad CI engines in 40 CFR Part 1039, appendix I, while the AECD is activated during a qualified emergency situation. A qualified emergency situation is defined in 40 CFR 1039.665. When the qualified emergency situation has ended and the AECD is deactivated, the engine must resume meeting the otherwise applicable emission standard specified in 40 CFR 60.4204. [40 CFR 60.4204(f)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### EQT\_0002 - Diesel ICEs - Engines Subject to NSPS III

- Pre-2007 model year emergency stationary C1 ICE with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder that are not fire pump engines: Comply with the Tier 1 emission standards in 40 CFR part 1042, appendix I. [40 CFR 60.4205(a)]
- 146 [40 CFR 60.4205(a)]
- 147 [40 CFR 60.4205(a)]
- Comply with the emission standards in Table 1 to Subpart III. [40 CFR 60.4205(a)]
- Pre-2007 model year and later emergency stationary C1 ICE with a displacement of less than 10 liters per cylinder that are not fire pump engines: Comply with the emission standards for new nonroad C1 engines in 40 CFR 60.4202, for all pollutants, for the same model year and maximum engine power for the 2007 model year and later emergency stationary C1 ICE. [40 CFR 60.4205(b)]
- Fire pump engines with a displacement of less than 30 liters per cylinder: Comply with the emission standards in table 4 to Subpart III, for all pollutants. [40 CFR 60.4205(c)]
- Emergency stationary C1 engines with a displacement of greater than or equal to 30 liters per cylinder: For engines installed prior to January 1, 2012, limit the emissions of NOx in the stationary C1 internal combustion engine exhaust to the following:
- (i) 12.7 g/HP-hr when maximum engine speed is less than 130 rpm;
  - (ii)  $34 \times n^{0.2}$  g/HP-hr when maximum engine speed is 130 or more but less than 2000 rpm, where n is maximum engine speed; and
  - (iii) 7.3 g/HP-hr when maximum engine speed is 2000 rpm or more. [40 CFR 60.4205(d)(1)]
- Emergency stationary C1 engines with a displacement of greater than or equal to 30 liters per cylinder: For engines installed on or after January 1, 2012, limit the emissions of NOx in the stationary C1 internal combustion engine exhaust to the following:
- (i) 10.7 g/HP-hr when maximum engine speed is less than 130 rpm;
  - (ii)  $33 \times n^{0.23}$  g/HP-hr when maximum engine speed is greater than or equal to 130 but less than 2000 rpm and where n is maximum engine speed; and
  - (iii) 5.7 g/HP-hr when maximum engine speed is greater than or equal to 2000 rpm. [40 CFR 60.4205(d)(2)]
- Emergency stationary C1 engines with a displacement of greater than or equal to 30 liters per cylinder: Limit the emissions of PM in the stationary C1 internal combustion engine exhaust to 0.30 g/HP-hr. [40 CFR 60.4205(d)(3)]
- Owners and operators of emergency stationary C1 ICE with a displacement of less than 30 liters per cylinder who conduct performance tests in-use must meet the NTE standards as indicated in 40 CFR 60.4212. [40 CFR 60.4205(e)]
- Owners and operators of any modified or reconstructed emergency stationary C1 ICE subject to Subpart III must meet the emission standards applicable to the model year, maximum engine power, and displacement of the modified or reconstructed C1 ICE that are specified in 40 CFR 60.4205(a)-(e). [40 CFR 60.4205(f)]
- Owners and operators of stationary C1 ICE must operate and maintain stationary C1 ICE that achieve the emission standards as required in 40 CFR 60.4204 and 60.4205 over the entire life of the engine.
- Beginning October 1, 2010, owners and operators of stationary C1 ICE subject to Subpart III with a displacement of less than 30 liters per cylinder that use diesel fuel must use diesel fuel that meets the requirements of 40 CFR 1090.305 for nonroad diesel fuel, except that any existing diesel fuel purchased (or otherwise obtained) prior to October 1, 2010, may be used until depleted. [40 CFR 60.4207(b)]
- Beginning June 1, 2012, owners and operators of stationary C1 ICE subject to Subpart III with a displacement of greater than or equal to 30 liters per cylinder must use diesel fuel that meets a maximum per-gallon sulfur content of 1000 parts per million (ppm). [40 CFR 60.4207(d)]
- After December 31, 2008, owners and operators may not install stationary C1 ICE (excluding fire pump engines) that do not meet the applicable requirements for 2007 model year engines. [40 CFR 60.4208(a)]
- After December 31, 2009, owners and operators may not install stationary C1 ICE with a maximum engine power of less than 25 HP (excluding fire pump engines) that do not meet the applicable requirements for 2008 model year engines. [40 CFR 60.4208(b)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### EQT 0002 - Diesel ICEs - Engines Subject to NSPS III

- 160 [40 CFR 60.4208(c)] After December 31, 2014, owners and operators may not install non-emergency stationary CI ICE with a maximum engine power of greater than or equal to 25 HP and less than 75 HP that do not meet the applicable requirements for 2013 model year non-emergency engines. [40 CFR 60.4208(c)]
- 161 [40 CFR 60.4208(d)] After December 31, 2013, owners and operators may not install non-emergency stationary CI ICE with a maximum engine power of greater than or equal to 75 HP and less than 175 HP that do not meet the applicable requirements for 2012 model year non-emergency engines. [40 CFR 60.4208(d)]
- 162 [40 CFR 60.4208(e)] After December 31, 2012, owners and operators may not install non-emergency stationary CI ICE with a maximum engine power of greater than or equal to 175 HP, including those above 750 HP, that do not meet the applicable requirements for 2011 model year non-emergency engines. [40 CFR 60.4208(e)]
- 163 [40 CFR 60.4208(f)] After December 31, 2016, owners and operators may not install non-emergency stationary CI ICE with a maximum engine power of greater than or equal to 750 HP that do not meet the applicable requirements for 2015 model year non-emergency engines. [40 CFR 60.4208(f)]
- 164 [40 CFR 60.4208(g)] After December 31, 2018, owners and operators may not install non-emergency stationary CI ICE with a maximum engine power greater than or equal to 804 HP and less than 2680 HP and a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder that do not meet the applicable requirements for 2017 model year non-emergency engines. [40 CFR 60.4208(g)] In addition to the requirements specified in 40 CFR 60.4201, 60.4202, 60.4204, and 60.4205, it is prohibited to import stationary CI ICE with a displacement of less than 30 liters per cylinder that do not meet the applicable requirements specified in 40 CFR 60.4208(a)-(g) after the dates specified in 40 CFR 60.4208(a)-(g). [40 CFR 60.4208(h)] The requirements of 40 CFR 60.4208 do not apply to owners or operators of stationary CI ICE that have been modified, reconstructed, and do not apply to engines that were removed from one existing location and reinstalled at a new location. [40 CFR 60.4208(i)] Emergency stationary CI internal combustion engine that does not meet the standards applicable to non-emergency engines. Install a non-resettable hour meter prior to startup of the engine. In addition, meet the monitoring requirements specified in 40 CFR 60.4211. [40 CFR 60.4209(a)]
- 165 [40 CFR 60.4208(h)] Stationary CI internal combustion engine equipped with a diesel particulate filter to comply with the emission standards in 40 CFR 60.4209(b) If you are an owner or operator and must comply with the emission standards specified in Subpart III, you must do all of the following, except as permitted under 40 CFR 60.4211(g):
- (1) Operate and maintain the stationary CI internal combustion engine and control device according to the manufacturer's emission-related written instructions;
- (2) Change only those emission-related settings that are permitted by the manufacturer; and
- (3) Meet the requirements of 40 CFR part 1068, as they apply to you. [40 CFR 60.4211(a)] If you are an owner or operator of a pre-2007 model year stationary CI internal combustion engine and must comply with the emission standards specified in 40 CFR 60.4204(a) or 60.4205(a), or if you are an owner or operator of a CI fire pump engine that is manufactured prior to the model years in table 3 to Subpart III and must comply with the emission standards specified in 40 CFR 60.4205(c), you must demonstrate compliance according to one of the methods specified in 40 CFR 60.4211(b)(1)-(5). [40 CFR 60.4211(b)]

**SPECIFIC REQUIREMENTS**

**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**

**Activity Number: PER2024001**

**Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod**

**EQT\_0002 - Diesel ICEs - Engines Subject to NSPS III**

- 171 [40 CFR 60.4211(c)]  
If you are an owner or operator of a 2007 model year and later stationary CI internal combustion engine and must comply with the emission standards specified in 40 CFR 60.4204(b) or 60.4205(b), or if you are an owner or operator of a CI fire pump engine that is manufactured during or after the model year that applies to your fire pump engine power rating in table 3 to Subpart IIII and must comply with the emission standards specified in 40 CFR 60.4205(c), you must comply by purchasing an engine certified to the emission standards in 40 CFR 60.4204(b), or 40 CFR 60.4205(b) or (c), as applicable, for the same model year and maximum (or in the case of fire pumps, NPPA nameplate) engine power. The engine must be installed and configured according to the manufacturer's emission-related specifications, except as permitted in 40 CFR 60.4211(g). [40 CFR 60.4211(c)]
- If you are an owner or operator and must comply with the emission standards specified in 40 CFR 60.4204(c) or 60.4205(d), you must demonstrate compliance according to the requirements specified in 40 CFR 60.4211(d)(1)-(3). [40 CFR 60.4211(d)]
- If you are an owner or operator of a modified or reconstructed stationary CI internal combustion engine and must comply with the emission standards specified in 40 CFR 60.4204(e) or 60.4205(f), you must demonstrate compliance according to one of the methods specified in 40 CFR 60.4211(e) or (2). [40 CFR 60.4211(e)]
- If you own or operate an emergency stationary ICE, operate the emergency stationary ICE according to the requirements in 40 CFR 60.4211(f)(1), (f)(2)(i), and (f)(3). In order for the engine to be considered an emergency stationary ICE under Subpart IIII, any operation other than emergency operation, maintenance and testing, and operation in non-emergency situations for 50 hours per year, is prohibited.
- If you do not operate the engine according to these requirements, the engine will not be considered an emergency engine under Subpart IIII and must meet all requirements for non-emergency engines.

- (1) There is no time limit on the use of emergency stationary ICE in emergency situations.
- (2) Emergency stationary ICE may be operated for maintenance checks and readiness testing for a maximum of 100 hours per calendar year, provided that the tests are recommended by federal, state or local government, the manufacturer, the vendor, or the insurance company associated with the engine. The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or operator maintains records indicating that federal, state, or local standards require maintenance and testing of emergency ICE beyond 100 hours per calendar year.
- (3) Emergency stationary ICE may be operated for up to 50 hours per calendar year in non-emergency situations. The 50 hours of operation in non-emergency situations are counted as part of the 100 hours per calendar year for maintenance and testing. [40 CFR 60.4211(f)]
- If you do not install, configure, operate, and maintain your engine and control device according to the manufacturer's emission-related written instructions, or you change emission-related settings in a way that is not permitted by the manufacturer, you must demonstrate compliance as described in 40 CFR 60.4211(g)(1)-(3). [40 CFR 60.4211(g)]
- The requirements for operators and prohibited acts specified in 40 CFR 1039.665 apply to owners or operators of stationary CI ICE equipped with AECDs for qualified emergency situations as allowed by 40 CFR 1039.665. [40 CFR 60.4211(h)]
- Owners and operators of stationary CI ICE with a displacement of less than 30 liters per cylinder who conduct performance tests pursuant to Subpart IIII must do so according to 40 CFR 60.4212(a)-(e).
- Owners and operators of stationary CI ICE with a displacement of greater than or equal to 30 liters per cylinder must conduct performance tests according to 40 CFR 60.4213(a)-(f).
- Owners and operators of non-emergency stationary CI ICE that are greater than 3000 HP, or have a displacement of greater than or equal to 10 liters per cylinder, or are pre-2007 model year engines that are greater than 175 HP and not certified, must meet the requirements of 40 CFR 60.4214(a)(1) and (2). [40 CFR 60.4214(a)]

**SPECIFIC REQUIREMENTS****AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**

Activity Number: PER2024001

**Permit Number: MSOG Master Gen Permit**  
**Air - Minor Gen Permit-Oil and Gas Mod**

**EQT\_0002 - Diesel ICEs - Engines Subject to NSPS III**

180 [40 CFR 60.4214(b)]

If the stationary CI internal combustion engine is an emergency stationary internal combustion engine, the owner or operator is not required to submit an initial notification. Starting with the model years in table 5 to Subpart III, if the emergency engine does not meet the standards applicable to non-emergency engines in the applicable model year, the owner or operator must keep records of the operation of the engine in emergency and non-emergency service that are recorded through the non-resettable hour meter. The owner must record the time of operation of the engine and the reason the engine was in operation during that time. [40 CFR 60.4214(b)]

181 [40 CFR 60.4214(c)]

If the stationary CI internal combustion engine is equipped with a diesel particulate filter, the owner or operator must keep records of any corrective action taken after the backpressure monitor has notified the owner or operator that the high backpressure limit of the engine is approached. [40 CFR 60.4214(c)]

182 [40 CFR 60.4214(e)]

Owners or operators of stationary CI ICE equipped with AECDs pursuant to the requirements of 40 CFR 1039.665 must report the use of AECDs as required by 40 CFR 1039.665(e). [40 CFR 60.4214(e)]

183 [40 CFR 60.4218]

(a) Table 8 to Subpart III shows which parts of the General Provisions in 40 CFR 60.1 through 60.19 apply to you.  
 (b) The provisions of 40 CFR 1068.10 and 1068.11 apply for engine manufacturers. For others, the general confidential business information (CBI) provisions apply as described in 40 CFR part 2.

**EQT\_0017 - All Diesel ICEs**

184 [LAC 33.III.1101.B]

Opacity <= 20 percent, except that such emissions may have an average opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes.

Which Months: All Year Statistical Basis: Six-minute average

Opacity <= 20 percent, except emissions may have an average opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes.

Which Months: All Year Statistical Basis: Six-minute average

**EQT\_0029 - All Diesel ICEs for Which Construction or Reconstruction Commenced On or After June 12, 2006**

186 [40 CFR 63.6590(c)(1)]

Meet the requirements of 40 CFR 63 by meeting the requirements of 40 CFR 60 Subpart III. No further requirements apply to such engines under 40 CFR 63. Subpart ZZZZ. [40 CFR 63.6590(c)(1)]

**EQT\_0032 - Diesel ICEs for Which Construction or Reconstruction Commenced Before June 12, 2006**

187 [40 CFR 63.6595(a)(1)]

If you have an existing stationary CI RICE located at an area source of HAP emissions, you must comply with the applicable emission limitations, operating limitations, and other requirements no later than May 3, 2013. [40 CFR 63.6595(a)(1)]  
 If you own or operate an affected source, you must meet the applicable notification requirements in 40 CFR 63.6645 and in 40 CFR part 63, subpart A. [40 CFR 63.6595(c)]

188 [40 CFR 63.6595(c)]

Comply with the requirements in Table 2d to Subpart ZZZZ and the operating limitations in Table 2b to Subpart ZZZZ that apply to you. [40 CFR 63.6603(a)]

189 [40 CFR 63.6603(a)]

If you own or operate an existing non-emergency CI RICE with a site rating of more than 300 HP located at an area source of HAP emissions that is certified to the Tier 3 (Tier 2 for engines above 560 kilowatt (kW)) emission standards in Table 1 of 40 CFR 89.112, you may comply with the requirements under 40 CFR 63 by meeting the requirements for Tier 3 engines (Tier 2 for engines above 560 kW) in 40 CFR 60 Subpart III instead of the emission limitations and other requirements that would otherwise apply under 40 CFR 63 for existing non-emergency CI RICE with a site rating of more than 300 HP located at an area source of HAP emissions. [40 CFR 63.6603(e)]

**EQT 0032 - Diesel ICEs for Which Construction or Reconstruction Commenced Before June 12, 2006**

If you own or operate an existing non-emergency, non-black start CI stationary RICE with a site rating of more than 300 brake HP with a displacement of less than 30 liters per cylinder that uses diesel fuel, you must use diesel fuel that meets the requirements in 40 CFR 1090.305 for nonroad diesel fuel.

You must be in compliance with the emission limitations, operating limitations, and other requirements in Subpart ZZZZ that apply to you at all times. At all times you must operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require you to make any further efforts to reduce emissions if levels required by this standard have been achieved. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.

You must conduct any initial performance test or other initial compliance demonstration according to Tables 4 and 5 to Subpart ZZZZ that apply to you within 180 days after the compliance date that is specified for your stationary RICE in 40 CFR 63.6595 and according to the provisions in 40 CFR 63.7(a)(2). An owner or operator is not required to conduct an initial performance test on a unit for which a performance test has been previously conducted, but the test must meet all of the conditions described in 40 CFR 63.6612(b)(1)-(4).

If you must comply with the emission limitations and operating limitations, you must conduct subsequent performance tests as specified in Table 3 of Subpart ZZZZ.

You must conduct each performance test in Tables 3 and 4 of Subpart ZZZZ that applies to you. [40 CFR 63.6620(a)]

Each performance test must be conducted according to the requirements that Subpart ZZZZ specifies in Table 4. If you own or operate a non-operational stationary RICE that is subject to performance testing, you do not need to start up the engine solely to conduct the performance test. Owners and operators of a non-operational engine can conduct the performance test when the engine is started up again. [40 CFR 63.6620(b)]

Conduct three separate test runs for each performance test required in 40 CFR 63.6620, as specified in 40 CFR 63.7(e)(3). Each test run must last at least 1 hour, unless otherwise specified in Subpart ZZZZ. [40 CFR 63.6620(d)]

Use Equation 1 of 40 CFR 63.6620(e)(1) to determine compliance with the percent reduction requirement. Normalize the CO, THC, or formaldehyde concentrations at the inlet and outlet of the control device to a dry basis and to 15 percent oxygen, or an equivalent percent carbon dioxide (CO<sub>2</sub>). If pollutant concentrations are to be corrected to 15 percent oxygen and CO<sub>2</sub> concentration is measured in lieu of oxygen concentration measurement, a CO<sub>2</sub> correction factor is needed. Calculate the CO<sub>2</sub> correction factor as described in 40 CFR 63.6620(e)(2)(i)-iii. [40 CFR 63.6620(e)]

If you comply with the emission limitation to reduce CO and you are not using an oxidation catalyst, if you comply with the emission limitation to reduce formaldehyde and you are not using NSCR, or if you comply with the emission limitation to limit the concentration of formaldehyde in the stationary RICE exhaust and you are not using an oxidation catalyst or NSCR, you must petition the Administrator for operating limitations to be established during the initial performance test and continuously monitored thereafter; or for approval of no operating limitations. You must not conduct the initial performance test until after the petition has been approved by the Administrator. [40 CFR 63.6620(f)]

If you petition the Administrator for approval of operating limitations, your petition must include the information described in 40 CFR 63.6620(g)(1)-(5). [40 CFR 63.6620(g)]

If you petition the Administrator for approval of no operating limitations, your petition must include the information described in 40 CFR 63.6620(h)(1)-(7). [40 CFR 63.6620(h)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### **EQT\_0032 - Diesel ICEs for Which Construction or Reconstruction Commenced Before June 12, 2006**

202 [40 CFR 63.6620(i)]

The engine percent load during a performance test must be determined by documenting the calculations, assumptions, and measurement devices used to measure or estimate the percent load in a specific application. A written report of the average percent load determination must be included in the notification of compliance status. The following information must be included in the written report: the engine model number, the engine manufacturer, the year of purchase, the manufacturer's site-rated brake horsepower, the ambient temperature, pressure, and humidity during the performance test, and all assumptions that were made to estimate or calculate percent load during the performance test must be clearly explained. If measurement devices such as flow meters, kilowatt meters, beta analyzers, strain gauges, etc. are used, the model number of the measurement device, and an estimate of its accurate in percentage of true value must be provided. [40 CFR 63.6620(i)]

203 [40 CFR 63.6625(a)]

If you elect to install a CEMS as specified in Table 5 of Subpart ZZZZ, install, operate, and maintain a CEMS to monitor CO and either O<sub>2</sub> or CO<sub>2</sub> according to the requirements in 40 CFR 63.6625(a)(1)-(4). If you are meeting a requirement to reduce CO emissions, the CEMS must be installed at both the inlet and outlet of the control device. If you are meeting a requirement to limit the concentration of CO, the CEMS must be installed at the outlet of the control device. [40 CFR 63.6625(a)]

If you are required to install a continuous parameter monitoring system (CPMS) as specified in Table 5 of Subpart ZZZZ, install, operate, and maintain each CPMS according to the requirements in 40 CFR 63.6625(b)(1)-(6). [40 CFR 63.6625(b)]

If you own or operate any of the following stationary RICE, operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions:

(1) An existing emergency stationary RICE located at an area source of HAP emissions; or  
(2) An existing non-emergency stationary CI RICE with a site rating less than or equal to 300 HP located at an area source of HAP emissions. [40 CFR 63.6625(e)]

204 [40 CFR 63.6625(f)]

If you own or operate an existing emergency stationary RICE located at an area source of HAP emissions, install a non-resettable hour meter if one is not already installed. [40 CFR 63.6625(f)]

If you own or operate an existing non-emergency, non-black start CI engine greater than or equal to 300 HP that is not equipped with a closed crankcase ventilation system, install a closed crankcase ventilation system that prevents crankcase emissions from being emitted to the atmosphere, or install an open crankcase filtration emission control system that reduces emissions from the crankcase by filtering the exhaust stream to remove oil mist, particulates and metals. Owners and operators must follow the manufacturer's specified maintenance requirements for operating and maintaining the open or closed crankcase ventilation systems and replacing the crankcase filters, or can request the Administrator to approve different maintenance requirements that are as protective as manufacturer requirements. [40 CFR 63.6625(g)]

205 [40 CFR 63.6625(e)]

Minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all times other than startup in Table 2d to Subpart ZZZZ apply. [40 CFR 63.6625(h)]

**EQT\_0032 - Diesel ICEs for Which Construction or Reconstruction Commenced Before June 12, 2006**

209 [40 CFR 63.6625(i)]

If you own or operate a stationary CI engine that is subject to the work, operation or management practices in items 1 or 4 of Table 2d to Subpart ZZZZ, you have the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Table 2d.

The oil analysis must be performed at the same frequency specified for changing the oil in Table 2d. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 business days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 business days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63.6625(i)]

Demonstrate initial compliance with each emission limitation, operating limitation, and other requirement that applies to you according to Table 5 of Subpart ZZZZ. [40 CFR 63.6630(a)]

During the initial performance test, establish each operating limitation in Table 2b of Subpart ZZZZ that applies to you. [40 CFR 63.6630 (b)]

210 [40 CFR 63.6630(a)]

Submit the Notification of Compliance Status containing the results of the initial compliance demonstration according to the requirements in 40 CFR 63.6645. [40 CFR 63.6630(c)]

If you must comply with emission and operating limitations, you must monitor and collect data according to 40 CFR 63.6635. Except for monitor malfunctions, associated repairs, required performance evaluations, and required quality assurance or control activities, you must monitor continuously at all times that the stationary RICE is operating. A monitoring malfunction is any sudden, infrequent, not reasonably preventable failure of the monitoring to provide valid data. Monitoring failures that are caused in part by poor maintenance or careless operation are not malfunctions. You may not use data recorded during monitoring malfunctions, associated repairs, and required quality assurance or control activities in data averages and calculations used to report emission or operating levels. You must, however, use all the valid data collected during all other periods.

211 [40 CFR 63.6630(b)]

Demonstrate continuous compliance with each emission limitation, operating limitation, and other requirements in Tables 2b and 2d to Subpart ZZZZ that apply to you according to methods specified in Table 6 to Subpart ZZZZ. [40 CFR 63.6640(a)]

Report each instance in which you did not meet each emission limitation or operating limitation in Tables 2b and 2d to Subpart ZZZZ that apply to you. These instances are deviations from the emission and operating limitations in Subpart ZZZZ. These deviations must be reported according to the requirements in 40 CFR 63.6650. If you change your catalyst, reestablish the values of the operating parameters measured during the initial performance test. When you reestablish the values of your operating parameters, also conduct a performance test to demonstrate that you are meeting the required emission limitation applicable to your stationary RICE. [40 CFR 63.6640(b)] Report each instance in which you did not meet the requirements in Table 8 to Subpart ZZZZ that apply to you. [40 CFR 63.6640(e)]

212 [40 CFR 63.6630(c)]

213 [40 CFR 63.6635]

214 [40 CFR 63.6640(a)]

215 [40 CFR 63.6640(b)]

216 [40 CFR 63.6640(e)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### **EQT 0032 - Diesel RICEs for Which Construction or Reconstruction Commenced Before June 12, 2006**

217 [40 CFR 63.6640(f)]

If you own or operate an emergency stationary RICE, operate the emergency stationary RICE according to the requirements in 40 CFR 63.6640(f)(1), (f)(2)(i), and (f)(4). In order for the engine to be considered an emergency stationary RICE under Subpart ZZZZ, any operation other than emergency operation, maintenance and testing, and operation in non-emergency situations for 50 hours per year, is prohibited. If you do not operate the engine according to these requirements, the engine will not be considered an emergency engine under Subpart ZZZZ and must meet all requirements for non-emergency engines.

(1) There is no time limit on the use of emergency stationary RICE in emergency situations.

(2) Emergency stationary RICE may be operated for maintenance checks and readiness testing for a maximum of 100 hours per calendar year, provided that the tests are recommended by federal, state or local government, the manufacturer, the vendor, or the insurance company associated with the engine. The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or operator maintains records indicating that federal, state, or local standards require maintenance and testing of emergency RICE beyond 100 hours per calendar year.

(3) Emergency stationary RICE located at area sources of HAP may be operated for up to 50 hours per calendar year in non-emergency situations. The 50 hours of operation in non-emergency situations are counted as part of the 100 hours per calendar year for maintenance and testing. [40 CFR 63.6640(f)]

You must submit all of the notifications in 40 CFR 63.7(b) and (c), 63.8(e), (f)(4) and (f)(6), 63.9(b)-(e), and (g) and (h) that apply to you by the dates specified. This requirement does not apply if you own or operate an existing stationary RICE less than 100 HP, an existing stationary emergency RICE, or an existing stationary RICE that is not subject to any numerical emission standards. [40 CFR 63.6645(a)]

If you are required to conduct a performance test, you must submit a Notification of Intent to conduct a performance test at least 60 days before the performance test is scheduled to begin as required in 40 CFR 63.7(b)(1). [40 CFR 63.6645(g)]

If you are required to conduct a performance test or other initial compliance demonstration as specified in Tables 4 and 5 to Subpart ZZZZ, you must submit a Notification of Compliance Status according to 40 CFR 63.9(h)(2)(ii). For each initial compliance demonstration required in Table 5 to Subpart ZZZZ that does not include a performance test, you must submit the Notification of Compliance Status before the close of business on the 30th day following the completion of the initial compliance demonstration. For each initial compliance demonstration required in Table 5 to Subpart ZZZZ, that includes a performance test conducted according to the requirements in Table 3 to Subpart ZZZZ, you must submit the Notification of Compliance Status, including the performance test results, before the close of business on the 60th day following the completion of the performance test according to 40 CFR 63.10(d)(2). [40 CFR 63.6645(h)]

You must submit each report in Table 7 of Subpart ZZZZ that applies to you. [40 CFR 63.6650(a)] Unless the Administrator has approved a different schedule for submission of reports under 40 CFR 63.10(a), you must submit each report by the date in Table 7 of Subpart ZZZZ and according to the requirements in 40 CFR 63.6650(b)(1)-(9). [40 CFR 63.6650(b)]

The Compliance report must contain the information in 40 CFR 63.6650(c)(1)-(6). [40 CFR 63.6650(c)]

For each deviation from an emission or operating limitation that occurs for a stationary RICE where you are not using a CMS to comply with the emission or operating limitations in Subpart ZZZZ, the Compliance report must contain the information in 40 CFR 63.6650(c)(1)-(4) and the information in 40 CFR 63.6650(d)(1) and (2). [40 CFR 63.6650(d)] For each deviation from an emission or operating limitation occurring for a stationary RICE where you are using a CMS to comply with the emission and operating limitations in Subpart ZZZZ, you must include information in 40 CFR 63.6650(c)(1)-(4) and (e)(1)-(12). [40 CFR 63.6650(e)]

If you must comply with the emission and operating limitations, you must keep the records described in 40 CFR 63.6655(a)(1)-(5) and (b)(1)-(3). [40 CFR 63.6655(a)]

For each CEMS or CPMS, you must keep the records listed in 40 CFR 63.6655(b)(1)-(3). [40 CFR 63.6655(b)]

**SPECIFIC REQUIREMENTS**  
AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities  
Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

**EQT 0032 - Diesel ICEs for Which Construction or Reconstruction Commenced Before June 12, 2006**

228 [40 CFR 63.6655(d)] You must keep the records required in Table 6 of Subpart ZZZZ to show continuous compliance with each emission or operating limitation that applies to you. [40 CFR 63.6655(d)]

229 [40 CFR 63.6655(e)] You must keep records of the maintenance conducted on the stationary RICE in order to demonstrate that you operated and maintained the stationary RICE and after-treatment control device (if any) according to your own maintenance plan if you own or operate an existing stationary RICE or an existing stationary RICE located at an area source of HAP emissions subject to management practices as shown in Table 2d to Subpart ZZZZ. [40 CFR 63.6655(e)]

230 [40 CFR 63.6655(f)] If you own or operate an existing emergency stationary RICE located at an area source of HAP emissions that does not meet the standards applicable to non-emergency engines, keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. The owner or operator must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. [40 CFR 63.6655(f)]

231 [40 CFR 63.6660] Your records must be in a form suitable and readily available for expeditious review according to 40 CFR 63.10(b)(1). As specified in 40 CFR 63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, corrective action, report, or record. You must keep each record readily accessible in hard copy or electronic form for at least 5 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to 40 CFR 63.10(b)(1).

232 [40 CFR 63.6665] Table 8 to Subpart ZZZZ shows which parts of the General Provisions in 40 CFR 63.1 through 63.15 apply to you.

## PCS 0007 Flares

### **EQT 0007 - Flares Controlling Offgas from Amine Regenerator Vents**

233 [LAC 33.III.501.C.6]

Flare gas: Heat content > 300 BTU/scf to ensure destruction of emissions to the flare stack.

Which Months: All Year Statistical Basis: None specified

234 [LAC 33.III.501.C.6]

235 [LAC 33.III.501.C.6]

### **EQT 0024 - All Flares Except Those Subject to 40 CFR 60 Subpart OOO, OOOa, or OOOOb and Those Subject to Requirements under Table 4 of Subsection V.G**

236 [LAC 33.III.1105]

Opacity <= 20 percent, except for a combined total of six hours in any 10 consecutive day period, for burning in connection with pressure valve releases for control over process upsets.

Which Months: All Year Statistical Basis: None specified

237 [LAC 33.III.1105]

238 [LAC 33.III.1313.C]

239 [LAC 33.III.501.C.6]

240 [LAC 33.III.501.C.6]

241 [LAC 33.III.501.C.6]

242 [LAC 33.III.501.C.6]

243 [LAC 33.III.501.C.6]

244 [LAC 33.III.501.C.6]

Which Months: All Year Statistical Basis: None specified

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### **PCS 0008 Storage Vessels and Flash Gas Emissions**

#### **EQT 0022 - Storage Vessels**

- 245 [LAC 33:III.2103.A] Any stationary tank, reservoir, or other container of more than 250 gallons and up to 40,000 gallons nominal capacity shall not store any volatile organic compound having a maximum true vapor pressure of 1.5 psia or greater at storage conditions unless such tank, reservoir, or other container is designed and equipped with a submerged fill pipe or a vapor loss control system as defined in LAC 33:III.2103.E or a pressure tank capable of maintaining working pressures sufficient at all times under normal operating conditions to prevent vapor or gas loss to the atmosphere.
- 246 [LAC 33:III.2103.I] Maintain records to verify compliance with or exemption from LAC 33:III.2103. Maintain records for at least five years.

#### **EQT 0046 - Gasoline Dispensing Facilities**

- 247 [40 CFR 63.1111(e)] An affected source shall, upon request by the Administrator, demonstrate that their monthly throughput is less than the 10,000-gallon or the 100,000-gallon threshold level, as applicable. For new or reconstructed affected sources, as specified in 40 CFR 63.11112(b) and (c), recordkeeping to document monthly throughput must begin upon startup of the affected source. For existing sources, as specified in 40 CFR 63.11112(d), recordkeeping to document monthly throughput must begin on January 10, 2008. For existing sources that are subject to Subpart CCCCCC only because they load gasoline into fuel tanks other than those in motor vehicles, as defined in 40 CFR 63.11132, recordkeeping to document monthly throughput must begin on January 24, 2011. Records required under this paragraph shall be kept for a period of 5 years. [40 CFR 63.1111(e)]

You must, at all times, operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source. [40 CFR 63.11115(a)]

You must not allow gasoline to be handled in a manner that would result in vapor releases to the atmosphere for extended periods of time. Measures to be taken include, but are not limited to, the following:

- (1) Minimize gasoline spills.
- (2) Clean up spills as expeditiously as practicable.
- (3) Cover all open gasoline containers and all gasoline storage tank fill-pipes with a gasketed seal when not in use. Per 40 CFR 63.11116 (d), portable gasoline containers that meet the requirements of 40 CFR 59 Subpart F are considered acceptable for compliance with this provision.
- (4) Minimize gasoline sent to open waste collection systems that collect and transport gasoline to reclamation and recycling devices, such as oil/water separators. [40 CFR 63.11116(a)]

You are not required to submit notifications or reports as specified in 40 CFR 63.11125, 40 CFR 63.11126, or 40 CFR 63 Subpart A, but you must have records available within 24 hours of a request by the Administrator to document your gasoline throughput. [40 CFR 63.11116(b)]

Table 3 to Subpart CCCCCC shows which parts of the General Provisions apply to you.

#### **RLP 0001 - Flash Gas Emissions Subject to LAC 33:III.2104**

- 252 [LAC 33:III.2104.C.1] Potential to emit >= 250 tpy of flash gas: Reduce aggregated facility flash gas emissions by a minimum of 95 percent.

**SPECIFIC REQUIREMENTS**  
**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**  
**Activity Number: PER2024001**

**Permit Number: MSOG Master Gen Permit**  
**Air - Minor Gen Permit-Oil and Gas Mod**

**RLP\_0001 - Flash Gas Emissions Subject to LAC 33:III.2104**

- 253 [LAC 33:III.2104.C.2] Facilities located in Ascension, East Baton Rouge, Iberville, Livingston, or West Baton Rouge Parish (potential to emit < 250 tpy of flash gas); Reduce aggregated facility flash gas emissions by a minimum of 95 percent or to a potential to emit of less than 2.5 tpy without artificially restricting production, hours of operation, capacity utilization, or similar parameter.
- 254 [LAC 33:III.2104.C.3] Facilities located in Calcasieu Parish (potential to emit < 250 tpy of flash gas); Reduce aggregated facility flash gas emissions by a minimum of 95 percent or to a potential to emit of less than 50 tpy without artificially restricting production, hours of operation, capacity utilization, or similar parameter.
- 255 [LAC 33:III.2104.C.4] Facilities located in other parishes (potential to emit < 250 tpy of flash gas); Reduce aggregated facility flash gas emissions by a minimum of 95 percent or to a potential to emit of less than 100 tpy without artificially restricting production, hours of operation, capacity utilization, or similar parameter.
- 256 [LAC 33:III.2104.C] Facilities to which LAC 33:III.2104 is applicable: Install a vapor recovery system that directs vapors to a fuel gas system, a sales gas system, an underground gas injection system, or a control device.
- 257 [LAC 33:III.2104.G] Maintain records to verify compliance with or exemption from LAC 33:III.2104 including, but not limited to, those described in LAC 33:III.2104.G.1-5. Keep records on the premises, or at an alternate location approved by DEQ, for at least five years.

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### **PCS 0009 Affected Facilities Subject to NSPS OOOO**

#### **CRG 0001 - General Requirements under NSPS OOOO**

Group Members: EMS 0002 EQR 0042 EQT 0043 EQT 0045 EQT 0062

- 258 [40 CFR 60.5420(a)] Submit the notifications according to 40 CFR 60.5420(a)(1) and (2) if you own or operate one or more of the affected facilities specified in 40 CFR 60.5365 that was constructed, modified, or reconstructed during the reporting period. [40 CFR 60.5420(a)]  
259 [40 CFR 60.5420(b)] Submit annual reports containing the information specified in 40 CFR 60.5420(b)(1)-(6) and performance test reports as specified in 40 CFR 60.5420(b)(7) or (8). [40 CFR 60.5420(b)]  
260 [40 CFR 60.5420(c)] Maintain the records identified as specified in 40 CFR 60.7(f) and in 40 CFR 60.5420(c)(1)-(13). All records required by this subpart must be maintained either onsite or at the nearest local field office for at least 5 years. [40 CFR 60.5420(c)]

#### **EMS 0002 - Gas Wells Subject to NSPS OOOO**

- 261 [40 CFR 60.5375(a)(1)(i)] During the initial flowback stage, route the flowback into one or more well completion vessels or storage vessels and commence operation of a separator unless it is technically infeasible for a separator to function. Any gas present in the initial flowback stage is not subject to control under 40 CFR 60.5375. [40 CFR 60.5375(a)(1)(i)]  
262 [40 CFR 60.5375(a)(1)(ii)] During the separation flowback stage, route all recovered liquids from the separator to one or more well completion vessels or storage vessels, re-inject the liquids into the well or another well or route the recovered liquids to a collection system. Route the recovered gas from the separator into a gas flow line or collection system, re-inject the recovered gas into the well or another well, use the recovered gas as an on-site fuel source, or use the recovered gas for another useful purpose that a purchased fuel or raw material would serve. If it is infeasible to route the recovered gas as required above, follow the requirements in 40 CFR 60.5375(a)(3). If, at any time during the separation flowback stage, it is not technically feasible for a separator to function, comply with 40 CFR 60.5375(a)(1)(i). [40 CFR 60.5375(a)(1)(ii)]

- 263 [40 CFR 60.5375(a)(2) and (3)] All salable quality recovered gas must be routed to the gas flow line as soon as practicable. In cases where salable quality gas cannot be directed to the flow line, capture and direct recovered gas to a completion combustion device, except in conditions that may result in a fire hazard or explosion, or where high heat emissions from a completion combustion device may negatively impact waterways. Completion combustion devices must be equipped with a reliable continuous ignition source. [40 CFR 60.5375(a)(2) and (3)]  
264 [40 CFR 60.5375(a)(4)] You have a general duty to safely maximize resource recovery and minimize releases to the atmosphere during flowback and subsequent recovery. [40 CFR 60.5375(a)(4)]  
265 [40 CFR 60.5375(b)] Maintain a log for each well completion operation at each gas well affected facility. The log must be completed on a daily basis for the duration of the well completion operation and must contain the records specified in 40 CFR 60.5420(c)(1)(iii). [40 CFR 60.5375(b)]  
266 [40 CFR 60.5375(c)] Demonstrate initial compliance with the standards that apply to gas well affected facilities as required by 40 CFR 60.5410. [40 CFR 60.5375(c)]

- 267 [40 CFR 60.5375(d)] Demonstrate continuous compliance with the standards that apply to gas well affected facilities as required by 40 CFR 60.5415. [40 CFR 60.5375(d)]  
268 [40 CFR 60.5375(e)] Perform the required notification, recordkeeping and reporting as required by 40 CFR 60.5420. [40 CFR 60.5375(e)]

**SPECIFIC REQUIREMENTS****EMS\_0002 - Gas Wells Subject to NSPS 0000**

269 [40 CFR 60.5375(f)]

For each well completion operation with hydraulic fracturing at a wildcat or delineation well and for each well completion operation with hydraulic fracturing at a non-wildcat low pressure gas well or non-delineation low pressure gas well, route the flowback into one or more well completion vessels and commence operation of a separator unless it is technically infeasible for a separator to function. Any gas present in the flowback before the separator can function is not subject to control under 40 CFR 60.5375. Capture and direct recovered gas to a completion combustion device, except in conditions that may result in a fire hazard or explosion, or where high heat emissions from a completion combustion device may negatively impact waterways. Completion combustion devices must be equipped with a reliable continuous ignition source. Comply with 40 CFR 60.5375(a)(4) and (b)-(e). Maintain records specified in 40 CFR 60.5420(c)(1)(iii) for wildcat, delineation and low pressure gas wells. [40 CFR 60.5375(f)]

Comply with 40 CFR 60.5410(a)(1)-(4). [40 CFR 60.5410(a)]

Demonstrate continuous compliance by submitting the reports required by 40 CFR 60.5420(b) and maintaining the records for each completion operation specified in 40 CFR 60.5420(c)(1). [40 CFR 60.5415(a)]

**EQT 0042 - Reciprocating Compressors Subject to NSPS 0000**

272 [40 CFR 60.5385(a)]

Replace the reciprocating compressor rod packing according to either 40 CFR 60.5385(a)(1) or (2) or comply with 40 CFR 60.5385(a)(3).  
 (1) Before the compressor has operated for 26,000 hours. The number of hours of operation must be continuously monitored beginning upon initial startup of your reciprocating compressor affected facility, or October 15, 2012, or the date of the most recent reciprocating compressor rod packing replacement, whichever is later.

(2) Prior to 36 months from the date of the most recent rod packing replacement, or 36 months from the date of startup for a new reciprocating compressor for which the rod packing has not yet been replaced.

(3) Collect the emissions from the rod packing using a rod packing emissions collection system which operates under negative pressure and route the rod packing emissions to a closed vent system that meets the requirements of 40 CFR 60.5411(a). [40 CFR 60.5385(a)]

Demonstrate initial compliance with standards that apply to reciprocating compressor affected facilities as required by 40 CFR 60.5410.  
 [40 CFR 60.5385(b)]

Demonstrate continuous compliance with standards that apply to reciprocating compressor affected facilities as required by 40 CFR 60.5415. [40 CFR 60.5385(c)]

Perform the required notification, recordkeeping, and reporting as required by 40 CFR 60.5420. [40 CFR 60.5385(d)]

Comply with 40 CFR 60.5410(c)(1)-(4). [40 CFR 60.5410(c)]

Closed vent system requirements:

(1) Design the closed vent system to route all gases, vapors, and fumes emitted from the material in the reciprocating compressor rod packing emissions collection system to a control device or to a process that meets the requirements specified in 40 CFR 60.5412(a) through (c).  
 (2) Design and operate the closed vent system with no detectable emissions as demonstrated by 40 CFR 60.5416(b).  
 (3) Meet the requirements specified in 40 CFR 60.5411(a)(3)(i) and (ii) if the closed vent system contains one or more bypass devices that could be used to divert all or a portion of the gases, vapors, or fumes from entering the control device. Subpart OOOO. [40 CFR 60.5411(a)]

For each reciprocating compressor affected facility complying with 40 CFR 60.5385(a)(1) or (2), demonstrate continuous compliance according to 40 CFR 60.5415(c)(1)-(3). For each reciprocating compressor affected facility complying with 40 CFR 60.5385(a)(3), demonstrate continuous compliance according to 40 CFR 60.5415(c)(4). [40 CFR 60.5415(c)]

278 [40 CFR 60.5415(c)]

**SPECIFIC REQUIREMENTS**  
**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

**EQT 0042 - Reciprocating Compressors Subject to NSPS OOOO**

- 279 [40 CFR 60.5416(a)]  
Except as provided in 40 CFR 60.5416(b)(11) and (12), inspect each closed vent system according to the procedures and schedule specified in 40 CFR 60.5416(a)(1) and (2), inspect each cover according to the procedures and schedule specified in 40 CFR 60.5416(a)(3), and inspect each bypass device according to the procedures of 40 CFR 60.5416(a)(4). Subpart OOOO. [40 CFR 60.5416(a)]  
No detectable emissions test methods and procedures. If you are required to conduct an inspection of a closed vent system or cover as specified in 40 CFR 60.5416(a)(1), (2), or (3), meet the requirements of 40 CFR 60.5416(b)(1) through (13). Subpart OOOO. [40 CFR 60.5416(b)]

**EQT 0043 - Pneumatic Controllers Subject to NSPS OOOO**

- Compliance with 40 CFR 60.5390(c)(1) is not required if you determine that the use of a pneumatic controller affected facility with a bleed rate greater than the applicable standard is required based on functional needs, including but not limited to response time, safety and positive actuation. However, you must tag such pneumatic controller with the month and year of installation, reconstruction or modification, and identification information that allows traceability to the records for that pneumatic controller, as required in 40 CFR 60.5420(c)(4)(ii). [40 CFR 60.5390(a)]

Each pneumatic controller affected facility constructed, modified or reconstructed on or after October 15, 2013, at a location between the wellhead and a natural gas processing plant or the point of custody transfer to an oil pipeline must have a bleed rate less than or equal to 6 standard cubic feet per hour and be tagged with the month and year of installation, reconstruction or modification, and identification information that allows traceability to the records for that controller as required in 40 CFR 60.5420(c)(4)(ii). [40 CFR 60.5390(c)]

Demonstrate initial compliance with standards that apply to pneumatic controller affected facilities as required by 40 CFR 60.5410. [40 CFR 60.5390(d)]  
Demonstrate continuous compliance with standards that apply to pneumatic controller affected facilities as required by 40 CFR 60.5415. [40 CFR 60.5390(e)]

Perform the required notification, recordkeeping, and reporting as required by 40 CFR 60.5420, except that you are not required to submit the notifications specified in 40 CFR 60.5420(a). [40 CFR 60.5390(f)]  
Comply with the requirements specified in 40 CFR 60.5410(d)(1)-(6), as applicable. [40 CFR 60.5410(d)]  
Demonstrate continuous compliance according to 40 CFR 60.5415(d)(1)-(3). [40 CFR 60.5415(d)]

**EQT 0045 - Storage Vessels Subject to NSPS OOOO**

- Group 1 storage vessel affected facilities: Submit a notification identifying each Group 1 storage vessel affected facility, including its location, with your initial annual report as specified in 40 CFR 60.5420(b)(6)(iv). Comply with 40 CFR 60.5395(d)-(g). [40 CFR 60.5395(b)]  
Group 2 storage vessel affected facilities: Comply with 40 CFR 60.5395(d)-(g). [40 CFR 60.5395(c)]  
Reduce VOC emissions by 95.0 percent unless you meet the conditions specified in 40 CFR 60.5395(d)(2). For Group 2 storage vessel affected facilities, achieve the required emissions reductions within 60 days after startup. For Group 2 storage vessel affected facilities receiving liquids pursuant to the standards for gas well affected facilities in 40 CFR 60.5375, achieve the required emissions reductions within 60 days after startup of production as defined in 40 CFR 60.5430. [40 CFR 60.5395(d)(1)]  
If a well feeding the storage vessel affected facility undergoes fracturing or refracturing, comply with 40 CFR 60.5395(d)(1) as soon as liquids from the well following fracturing or refracturing are routed to the storage vessel affected facility. [40 CFR 60.5395(d)(2)(i)]

**SPECIFIC REQUIREMENTS**  
**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**  
**Activity Number: PER2024001**

**Permit Number: MSOG Master Gen Permit**  
**Air - Minor Gen Permit-Oil and Gas Mod**

**EQT 0045 - Storage Vessels Subject to NSPS OOOO**

- 292 [40 CFR 60.5395(d)(2)(ii)]  
If the monthly emissions determination required in 40 CFR 60.5395 indicates that VOC emissions from your storage vessel affected facility increase to 4 tpy or greater and the increase is not associated with fracturing or refracturing of a well feeding the storage vessel affected facility, comply with 40 CFR 60.5395(d)(1) within 30 days of the monthly calculation. [40 CFR 60.5395(d)(2)(ii)]
- 293 [40 CFR 60.5395(d)(2)]  
Maintain the uncontrolled actual VOC emissions from the storage vessel affected facility at less than 4 tpy without considering control. Prior to using the uncontrolled actual VOC emission rate for compliance purposes, demonstrate that the uncontrolled actual VOC emissions have remained less than 4 tpy as determined monthly for 12 consecutive months. After such demonstration, determine the uncontrolled actual VOC emission rate each month. The uncontrolled actual VOC emissions must be calculated using a generally accepted model or calculation methodology. Monthly calculations must be based on the average throughput for the month. Monthly calculations must be separated by at least 14 days. [40 CFR 60.5395(d)(2)]
- If you use a control device (other than a floating roof) to reduce emissions from your storage vessel affected facility, equip the storage vessel with a cover that meets the requirements of 40 CFR 60.5411(b) and is connected through a closed vent system that meets the requirements of 40 CFR 60.5411(c), and route emissions to a control device that meets the conditions specified in 40 CFR 60.5412(c) and (d). As an alternative to routing the closed vent system to a control device, you may route the closed vent system to a process. [40 CFR 60.5395(e)(1)]
- If you use a floating roof to reduce emissions, meet the requirements of 40 CFR 60.112b(a)(1) or (2) and the relevant monitoring, inspection, recordkeeping, and reporting requirements in 40 CFR 60 Subpart Kb. [40 CFR 60.5395(e)(2)]
- If you remove a Group 1 or Group 2 storage vessel affected facility from service, completely empty and degas the storage vessel, such that the storage vessel no longer contains crude oil, condensate, produced water or intermediate hydrocarbon liquids. A storage vessel where liquid is left on walls, as bottom clinging or in pools due to floor irregularity is considered to be completely empty. Submit a notification as required in 40 CFR 60.5420(b)(6)(vi) in your next annual report, identifying each storage vessel affected facility removed from service during the reporting period and the date of its removal from service. A Group 1 or Group 2 storage vessel is not an affected facility under Subpart OOOO for the period that it is removed from service. [40 CFR 60.5395(f)(1)]
- If a storage vessel is returned to service, determine its affected facility status as provided in 40 CFR 60.5365(e). For each storage vessel affected facility returned to service during the reporting period, submit a notification in your next annual report as required in 40 CFR 60.5420(b)(6)(vii), identifying each storage vessel affected facility and the date of its return to service. [40 CFR 60.5395(f)(2) and (3)]
- 296 [40 CFR 60.5395(f)(1)]  
Demonstrate initial compliance with standards as required by 40 CFR 60.5410(h) and (i). Demonstrate continuous compliance with standards as required by 40 CFR 60.5415(e)(3). Perform the required notification, recordkeeping and reporting as required by 40 CFR 60.5420. [40 CFR 60.5395(g)]
- Comply with 40 CFR 60.5410(h)(1)-(5). For a Group 2 storage vessel affected facility, you must demonstrate initial compliance within 60 days after startup. [40 CFR 60.5410(h)]
- For each Group 1 storage vessel affected facility, submit the notification specified in 40 CFR 60.5395(b)(2) with the initial annual report specified in 40 CFR 60.5420(b)(6). [40 CFR 60.5410(i)]
- 297 [40 CFR 60.5395(f)(2) and (3)]
- 298 [40 CFR 60.5395(g)]
- 299 [40 CFR 60.5410(h)]
- 300 [40 CFR 60.5410(i)]

**SPECIFIC REQUIREMENTS**

**EQT\_0045 - Storage Vessels Subject to NSPS OOOO**

301 [40 CFR 60.5411(b)]

Cover requirements for storage vessels:

- (1) The cover and all openings on the cover (e.g., access hatches, sampling ports, pressure relief valves and gauge wells) shall form a continuous impermeable barrier over the entire surface area of the liquid in the storage vessel.
- (2) Each cover opening shall be secured in a closed, sealed position (e.g., covered by a gasketed lid or cap) whenever material is in the unit on which the cover is installed except during those times when it is necessary to use an opening as described in 40 CFR 60.5411(b)(2)(i)-(iv).

(3) Each storage vessel thief hatch shall be equipped, maintained and operated with a weighted mechanism or equivalent, to ensure that the lid remains properly seated. Select gasket material for the hatch based on composition of the fluid in the storage vessel and weather conditions. Subpart OOOO. [40 CFR 60.5411(b)]

Closed vent system requirements for storage vessel affected facilities using a control device or routing emissions to a process:

- (1) Design the closed vent system to route all gases, vapors, and fumes emitted from the material in the storage vessel to a control device that meets the requirements specified in 40 CFR 60.5412(c) and (d), or to a process.
- (2) Design and operate a closed vent system with no detectable emissions, as determined using olfactory, visual and auditory inspections. Each closed vent system that routes emissions to a process must be operational 95 percent of the year or greater.
- (3) Meet the requirements specified in 40 CFR 60.5411(c)(3)(i) and (ii) if the closed vent system contains one or more bypass devices that could be used to divert all or a portion of the gases, vapors, or fumes from entering the control device or to a process. [40 CFR 60.5411(c)]

Each control device used to meet the emission reduction standard in 40 CFR 60.5395(d) for your storage vessel affected facility must be installed according to 40 CFR 60.5412(d)(1)-(3), as applicable. As an alternative to 40 CFR 60.5412(d)(1), you may install a control device model tested under 40 CFR 60.5413(d), which meets the criteria in 40 CFR 60.5413(d)(11) and 40 CFR 60.5413(e). [40 CFR 60.5412(d)]

Demonstrate continuous compliance according to 40 CFR 60.5415(e)(3) for each storage vessel affected facility, for which you are using a control device or routing emissions to a process to meet the requirement of 40 CFR 60.5395(d)(1). [40 CFR 60.5415(e)]

Cover and closed vent system inspections for storage vessel affected facilities: If you install a control device or route emissions to a process, inspect each closed vent system according to the procedures and schedule specified in 40 CFR 60.5416(c)(1), inspect each cover according to the procedures and schedule specified in 40 CFR 60.5416(c)(2), and inspect each bypass device according to the procedures of 40 CFR 60.5416(c)(3). Also comply with the requirements of 40 CFR 60.5416(c)(4)-(7). [40 CFR 60.5416(c)]

For each control device used to comply with the emission reduction standard in 40 CFR 60.5395(d)(1) for your storage vessel affected facility, demonstrate continuous compliance according to 40 CFR 60.5417(h)(1)-(3). You are exempt from the requirements of 40 CFR 60.5417(h) if you install a control device model tested in accordance with 40 CFR 60.5413(d)(2)-(10), which meets the criteria in 40 CFR 60.5413(d)(11), the reporting requirement in 40 CFR 60.5413(d)(12), and meet the continuous compliance requirement in 40 CFR 60.5413(e). [40 CFR 60.5417(h)]

**EQT\_0062 - Super-Emitter Events Subject to NSPS OOOO**

307 [40 CFR 60.5371(a)(1)]

If you do not own or operate an oil and natural gas facility within 50 meters from the latitude and longitude provided in the notification subject to the regulation under Subpart OOOO, report this result to the EPA. Subpart OOOO. [40 CFR 60.5371(a)(1)]

If you own or operate an oil and natural gas facility within 50 meters from the latitude and longitude provided in the notification subject to regulation under Subpart OOOO, investigate to determine the source of super-emitter event. The investigation may include but is not limited to the actions specified below in 40 CFR 60.5371(a)(2)(i) through (iii). Subpart OOOO. [40 CFR 60.5371(a)(2)]

**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**  
**Activity Number: PER2024001**

**Permit Number: MSOG Master Gen Permit**  
**Air - Minor Gen Permit-Oil and Gas Mod**

**SPECIFIC REQUIREMENTS**

**EQT 0062 - Super-Emitter Events Subject to NSPS OOOO**

- 309 [40 CFR 60.5371(b)]  
Submit the results of the super-emitter event investigation conducted under 40 CFR 60.5371(a) to the EPA in accordance with 40 CFR 60.5371(b)(1). If the super-emitter event (i.e., emission at 100 kg/hr of methane or more) is ongoing at the time of the initial report, submit the additional information in accordance with 40 CFR 60.5371(b)(2). Attest to the information included in the report as specified in 40 CFR 60.5371(b)(3). Subpart OOOO. [40 CFR 60.5371(b)]
- 310 [40 CFR 60.5371]  
Upon receiving a notification of a super emitter event issued by the EPA under 40 CFR 60.5371b(c), owners or operators must take the actions listed in 40 CFR 60.5371(a) and (b). Within 5 calendar days of receiving a notification from the EPA of a super-emitter event, the owner or operator of an oil and natural gas facility must initiate a super-emitter event investigation. Subpart OOOO.

**SPECIFIC REQUIREMENTS**

Activity Number: PER20240001  
 Permit Number: MSOG Master Gen Permit  
 Air - Minor Gen Permit-Oil and Gas Mod

**PCS 0010 Affected Facilities Subject to NSPS OOOOa****CRG 0004 - General Requirements under NSPS OOOOa**

Group Members: EMS 0003 EQT 0048 EQT 0050 EQT 0051 EQT 0063 F1G 0004

311 [40 CFR 60.5370(a)(a)] Be in compliance with the standards of 40 CFR 60 Subpart OOOOa no later than August 2, 2016, or upon startup, whichever is later. [40 CFR 60.5370(a)(a)]

312 [40 CFR 60.5370a(b)] At all times, including periods of startup, shutdown, and malfunction, maintain and operate any affected facility including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. The provisions for exemption from compliance during periods of startup, shutdown and malfunctions provided for in 40 CFR 60.8(c) do not apply. [40 CFR 60.5370a(b)]

313 [40 CFR 60.5420a(b)] Submit annual reports containing the information specified in 40 CFR 60.5420a(b)(1)-(8) and (12) and performance test reports as specified in 40 CFR 60.5420a(b)(9) or (10), if applicable. Submit annual reports following the procedure specified in 40 CFR 60.5420a(b)(11). The initial annual report is due no later than 90 days after the end of the initial compliance period as determined according to 40 CFR 60.5410a. Subsequent annual reports are due no later than same date each year as the initial annual report. If you own or operate more than one affected facility, you may submit one report for multiple affected facilities provided the report contains all of the information required as specified in 40 CFR 60.5420a(b)(1)-(8). [40 CFR 60.5420a(b)]

314 [40 CFR 60.5420a(c)] Maintain the records identified as specified in 40 CFR 60.7(f) and in 40 CFR 60.5420a(c)(1)-(16). All records required by Subpart OOOOa must be maintained either onsite or at the nearest local field office for at least 5 years. Any records required to be maintained by Subpart OOOOa that are submitted electronically via the EPA's CDX may be maintained in electronic format. [40 CFR 60.5420a(c)]

315 [40 CFR 60.5425a]

**EMS 0003 - Wells Subject to NSPS OOOOa**

316 [40 CFR 60.5375a(a)(1)(i)] During the initial flowback stage, route the flowback into one or more well completion vessels or storage vessels and commence operation of a separator unless it is technically infeasible for a separator to function. Any gas present in the initial flowback stage is not subject to control under 40 CFR 60.5375a. [40 CFR 60.5375a(a)(1)(i)]

317 [40 CFR 60.5375a(a)(1)(ii)] During the separation flowback stage, route all recovered liquids from the separator to one or more well completion vessels or storage vessels, re-inject the recovered liquids into the well or another well, or route the recovered liquids to a collection system. Route the recovered gas from the separator into a gas flow line or collection system, re-inject the recovered gas into the well or another well, use the recovered gas as an onsite fuel source, or use the recovered gas for another useful purpose that a purchased fuel or raw material would serve. If it is technically infeasible to route the recovered gas as required above, follow the requirements in 40 CFR 60.5375a(a)(3). If, at any time during the separation flowback stage, it is technically infeasible for a separator to function, comply with 40 CFR 60.5375a (a)(1)(i). [40 CFR 60.5375a(a)(1)(ii)]

318 [40 CFR 60.5375a(a)(1)(iii)(C)] The owner or operator of a well that meets the criteria of 40 CFR 60.5375a(a)(1)(iii)(A) or (B) must submit the report in 40 CFR 60.5420a (b)(2) and maintain the records in 40 CFR 60.5420a(c)(1)(iii)(C). [40 CFR 60.5375a(a)(1)(iii)(C)]

319 [40 CFR 60.5375a(a)(1)(iii)] Have a separator onsite during the entirety of the flowback period, except as provided in 40 CFR 60.5375a(a)(1)(iii)(A)-(C). [40 CFR 60.5375a(a)(1)(iii)]

320 [40 CFR 60.5375a(a)(3)] If it is technically infeasible to route the recovered gas as required in 40 CFR 60.5375a(a)(1)(ii), capture and direct recovered gas to a completion combustion device, except in conditions that may result in a fire hazard or explosion, or where high heat emissions from a completion combustion device may negatively impact waterways. Completion combustion devices must be equipped with a reliable continuous pilot flame. [40 CFR 60.5375a(a)(3)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024p001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### EMS 0003 - Wells Subject to NSPS OOOOa

- 321 [40 CFR 60.5375(a)(4)]  
You have a general duty to safely maximize resource recovery and minimize releases to the atmosphere during flowback and subsequent recovery. [40 CFR 60.5375(a)(4)]
- Except as provided in 40 CFR 60.5375(a)(f) and (g), for each well completion operation with hydraulic fracturing, comply with the requirements in 40 CFR 60.5375(a)(1)-(4). Maintain a log as specified in 40 CFR 60.5375(a)]. [40 CFR 60.5375(a)]
- Maintain a log for each well completion operation at each well. The log must be completed on a daily basis for the duration of the well completion operation and must contain the records specified in 40 CFR 60.5420(a)(1)(iii). [40 CFR 60.5375(a)(b)]
- Demonstrate initial compliance with the standards that apply to wells as required by 40 CFR 60.5410(a). [40 CFR 60.5375(a)(c)]
- Demonstrate continuous compliance with the standards that apply to wells as required by 40 CFR 60.5415(a). [40 CFR 60.5375(a)(d)]
- Perform the required notification, recordkeeping and reporting as required by 40 CFR 60.5420(a)(2), (b)(1) and (2), and (c)(1). [40 CFR 60.5375(a)(e)]
- For each well completion operation with hydraulic fracturing at a wildcat or delineation well or at a non-wildcat low pressure well or non-delineation low pressure well, comply with either 40 CFR 60.5375(a)(f)(3)(i) or (ii), unless you meet the requirements in 40 CFR 60.5375(a)(g). Also comply with 40 CFR 60.5375(a)(b). [40 CFR 60.5375(a)(f)(1)-(3)]
- Submit the notification as specified in 40 CFR 60.5420(a)(2), submit annual reports as specified in 40 CFR 60.5420(a)(b)(1) and (2), and maintain records specified in 40 CFR 60.5420(a)(c)(1)(iii) for each wildcat and delineation well. Submit the notification as specified in 40 CFR 60.5420(a)(2), submit annual reports as specified in 40 CFR 60.5420(a)(b)(1) and (2), and maintain records as specified in 40 CFR 60.5420(a)(c)(1)(iii) and (vii) for each low pressure well. [40 CFR 60.5375(a)(f)(4)]
- For each well with less than 300 scf of gas per stock tank barrel of oil produced, maintain records specified in 40 CFR 60.5420(a)(c)(1)(vi) and submit reports specified in 40 CFR 60.5420(a)(b)(1) and (2). [40 CFR 60.5375(a)(g)]
- If you are the owner or operator of a well affected facility as described in 40 CFR 60.5365(a) that also meets the criteria for a well affected facility in 40 CFR 60.5365(a) (in Subpart OOOO), comply with 40 CFR 60.5375(a) through (g). If you own or operate a well affected facility as described in 40 CFR 60.5365(a)(a) that does not meet the criteria for a well affected facility in 40 CFR 60.5365(a) (in Subpart OOOO), comply with 40 CFR 60.5375(a)(3) and (4) or 40 CFR 60.5375(a)(g) for each well completion operation with hydraulic fracturing prior to November 30, 2016, and with 40 CFR 60.5375(a) through (g) for each well completion operation with hydraulic fracturing on or after November 30, 2016. Subpart OOOOa.
- To achieve initial compliance with the methane and VOC standards for each well completion operation conducted at your well, comply with 40 CFR 60.5410(a)(1)-(4). [40 CFR 60.5410(a)]
- For each well, demonstrate continuous compliance by submitting the reports required by 40 CFR 60.5420(a)(b)(1) and (2) and maintaining the records for each completion operation specified in 40 CFR 60.5420(a)(c)(1). [40 CFR 60.5415(a)]
- Submit a notification to the Administrator no later than 2 days prior to the commencement of each well completion operation listing the anticipated date of the well completion operation. The notification shall include contact information for the owner or operator; the United States Well Number; the latitude and longitude coordinates for each well in decimal degrees to an accuracy and precision of five (5) decimals of a degree using the North American Datum of 1983; and the planned date of the beginning of flowback. You may submit the notification in writing or in electronic format. [40 CFR 60.5420(a)(2)(i)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### **EQT\_0048 - Reciprocating Compressors Subject to NSPS OOOa**

334 [40 CFR 60.5385a(a)(1) and (2)]

Replace the reciprocating compressor rod packing according to either (1) or (2) below.  
(1) On or before the compressor has operated for 26,000 hours. The number of hours of operation must be continuously monitored beginning upon initial startup of your reciprocating compressor, or the date of the most recent reciprocating compressor rod packing replacement, whichever is later.

(2) Prior to 36 months from the date of the most recent rod packing replacement, or 36 months from the date of startup for a new reciprocating compressor for which the rod packing has not yet been replaced. [40 CFR 60.5385a(a)(1) and (2)]

335 [40 CFR 60.5385a(a)(3)]

As an alternative to replacing the rod packing, collect the methane and VOC emissions from the rod packing using a rod packing emissions collection system that operates under negative pressure and route the rod packing emissions to a process through a closed vent system that meets the requirements of 40 CFR 60.5411a(a) and (d). [40 CFR 60.5385a(a)(3)]

336 [40 CFR 60.5385a(b)]

Demonstrate initial compliance with standards that apply to reciprocating compressors as required by 40 CFR 60.5410a(c). [40 CFR 60.5385a(b)]

337 [40 CFR 60.5385a(c)]

Demonstrate continuous compliance with standards that apply to reciprocating compressors as required by 40 CFR 60.5415a(c). [40 CFR 60.5385a(c)]  
Perform the reporting as required by 40 CFR 60.5420a(b)(1) and (4) and the recordkeeping as required by 40 CFR 60.5420a(c)(3), (6)-(9), and (17), as applicable. [40 CFR 60.5385a(d)]

338 [40 CFR 60.5385a(d)]

To achieve initial compliance with the standards for each reciprocating compressor, comply with 40 CFR 60.5410a(c)(1)-(4). [40 CFR 60.5410a(c)]

339 [40 CFR 60.5410a(c)]

Closed vent system requirements:

- (1) Design the closed vent system to route all gases, vapors, and fumes emitted from the material in the reciprocating compressor rod packing emissions collection system to a process.
- (2) Design and operate the closed vent system with no detectable emissions as demonstrated by 40 CFR 60.5416a(b).
- (3) Meet the requirements specified in 40 CFR 60.5411a(a)(3)(i) and (ii) if the closed vent system contains one or more bypass devices that could be used to divert all or a portion of the gases, vapors, or fumes from entering the control device. Subpart OOOOa. [40 CFR 60.5411a(a)(3)(i) and (ii).]

(a)

Closed vent systems requirements for reciprocating compressors using a control device or routing emissions to a process: Conduct an assessment that the closed vent system is of sufficient design and capacity to ensure that all emissions from the reciprocating compressor are routed to the control device and that the control device is of sufficient design and capacity to accommodate all emissions from the reciprocating compressor and have it certified by a qualified professional engineer in accordance with 40 CFR 60.5411a(d)(1) and (ii). [40 CFR 60.5411a(d)]  
For each reciprocating compressor complying with 40 CFR 60.5385a(a)(1) or (2), demonstrate continuous compliance according to 40 CFR 60.5415a(c)(1)-(3). For each reciprocating compressor complying with 40 CFR 60.5385a(a)(3), demonstrate continuous compliance according to 40 CFR 60.5415a(c)(4). [40 CFR 60.5415a(c)]

Except as provided in 40 CFR 60.5416a(b)(11) and (12), inspect each closed vent system according to the procedures and schedule specified in 40 CFR 60.5416a(a)(1) and (2), inspect each cover according to the procedures and schedule specified in 40 CFR 60.5416a(a)(4). Subpart OOOOa. [40 CFR 60.5416a(a)(4)]  
(3), and inspect each bypass device according to the procedures of 40 CFR 60.5416a(a)(4). No detectable emissions test methods and procedures. If you are required to conduct an inspection of a closed vent system or cover as specified in 40 CFR 60.5416a(a)(1), (2), or (3), meet the requirements of 40 CFR 60.5416a(b)(1) through (13). Subpart OOOOa. [40 CFR 60.5416a(b)]

340 [40 CFR 60.5411a(d)]

341 [40 CFR 60.5415a(c)]

Closed vent systems requirements for reciprocating compressors using a control device or routing emissions to a process: Conduct an assessment that the closed vent system is of sufficient design and capacity to ensure that all emissions from the reciprocating compressor are routed to the control device and that the control device is of sufficient design and capacity to accommodate all emissions from the reciprocating compressor and have it certified by a qualified professional engineer in accordance with 40 CFR 60.5411a(d)(1) and (ii). [40 CFR 60.5411a(d)]  
For each reciprocating compressor complying with 40 CFR 60.5385a(a)(1) or (2), demonstrate continuous compliance according to 40 CFR 60.5415a(c)(1)-(3). For each reciprocating compressor complying with 40 CFR 60.5385a(a)(3), demonstrate continuous compliance according to 40 CFR 60.5415a(c)(4). [40 CFR 60.5415a(c)]

342 [40 CFR 60.5416a(a)]

Except as provided in 40 CFR 60.5416a(b)(11) and (12), inspect each closed vent system according to the procedures and schedule specified in 40 CFR 60.5416a(a)(1) and (2), inspect each cover according to the procedures and schedule specified in 40 CFR 60.5416a(a)(4). Subpart OOOOa. [40 CFR 60.5416a(a)(4)]  
(3), and inspect each bypass device according to the procedures of 40 CFR 60.5416a(a)(4). No detectable emissions test methods and procedures. If you are required to conduct an inspection of a closed vent system or cover as specified in 40 CFR 60.5416a(a)(1), (2), or (3), meet the requirements of 40 CFR 60.5416a(b)(1) through (13). Subpart OOOOa. [40 CFR 60.5416a(b)]

**SPECIFIC REQUIREMENTS**  
**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

**EQT 0049 - Pneumatic Controllers Subject to NSPS OOOa**

- 345 [40 CFR 60.5390a(c)]  
Each pneumatic controller must have a bleed rate less than or equal to 6 standard cubic feet per hour and be tagged with the month and year of installation, reconstruction or modification, and identification information that allows traceability to the records for that controller as required in 40 CFR 60.5420(a)(c)(4)(ii). This requirement is not applicable if you determine that the use of a pneumatic controller with a bleed rate greater than the applicable standard is required based on functional needs, including but not limited to response time, safety and positive actuation. However, you must tag such pneumatic controller with the month and year of installation, reconstruction or modification, and identification information that allows traceability to the records for that pneumatic controller, as required in 40 CFR 60.5420(a)(c)(4)(ii). [40 CFR 60.5390a(c)]
- 346 [40 CFR 60.5390a(d)]  
Demonstrate initial compliance with standards that apply to pneumatic controllers as required by 40 CFR 60.5415a(d). [40 CFR 60.5390a(d)]
- 347 [40 CFR 60.5390a(e)]  
Demonstrate continuous compliance with standards that apply to pneumatic controllers as required by 40 CFR 60.5415a(d). [40 CFR 60.5390a(e)]
- 348 [40 CFR 60.5390a(f)]  
Perform the reporting as required by 40 CFR 60.5420a(b)(1) and (5) and the recordkeeping as required by 40 CFR 60.5420a(c)(4). [40 CFR 60.5390a(f)]
- 349 [40 CFR 60.5410a(d)]  
To achieve initial compliance with methane and VOC emission standards for your pneumatic controller, comply with the requirements specified in 40 CFR 60.5410a(d)(1)-(6), as applicable. [40 CFR 60.5410a(d)]
- 350 [40 CFR 60.5415a(d)]  
For each pneumatic controller, demonstrate continuous compliance according to 40 CFR 60.5415a(d)(1)-(3). [40 CFR 60.5415a(d)]

**EQT 0050 - Pneumatic Pumps Subject to NSPS OOOa**

- 351 [40 CFR 60.5393a(b)(1)]  
On or after November 30, 2016, if the pneumatic pump is located at a greenfield site as defined in 40 CFR 60.5430a, reduce natural gas emissions by 95.0 percent, except as provided in 40 CFR 60.5393a(b)(3) and (4). [40 CFR 60.5393a(b)(1)]
- 352 [40 CFR 60.5393a(b)(2)]  
On or after November 30, 2016, if the pneumatic pump is not located at a greenfield site as defined in 40 CFR 60.5430a, reduce natural gas emissions by 95.0 percent, except as provided in 40 CFR 60.5393a(b)(3), (4) and (5). [40 CFR 60.5393a(b)(2)]
- 353 [40 CFR 60.5393a(b)(3)]  
You are not required to install a control device solely for the purpose of complying with the 95.0 percent reduction requirement of 40 CFR 60.5393a(b)(1) or (2). If you do not have a control device installed on site by the compliance date and you do not have the ability to route to a process, submit a certification in accordance with 40 CFR 60.5420a(b)(8)(i)(A) in your next annual report, certifying that there is no available control device or process on site and maintain the records in 40 CFR 60.5420a(c)(16)(i) and (ii). If you subsequently install a control device or have the ability to route to a process, you are no longer required to comply with 40 CFR 60.5393a(b)(2)(i) and must submit the information in 40 CFR 60.5420a(b)(8)(ii) in your next annual report and maintain the records in 40 CFR 60.5420a(c)(16)(i), (ii), and (iii). Be in compliance with the requirements of 40 CFR 60.5393a(b)(2) within 30 days of startup of the control device or within 30 days of the ability to route to a process. [40 CFR 60.5393a(b)(3)]
- 354 [40 CFR 60.5393a(b)(4)]  
If the control device available on site is unable to achieve a 95 percent reduction and there is no ability to route the emissions to a process, you must still route the pneumatic pump's emissions to that existing control device. If you route the pneumatic pump to a control device installed on site that is designed to achieve less than a 95 percent reduction, submit the information specified in 40 CFR 60.5420a(b)(8)(i)(C) in your next annual report and maintain the records in 40 CFR 60.5420a(c)(16)(iii). [40 CFR 60.5393a(b)(4)]
- 355 [40 CFR 60.5393a(b)(5)]  
If an owner or operator at a non-greenfield site determines, through an engineering assessment, that routing a pneumatic pump to a control device or a process is technically infeasible, the requirements specified in 40 CFR 60.5393a(b)(5)(i)-(iv) must be met. Conduct the assessment of technical infeasibility in accordance with the criteria in 40 CFR 60.5393a(b)(5)(iii) and have it certified by a qualified professional engineer in accordance with 40 CFR 60.5393a(b)(5)(ii). Maintain the records in 40 CFR 60.5420a(c)(16)(iv). [40 CFR 60.5393a(b)(5)]

**EQT\_0050 - Pneumatic Pumps Subject to NSPS OOOOa**

356 [40 CFR 60.5393(a)(b)(6)]  
If the pneumatic pump is routed to a control device or a process and the control device or process is subsequently removed from the location or is no longer available, you are no longer required to be in compliance with the requirements of 40 CFR 60.5393(a)(b)(1) or (2), and instead must comply with 40 CFR 60.5393a(b)(3) and report the change in next annual report in accordance with 40 CFR 60.5420a(b)(8)(ii). [40 CFR 60.5393a(b)(6)]

357 [40 CFR 60.5393(a)(c)]  
If you use a control device or route to a process to reduce emissions, connect the pneumatic pump through a closed vent system that meets the requirements of 40 CFR 60.5411a(a) and (d). [40 CFR 60.5393a(c)]

358 [40 CFR 60.5393(a)(d)]  
Demonstrate initial compliance with standards that apply to pneumatic pumps as required by 40 CFR 60.5410a(e). [40 CFR 60.5393a(d)]

359 [40 CFR 60.5393a(e)]  
Perform the reporting as required by 40 CFR 60.5420a(b)(1) and (8) and the recordkeeping as required by 40 CFR 60.5420a(c)(6)-(10), (16), and (17), as applicable. [40 CFR 60.5393a(e)]

360 [40 CFR 60.5410a(e)]  
To achieve initial compliance with emission standards for your pneumatic pump, comply with the requirements specified in 40 CFR 60.5410a(e)(2)-(7), as applicable.

(1) If you own or operate a pneumatic pump not located at a natural gas processing plant, reduce emissions in accordance 40 CFR 60.5393a(b)(1) or (2), and collect the pneumatic pump emissions through a closed vent system that meets the requirements of 40 CFR 60.5411a(a) and (d).

(2) If you own or operate a pneumatic pump not located at a natural gas processing plant and there is no control device or process available on site, submit the certification in 40 CFR 60.5420a(b)(8)(i)(A).

(3) If you own or operate a pneumatic pump not located at a natural gas processing plant or a greenfield site, and you are unable to route to an existing control device due to technical infeasibility, and you are unable to route to a process, submit the certification in 40 CFR 60.5420a(b)(8)(i)(B).

(4) If you own or operate a pneumatic pump not located other than at a natural gas processing plant and you reduce emissions in accordance with 40 CFR 60.5393a(b)(4), collect the pneumatic pump emissions through a closed vent system that meets the requirements of 40 CFR 60.5411a(c) and (d).

(5) Submit the initial annual report for your pneumatic pump required in 40 CFR 60.5420a(b)(1) and (8).

(6) Maintain the records as specified in 40 CFR 60.5420a(c)(6), (8)-(10), (16), and (17), as applicable, for each pneumatic pump. [40 CFR 60.5410a(e)]

361 [40 CFR 60.5411a(d)]  
Closed vent systems requirements for pneumatic pumps using a control device or routing emissions to a process: Conduct an assessment that the closed vent system is of sufficient design and capacity to ensure that all emissions from the pneumatic pump are routed to the control device and that the control device is of sufficient design and capacity to accommodate all emissions from the pneumatic pump and have it certified by a qualified professional engineer in accordance with 40 CFR 60.5411a(d)(1)(i) and (ii). [40 CFR 60.5411a(d)]

362 [40 CFR 60.5415a(b)]  
For each pneumatic pump, demonstrate continuous compliance according to 40 CFR 60.5415a(b)(3). [40 CFR 60.5415a(b)]

363 [40 CFR 60.5416a(d)]  
If you install a control device or route emissions to a process, comply with the inspection and recordkeeping requirements for each closed vent system as specified in 40 CFR 60.5416a(d)(1). Also comply with the requirements of 40 CFR 60.5416a(c)(3) through (7). Subpart OOOOa. [40 CFR 60.5416a(d)]

**EQT\_0051 - Storage Vessels Subject to NSPS OOOOa**

364 [40 CFR 60.5395a(a)(1)]  
Determine the potential for VOC emissions in accordance with 40 CFR 60.5365a(e). [40 CFR 60.5395a(a)(1)]

365 [40 CFR 60.5395a(a)(2)]  
Reduce VOC emissions by 95.0 percent within 60 days after startup. For storage vessels receiving liquids pursuant to the standards for wells in 40 CFR 60.5375a(a)(1)(i) or (ii), achieve the required emissions reductions within 60 days after startup of production as defined in 40 CFR 60.5430a. [40 CFR 60.5395a(a)(2)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### EQT 0051 - Storage Vessels Subject to NSPS 0000a

- 366 [40 CFR 60.5395(a)(3)(i)]  
If a well feeding the storage vessel undergoes fracturing or refracturing, comply with 40 CFR 60.5395(a)(2) as soon as liquids from the well following fracturing or refracturing are routed to the storage vessel. [40 CFR 60.5395(a)(3)(ii)]
- 367 [40 CFR 60.5395(a)(3)(ii)]  
If the monthly emissions determination required in 40 CFR 60.5395a indicates that VOC emissions from your storage vessel increase to 4 tpy or greater and the increase is not associated with fracturing or refracturing of a well feeding the storage vessel, comply with 40 CFR 60.5395(a)(2) within 30 days of the monthly determination. [40 CFR 60.5395(a)(3)(iii)]
- 368 [40 CFR 60.5395(a)(3)]  
Maintain the uncontrolled actual VOC emissions from the storage vessel at less than 4 tpy without considering control. Prior to using the uncontrolled actual VOC emission rate for compliance purposes, demonstrate that the uncontrolled actual VOC emissions have remained less than 4 tpy as determined monthly for 12 consecutive months. After such demonstration, you must determine the uncontrolled actual VOC emission rate each month. The uncontrolled actual VOC emissions must be calculated using a generally accepted model or calculation methodology, and the calculations must be based on the average throughput for the month. [40 CFR 60.5395(a)(3)]
- 369 [40 CFR 60.5395(a)]  
Comply with the requirements of 40 CFR 60.5395(a)(1) and (2). After 12 consecutive months of compliance with 40 CFR 60.5395(a)(1) and (2), you may continue to comply with 40 CFR 60.5395(a)(2), or you may comply with 40 CFR 60.5395(a)(3), if applicable. [40 CFR 60.5395(a)]
- 370 [40 CFR 60.5395(a)(1)]  
If you use a control device (other than a floating roof) to reduce VOC emissions from your storage vessel, equip the storage vessel with a cover that meets the requirements of 40 CFR 60.5411(a)(b) and is connected through a closed vent system that meets the requirements of 40 CFR 60.5411(a)(c) and (d), and route emissions to a control device that meets the conditions specified in 40 CFR 60.5412(a)(c) or (d). As an alternative to routing the closed vent system to a control device, you may route the closed vent system to a process. [40 CFR 60.5395(a)(1)]
- 371 [40 CFR 60.5395(a)(2)]  
If you use a floating roof to reduce emissions, meet the requirements of 40 CFR 60.112b(a)(1) or (2) and the relevant monitoring, inspection, recordkeeping, and reporting requirements in 40 CFR 60 Subpart Kb. [40 CFR 60.5395(a)(2)]
- 372 [40 CFR 60.5395(a)(1)]  
If you remove a storage vessel from service, completely empty and degas the storage vessel no longer contains crude oil, condensate, produced water or intermediate hydrocarbon liquids. A storage vessel where liquid is left on walls, as bottom clinging or in pools due to floor irregularity is considered to be completely empty. Submit a notification as required in 40 CFR 60.5420a(b)(6)(v) in your next annual report, identifying each storage vessel removed from service during the reporting period and the date of its removal from service. [40 CFR 60.5395(a)(1)]
- 373 [40 CFR 60.5395(a)(2) and (3)]  
If a storage vessel is returned to service, determine its affected facility status as provided in 40 CFR 60.5365(a)(e). Submit a notification in your next annual report as required in 40 CFR 60.5420a(b)(6)(vi), identifying each storage vessel and the date of its return to service. [40 CFR 60.5395(a)(2) and (3)]
- 374 [40 CFR 60.5410a(d)]  
Demonstrate initial compliance with standards as required by 40 CFR 60.5410a(h) and (i). Demonstrate continuous compliance with standards as required by 40 CFR 60.5415a(e)(3). Perform the required reporting as required by 40 CFR 60.5420a(b)(1) and (6) and the recordkeeping as required by 40 CFR 60.5420a(c)(5)-(8), (12)-(14), and (17), as applicable. [40 CFR 60.5410a(d)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### EQT\_0051 - Storage Vessels Subject to NSPS OOOOa

For each storage vessel, comply with 40 CFR 60.5410a(h)(1)-(6). Demonstrate initial compliance by August 2, 2016, or within 60 days after startup, whichever is later.

- (1) Determine the potential VOC emission rate as specified in 40 CFR 60.5365a(e).
- (2) Reduce VOC emissions in accordance with 40 CFR 60.5395a(a).
- (3) If you use a control device to reduce emissions, equip the storage vessel with a cover that meets the requirements of 40 CFR 60.5411a(b) and is connected through a closed vent system that meets the requirements of 40 CFR 60.5411a(c) and (d) to a control device that meets the conditions specified in 40 CFR 60.5412a(d) within 60 days after startup for storage vessels constructed, modified or reconstructed at well sites with no other wells in production, or upon startup for storage vessels constructed, modified or reconstructed at well sites with one or more wells already in production.

(4) Conduct an initial performance test as required in 40 CFR 60.5413a within 180 days after initial startup or within 180 days of August 2, 2016, whichever is later, and you must comply with the continuous compliance requirements in 40 CFR 60.5415a(e).

(5) Submit the information required for your storage vessel in your initial annual report as specified in 40 CFR 60.5420a(b)(1) and (6).

- (6) Maintain the records required for your storage vessel, as specified in 40 CFR 60.5420a(c)(5)-(8), (12)-(14), and (17), as applicable, for each storage vessel. [40 CFR 60.5410a(h)]

(7) For each storage vessel that complies by using a floating roof, submit a statement that you are complying with 40 CFR 60.112(b)(a)(1) or (2), in accordance with 40 CFR 60.5395a(b)(2) with the initial annual report specified in 40 CFR 60.5420a(b). [40 CFR 60.5410a(i)]

Cover requirements for storage vessels:

- (1) The cover and all openings on the cover (e.g., access hatches, sampling ports, pressure relief devices and gauge wells) shall form a continuous impermeable barrier over the entire surface area of the liquid in the storage vessel.
- (2) Each cover opening shall be secured in a closed, sealed position (e.g., covered by a gasketed lid or cap) whenever material is in the unit on which the cover is installed except during those times when it is necessary to use an opening as described in 40 CFR 60.5411a(b)(2)(i)-(iv).

(3) Each storage vessel thief hatch shall be equipped, maintained and operated with a weighted mechanism or equivalent, to ensure that the lid remains properly seated and sealed under normal operating conditions, including such times when working, standing/breathing, and flash emissions may be generated. Select gasket material for the hatch based on composition of the fluid in the storage vessel and weather conditions. Subpart OOOOa. [40 CFR 60.5411a(b)]

Closed vent system requirements for storage vessels using a control device or routing emissions to a process:

- (1) Design the closed vent system to route all gases, vapors, and fumes emitted from the material in the storage vessel to a control device that meets the requirements specified in 40 CFR 60.5412a(c) and (d), or to a process.
- (2) Design and operate a closed vent system with no detectable emissions, as determined using olfactory, visual and auditory inspections.
- (3) Meet the requirements specified in 40 CFR 60.5411a(c)(3)(i) and (ii) if the closed vent system contains one or more bypass devices that could be used to divert all or a portion of the gases, vapors, or fumes from entering the control device or to a process. [40 CFR 60.5411a(c)]

Closed vent systems requirements for storage vessels using a control device or routing emissions to a process: Conduct an assessment that the closed vent system is of sufficient design and capacity to ensure that all emissions from the storage vessel are routed to the control device and that the control device is of sufficient design and capacity to accommodate all emissions from the storage vessel and have it certified by a qualified professional engineer in accordance with 40 CFR 60.5411a(d)(1)(i) and (ii). [40 CFR 60.5411a(d)]

**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

**SPECIFIC REQUIREMENTS**

**EQT\_0051 - Storage Vessels Subject to NSPS OOOOa**

380 [40 CFR 60.5412a(d)]  
Each control device used to meet the emission reduction standard in 40 CFR 60.5395(a)(2) for your storage vessel must be installed according to 40 CFR 60.5412a(d)(1)-(4), as applicable. As an alternative to 40 CFR 60.5412a(d)(1), you may install a control device model tested under 40 CFR 60.5413a(d), which meets the criteria in 40 CFR 60.5413a(d)(11) and meet the continuous compliance requirements in 40 CFR 60.5413a(e). [40 CFR 60.5412a(d)]

Demonstrate continuous compliance according to 40 CFR 60.5415a(e)(3) for each storage vessel, for which you are using a control device or routing emissions to a process to meet the requirement of 40 CFR 60.5395(a)(2). [40 CFR 60.5415a(e)]

Cover and closed vent system inspections for storage vessels: If you install a control device or route emissions to a process, inspect each closed vent system according to the procedures and schedule specified in 40 CFR 60.5416a(c)(1), inspect each cover according to the procedures and schedule specified in 40 CFR 60.5416a(c)(2), and inspect each bypass device according to the procedures of 40 CFR 60.5416a(c)(3). Also comply with the requirements of 40 CFR 60.5416a(c)(4)-(7). [40 CFR 60.5416a(c)]

For each control device used to comply with the emission reduction standard in 40 CFR 60.5395a(a)(2) for your storage vessel, demonstrate continuous compliance according to 40 CFR 60.5417a(h)(1)-(4). You are exempt from the requirements of this 40 CFR 60.5417a(h) if you install a control device model tested in accordance with 40 CFR 60.5413a(d)(2)-(10), which meets the criteria in 40 CFR 60.5413a(d)(11), the reporting requirement in 40 CFR 60.5413a(d)(12), and meet the continuous compliance requirement in 40 CFR 60.5413a(e). [40 CFR 60.5417a(h)]

**EQT\_0063 - Super-Emitter Events Subject to NSPS OOOOa**

If you do not own or operate an oil and natural gas facility within 50 meters from the latitude and longitude provided in the notification subject to the regulation under Subpart OOOOa, report this result to the EPA. Subpart OOOOa. [40 CFR 60.5371(a)(1)]

If you own or operate an oil and natural gas facility within 50 meters from the latitude and longitude provided in the notification, and there is an affected facility or associated equipment subject to Subpart OOOOa onsite, investigate to determine the source of the super-emitter event in accordance with 40 CFR 60.5371a(a)(2), maintain records of your investigation, and report the results in accordance with 40 CFR 60.5371a(b). Subpart OOOOa. [40 CFR 60.5371a(a)(2)]

The investigation required by 40 CFR 60.5371a(a)(2) may include but is not limited to the actions specified in 40 CFR 60.5371(a)(3)(i) through (iv). Subpart OOOOa. [40 CFR 60.5371a(a)(3)]

Submit the results of the super-emitter event investigation conducted under 40 CFR 60.5371a(a) to the EPA in accordance with 40 CFR 60.5371a(b)(1). If the super-emitter event (i.e., emission at 100 kg/hr of methane or more) is ongoing at the time of the initial report, submit the additional information in accordance with 40 CFR 60.5371a(b)(2). Attest to the information included in the report as specified in 40 CFR 60.5371a(b)(3). Subpart OOOOa. [40 CFR 60.5371a(b)]

Upon receiving a notification of a super emitter event issued by the EPA under 40 CFR 60.5371b(c), owners or operators must take the actions listed in 40 CFR 60.5371(a) and (b). Within 5 calendar days of receiving a notification from the EPA of a super-emitter event, the owner or operator of an oil and natural gas facility must initiate a super-emitter event investigation. Subpart OOOOa.

**FUG\_0004 - Fugitive Emissions Subject to NSPS OOOOa**

389 [40 CFR 60.5397a(a)]  
Monitor all fugitive emission components, as defined in 40 CFR 60.5430a, in accordance with 40 CFR 60.5397a(b)-(g). Repair all sources of fugitive emissions in accordance with 40 CFR 60.5397a(h). Keep records in accordance with 40 CFR 60.5397a(i) and report in accordance with 40 CFR 60.5397a(j). For purposes of 40 CFR 60.5397a, fugitive emissions are defined as: any visible emission from a fugitive emissions component observed using optical gas imaging or an instrument reading of 500 ppm or greater using Method 21. [40 CFR 60.5397a(a)]

**FUG 0004 - Fugitive Emissions Subject to NSPS OOOa**

- Develop an emissions monitoring plan that covers the collection of fugitive emissions components at well sites and compressor stations within each company-defined area in accordance with 40 CFR 60.5397(a)(c) and (d). [40 CFR 60.5397(a)(b)]  
Fugitive emissions monitoring plans must include the elements specified in 40 CFR 60.5397(a)(1)-(8). [40 CFR 60.5397(a)(c)]  
Each fugitive emissions monitoring plan must include the information described in 40 CFR 60.5397(a)(1)-(4). [40 CFR 60.5397(a)(d)]  
Each monitoring survey shall observe each fugitive emissions component, as defined in 40 CFR 60.5430a, for fugitive emissions. [40 CFR 60.5397(a)(e)]
- Conduct an initial monitoring survey within 90 days of the startup of production, as defined in 40 CFR 60.5430a, for each collection of fugitive emissions components at a new well site or by June 3, 2017, whichever is later. For a modified collection of fugitive emissions components at a well site, the initial monitoring survey must be conducted within 90 days of the first day of production for each collection of fugitive emission components after the modification or by June 3, 2017, whichever is later. [40 CFR 60.5397(a)(f)(1)]
- Conduct an initial monitoring survey within 90 days of the startup of a new compressor station for each new collection of fugitive emissions components at the new compressor station or by June 3, 2017, whichever is later. For a modified collection of fugitive components at a compressor station, the initial monitoring survey must be conducted within 90 days of the modification or by June 3, 2017, whichever is later. [40 CFR 60.5397(a)(f)(2)]
- A monitoring survey of each collection of fugitive emissions components at a well site or at a compressor station must be performed at the frequencies specified in 40 CFR 60.5397(a)(1) and (2), with the exceptions noted in 40 CFR 60.5397(a)(3) through (6). Subpart OOOa.
- [40 CFR 60.5397(a)(g)]
- Delay of repair will be allowed if the conditions in 40 CFR 60.5397(a)(3)(i) or (ii) are met. Subpart OOOa. [40 CFR 60.5397(a)(3)]  
Each identified source of fugitive emissions shall be repaired or replaced in accordance with 40 CFR 60.5397(a)(1) and (2). For fugitive emissions components also subject to the repair provisions of 40 CFR 60.5416a(b)(9)-(12) and (c)(4)-(7), those provisions apply instead to those closed vent systems and covers, and the repair provisions of 40 CFR 60.5397(a)(1) and (2) do not apply to those closed vent systems and covers. [40 CFR 60.5397(a)(h)]

- Maintain records for each monitoring survey as specified 40 CFR 60.5420a(c)(15). [40 CFR 60.5397(a)(i)]  
Annual reports shall be submitted for each collection of fugitive emissions components at a well site and each collection of fugitive emissions components at a compressor station that include the information specified in 40 CFR 60.5420a(b)(7). Multiple collections of fugitive emissions components at a well site or at a compressor station may be included in a single annual report. [40 CFR 60.5397(a)(j)]  
To achieve initial compliance with the fugitive emission standards for each collection of fugitive emissions components at a well site and each collection of fugitive emissions components at a compressor station, comply with 40 CFR 60.5410a(j)(1)-(5).  
(1) Develop a fugitive emissions monitoring plan as required in 40 CFR 60.5397(a)(b), (c), and (d).  
(2) Conduct an initial monitoring survey as required in 40 CFR 60.5397(a)(f).  
(3) Maintain the records specified in 40 CFR 60.5420a(c)(15).  
(4) Repair each identified source of fugitive emissions for each affected facility as required in 40 CFR 60.5397(a)(h).  
(5) Submit the initial annual report for each collection of fugitive emissions components at a well site and each collection of fugitive emissions components at a compressor station as required in 40 CFR 60.5420a(b)(1) and (7). [40 CFR 60.5410a(j)]  
For each collection of fugitive emissions components at a well site and each collection of fugitive emissions components at a compressor station, demonstrate continuous compliance with the fugitive emission standards specified in 40 CFR 60.5397a according to 40 CFR 60.5415a(h)(1)-(4). [40 CFR 60.5415a(h)]

## **PCS 0011 Affected Facilities Subject to NSPS OOOOb**

### **CRG 0007 - General Requirements under NSPS OOOOb**

Group Members: EMS 0004 EQT 0052 EQT 0053 EQT 0054 EQT 0055 EQT 0056 EQT 0057 EQT 0058 EQT 0059 EQT 0060 EQT 0061 EQT 0062 EQT 0063 EQT 0064 EQT 0065 EQT 0066 EQT 0067 EQT 0068 EQT 0069 EQT 0070 EQT 0071 EQT 0072 EQT 0073 EQT 0074 EQT 0075 EQT 0076 EQT 0077 EQT 0078 EQT 0079 EQT 0080 EQT 0081 EQT 0082 EQT 0083 EQT 0084 EQT 0085 EQT 0086 EQT 0087 EQT 0088 EQT 0089 EQT 0090 EQT 0091 EQT 0092 EQT 0093 EQT 0094 EQT 0095 EQT 0096 EQT 0097 EQT 0098 EQT 0099 EQT 00905

Be in compliance with the standards of Subpart OOOOb no later than May 7, 2024, or upon initial startup, whichever date is later, except as specified in 40 CFR 60.5370b(a)(1) for reciprocating compressor affected facilities, 40 CFR 60.5370b(a)(2) and (3) for storage vessel affected facilities, 40 CFR 60.5370b(a)(5) for process controllers, 40 CFR 60.5370b(a)(6) for pumps, 40 CFR 60.5370b(a)(7) for centrifugal compressor affected facilities, and 40 CFR 60.5377b(b) or (c) for associated gas wells. Subpart OOOOb. [40 CFR 60.5370b(a)] At all times, including periods of startup, shutdown, and malfunction, maintain and operate any affected facility including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. Subpart OOOOb. [40 CFR 60.5370b(b)]

Submit notifications according to 40 CFR 60.5420b(a)(1) and (2) if you own or operate one or more of the affected facilities specified in 40 CFR 60.5365b that was constructed, modified, or reconstructed during the reporting period. Submit the notification in 40 CFR 60.5420b(a)(3) if you use an alternative standard for fugitive emissions components in accordance with 40 CFR 60.5399b. Submit the notification in 40 CFR 60.5420b(a)(4) if you undertake well closure activities as specified in 40 CFR 60.5397b(l). Subpart OOOOb. [40 CFR 60.5420b(a)]

Submit annual reports containing the information specified in 40 CFR 60.5420b(b)(1) through (14) following the procedure specified in 40 CFR 60.5420b(b)(15). Submit performance test reports as specified in 40 CFR 60.5420b(b)(12) or (13), if applicable. The initial annual report is due no later than 90 days after the end of the initial compliance period as determined according to 40 CFR 60.5410b. Subsequent annual reports are due no later than the same date each year as the initial annual report. If you own or operate more than one affected facility, you may submit one report for multiple affected facilities provided the report contains all of the information required as specified in 40 CFR 60.5420b(b)(1) through (14). Submit the information in 40 CFR 60.5420b(b)(1)(v), as applicable, for your well affected facility which undergoes a change of ownership during the reporting period, regardless of whether reporting under 40 CFR 60.5420b(b)(2) through (4) is required for the well affected facility. Subpart OOOOb. [40 CFR 60.5420b(b)]

Maintain the records identified as specified in 40 CFR 60.7(f) and in 40 CFR 60.5420b(c)(1) through (15). All records required by this subpart must be maintained either onsite or at the nearest local field office for at least 5 years. Any records required to be maintained by this subpart that are submitted electronically via the EPA's CEDRI may be maintained in electronic format. This ability to maintain electronic copies does not affect the requirement for facilities to make records, data, and reports available upon request to a delegated air agency or the EPA as part of an on-site compliance evaluation. Subpart OOOOb. [40 CFR 60.5420b(c)] If you are required to submit notifications or reports following the procedure specified in 40 CFR 60.5420b(d), submit notifications or reports to the EPA via CEDRI, which can be accessed through the EPA's Central Data Exchange (CDX) (<https://cdx.epa.gov/>). Subpart OOOOb. [40 CFR 60.5420b(d)] To assert a claim of EPA system outage, meet the requirements outlined in 40 CFR 60.5420b(e)(1) through (5). Subpart OOOOb. [40 CFR 60.5420b(e)]

To assert a claim of force majeure, meet the requirements outlined in 40 CFR 60.5420b(f)(1) through (5). Subpart OOOOb. [40 CFR 60.5420b(f)] Comply with the General Provisions in 40 CFR 60.1 through 60.19 as per Table 5 of Subpart OOOOb. Subpart OOOOb.

### **EMS 0004 - Associated Gas Wells Subject to NSPS OOOOb**

Comply with either 40 CFR 60.5377b(a)(1), (2), (3), or (4) for each associated gas well upon startup and at all times, except as provided in 40 CFR 60.5377b(b) through (f). Also comply with 40 CFR 60.5377b(h), (i), and (j). Subpart OOOOb. [40 CFR 60.5377b(a)]

SPECIFIC REQUIREMENTS**EMS 0004 - Associated Gas Wells Subject to NSPS OOOOb**

For associated gas wells that commenced construction between May 7, 2024 and May 7, 2026, you can comply with the requirements in 40 CFR 60.5377b (f) continually upon startup instead of 40 CFR 60.5377b(a) until May 7, 2026 if you demonstrate and certify that it is not feasible to comply with 40 CFR 60.5377b(a)(1), (2), (3), and (4) due to technical reasons in accordance with 40 CFR 60.5377b(g). After May 7, 2026, continually comply with 40 CFR 60.5377b(a) at all times. Subpart OOOOb. [40 CFR 60.5377b(b)]

For associated gas wells that commenced construction between December 6, 2022, and May 7, 2024, and for associated gas wells that undergo reconstruction or modification after December 6, 2022, you can comply with the requirements in 40 CFR 60.5377b(f) instead of 40 CFR 60.5377b(a) if you demonstrate and certify that it is not feasible to comply with 40 CFR 60.5377b(a)(1), (2), (3), and (4) due to technical reasons in accordance with 40 CFR 60.5377b(g). Associated gas wells that are modified or reconstructed must comply with 40 CFR 60.5377b(a) or (f) upon startup and at all times thereafter. Subpart OOOOb. [40 CFR 60.5377b(c)]

If you are complying with 40 CFR 60.5377b(a), you may temporarily route the associated gas to a flare or control device that achieves a 95.0 percent reduction in VOC and methane emissions in the situations and for the durations identified in 40 CFR 60.5377b(d)(1), (2), (3), or (4). The associated gas must be routed through a closed vent system that meets the requirements of 40 CFR 60.5411b(a) and (c), and the control device must meet the conditions specified in 40 CFR 60.5412b during the period when the associated gas is routed to the flare. Records must be kept of all instances in which associated gas is temporarily routed to a flare or to a control device in accordance with 40 CFR 60.5420b(c)(3)(i)(B) and reported in the annual report in accordance with 40 CFR 60.5420b(b)(4)(i)(B). Subpart OOOOb. [40 CFR 60.5377b(d)]

If you are complying with 40 CFR 60.5377b(a), (d), or (f), you may vent the associated gas in the situations and for the durations identified in 40 CFR 60.5377b(e)(1), (2), or (3) per incident. The cumulative period of venting must not exceed 24 hours for any calendar year. Records must be kept of all venting instances in accordance with 40 CFR 60.5420b(c)(3)(ii) and reported in the annual report in accordance with 40 CFR 60.5420b(b)(4)(ii). Subpart OOOOb. [40 CFR 60.5377b(e)]

Route the associated gas to a control device that reduces methane and VOC emissions by at least 95.0 percent. The associated gas must be routed through a closed vent system that meets the requirements of 40 CFR 60.5411b(a) and (c), and the control device must meet the conditions specified in 40 CFR 60.5412b. Subpart OOOOb. [40 CFR 60.5377b(f)]

For affected sources identified in 40 CFR 60.5377b(b) and (c) that are complying with the requirements in 40 CFR 60.5377b(f), demonstrate that it is not feasible to comply with 40 CFR 60.5377b(a)(1), (2), (3), and (4) due to technical reasons by providing a detailed analysis documenting and certifying the technical reasons for this infeasibility. Subpart OOOOb. [40 CFR 60.5377b(g)]

Demonstrate initial compliance with the standards that apply to associated gas wells as required by 40 CFR 60.5410bc. Subpart OOOOb. [40 CFR 60.5377b(h)]

Demonstrate continuous compliance with the standards that apply to associated gas wells as required by 40 CFR 60.5415bc. Subpart OOOOb. [40 CFR 60.5377b(i)]

Perform the reporting as required by 40 CFR 60.5420b(b)(1) and (4), and (b)(11) and (12), as applicable, and the recordkeeping as required by 40 CFR 60.5420bc(c)(3) and (8), and (c)(10) through (13), as applicable. Subpart OOOOb. [40 CFR 60.5377b(j)]

To demonstrate initial compliance with the GHG and VOC standards for each associated gas well as required by 40 CFR 60.5377b, comply with 40 CFR 60.5410b(c)(1) through (4). Subpart OOOOb. [40 CFR 60.5410bc(c)]

For each associated gas well, demonstrate continuous compliance with the requirements of 40 CFR 60.5377b by submitting the reports required by 40 CFR 60.5420b(b)(1) and (4) and maintaining the records specified in 40 CFR 60.5420bc(c)(3). For each associated gas well that complies with the requirements of 40 CFR 60.5377b(d) or (f), route emissions to a control device through a closed vent system and continuously comply with the closed vent requirements of 40 CFR 60.5416b. Also comply with the requirements specified in 40 CFR 60.5415bc(f) and maintain the records in 40 CFR 60.5420b(c)(8), (10) and (12). Subpart OOOOb. [40 CFR 60.5415bc(c)]

**SPECIFIC REQUIREMENTS**  
**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

**EMS 0004 - Associated Gas Wells Subject to NSPS 0000b**

424 [40 CFR 60.5415b(f)]  
For each associated gas well referenced to 40 CFR 60.5415b(f) from 40 CFR 60.5415b(c), install monitoring systems as specified in 40 CFR 60.5417b, demonstrate continuous compliance according to 40 CFR 60.5415b(f)(1), maintain the records in 40 CFR 60.5415b(f)(2), and comply with the reporting requirements specified in 40 CFR 60.5415b(f)(3). Subpart OOOOb. [40 CFR 60.5415b(f)]

**EQT 0052 - Super-Emitter Events Subject to NSPS 0000b**

425 [40 CFR 60.5371b(d)]  
Within 5 calendar days of receiving a notification from the EPA of a super-emitter event, initiate a super-emitter event investigation. The investigation must be conducted in accordance with 40 CFR 60.5371b(d) and completed within 15 days of receiving the notification from the EPA. Maintain records of its super-emitter event investigations and report the findings from the investigation according to the requirements in 40 CFR 60.5371b(e). Subpart OOOOb. [40 CFR 60.5371b(d)]

426 [40 CFR 60.5371b(e)]  
Submit the results of the super-emitter event investigation conducted under 40 CFR 60.5371b(d) to the EPA in accordance with 40 CFR 60.5371b(e)(1). If the super-emitter event (i.e., emission at 100 kg/hr of methane or more) is ongoing at the time of the initial report, submit the additional information in accordance with 40 CFR 60.5371b(e)(2). Attest to the information included in the report as specified in 40 CFR 60.5371b(e)(3). Subpart OOOOb. [40 CFR 60.5371b(e)]

**EQT 0053 - Well Completions Subject to NSPS 0000b**

427 [40 CFR 60.5375b(a)]  
Comply with the requirements of 40 CFR 60.5375b(a)(1) through (3) for each well completion operation with hydraulic fracturing and refracturing at a well affected facility, except as provided in 40 CFR 60.5375b(f), (g) and (h). Maintain a log as specified in 40 CFR 60.5375b(b). Subpart OOOOb. [40 CFR 60.5375b(a)]

428 [40 CFR 60.5375b(b)]  
Maintain a log for each well completion operation at each well affected facility. The log must be completed on a daily basis for the duration of the well completion operation and must contain the records specified in 40 CFR 60.5420b(c)(1)(ii). Subpart OOOOb. [40 CFR 60.5375b(b)]

429 [40 CFR 60.5375b(c)]  
Demonstrate initial compliance with the well completion operation standards that apply to well affected facilities as required by 40 CFR 60.5410b(a). Subpart OOOOb. [40 CFR 60.5375b(c)]

430 [40 CFR 60.5375b(d)]  
Demonstrate continuous compliance with the well completion operation standards that apply to well affected facilities as required by 40 CFR 60.5415b(a). Subpart OOOOb. [40 CFR 60.5375b(d)]

431 [40 CFR 60.5375b(e)]  
Perform the required notification, reporting and recordkeeping as required by 40 CFR 60.5420b(a)(2), (b)(1) and (2), and (c)(1). Subpart OOOOb. [40 CFR 60.5375b(e)]

432 [40 CFR 60.5375b(f)]  
For each well affected facility specified in 40 CFR 60.5375b(f)(1) and (2), comply with the requirements of 40 CFR 60.5375b(f)(3) and (4). Subpart OOOOb. [40 CFR 60.5375b(f)]

433 [40 CFR 60.5375b(g)]  
For each well completion affected facility with less than 300 scf of gas per stock tank barrel of oil produced, comply with 40 CFR 60.5375b(g)(1) and (2). Subpart OOOOb. [40 CFR 60.5375b(g)]

434 [40 CFR 60.5410b(a)]  
To achieve initial compliance with the GHG and VOC standards for each well completion operation conducted at your well affected facility as required by 40 CFR 60.5375b, comply with 40 CFR 60.5410b(a)(1) through (4). Subpart OOOOb. [40 CFR 60.5410b(a)]

435 [40 CFR 60.5415b(a)]  
For each well completion operation at your well affected facility, demonstrate continuous compliance with the requirements of 40 CFR 60.5375b by submitting the annual report required by 40 CFR 60.5420b(b)(1) and (2) and maintaining the records for each completion operation specified in 40 CFR 60.5420b(c)(1). Subpart OOOOb. [40 CFR 60.5415b(a)]

**EQT 0054 - Gas Well Liquids Unloading Operations Subject to NSPS OOOOb**

436 [40 CFR 60.5376b(a)] Comply with the requirements of 40 CFR 60.5376b for each gas well liquids unloading operation at your gas well affected facility as specified by 40 CFR 60.5376b(a)(1) and (2). You have a general duty to safely maximize resource recovery and minimize releases to the atmosphere during gas well liquids unloading operations. Subpart OOOOb. [40 CFR 60.5376b(a)]  
437 [40 CFR 60.5376b(b)] If a gas well liquids unloading operation employs a technology or technique that vents methane and VOC emissions to the atmosphere, comply with the requirements in 40 CFR 60.5376b(b)(1) through (3) and (c) through (f). Subpart OOOOb. [40 CFR 60.5376b(b)]  
438 [40 CFR 60.5376b(c)] For each gas well liquids unloading operation complying with 40 CFR 60.5376b(a)(2) and (b), develop, maintain, and follow a best management practice plan to minimize venting of methane and VOC emissions to the maximum extent possible from each gas well liquids unloading operation. This best management practice plan must meet the minimum criteria specified in 40 CFR 60.5376b(c)(1) through (4). Subpart OOOOb. [40 CFR 60.5376b(c)]

Demonstrate initial compliance with the standards that apply to well liquids unloading operations at your well affected facilities as required by 40 CFR 60.5410(b). Subpart OOOOb. [40 CFR 60.5376b(d)] Demonstrate continuous compliance with the standards that apply to well liquids unloading operations at your well affected facilities as required by 40 CFR 60.5410(b). Subpart OOOOb. [40 CFR 60.5376b(e)]

439 [40 CFR 60.5376b(d)] Perform the required notification, recordkeeping and reporting requirements as specified in 40 CFR 60.5420b(b)(3) and (c)(2). Subpart OOOOb. [40 CFR 60.5376b(f)] Reduce methane and VOC emissions from well affected facility gas wells that unload liquids by 95.0 percent by complying with the requirements specified in 40 CFR 60.5376b(g)(1) and (2) and meeting the initial and continuous compliance and recordkeeping and reporting requirements specified in 40 CFR 60.5376b(g)(3) through (5). Subpart OOOOb. [40 CFR 60.5376b(g)]

To demonstrate initial compliance with the GHG and VOC standards for each gas well liquids unloading operation conducted at your gas well affected facility as required by 40 CFR 60.5376b, comply with 40 CFR 60.5410b(1) through (4), as applicable. Subpart OOOOb. [40 CFR 60.5410b(b)] For each well liquids unloading operation at your well affected facility, demonstrate continuous compliance with the requirements of 40 CFR 60.5376b by submitting the annual report information specified in 40 CFR 60.5420b(b)(1) and (3) and maintaining the records for each well liquids unloading event specified in 40 CFR 60.5420b(c)(2). For each gas well liquids unloading well affected facility that complies with the requirements of 40 CFR 60.5376b(g), route emissions to a control device through a closed vent system and continuously comply with the closed vent requirements of 40 CFR 60.5416b. Also comply with the requirements specified in 40 CFR 60.5415b(f) and maintain the records in 40 CFR 60.5420b(c)(8), (10) and (12). Subpart OOOOb. [40 CFR 60.5415b(b)]

440 [40 CFR 60.5376b(e)] For each gas well that conducts liquids unloading referenced to 40 CFR 60.5415b(f) from 40 CFR 60.5415b(f) from 40 CFR 60.5415b(f)(1), install monitoring systems as specified in 40 CFR 60.5417b, demonstrate continuous compliance according to 40 CFR 60.5415b(f)(1), maintain the records in 40 CFR 60.5415b(f)(2), and comply with the reporting requirements specified in 40 CFR 60.5415b(f)(3). Subpart OOOOb. [40 CFR 60.5415b(f)]

**EQT 0055 - Reciprocating Compressors Subject to NSPS OOOOb**

446 [40 CFR 60.5385b(a)] The volumetric flow rate of each cylinder, measured in accordance with 40 CFR 60.5385b(b) or (c), must not exceed 2 scfm per individual cylinder. If the individual cylinders are manifolded to a single open-ended vent line, the volumetric flow rate must not exceed the sum of the individual cylinders multiplied by 2 scfm. Conduct measurements of the volumetric flow rate in accordance with the schedule specified in 40 CFR 60.5385b(a)(1) and (2) and determine the volumetric flow rate per cylinder in accordance with 40 CFR 60.5385b(b) or (c). If the volumetric flow rate, measured in accordance with 40 CFR 60.5385b(b) or (c), for a cylinder exceeds 2 scfm per cylinder (or a combined volumetric flow rate greater than the number of compression cylinders multiplied by 2 scfm), the rod packing or packings must be repaired or replaced as provided in 40 CFR 60.5385b(a)(3). Subpart OOOOb. [40 CFR 60.5385b(a)]

**EQT 0055 - Reciprocating Compressors Subject to NSPS OOOOb**

- 447 [40 CFR 60.5385b(b)] Determine the volumetric flow rate per cylinder from your reciprocating compressor as specified in 40 CFR 60.5385b(b)(1) or (2). Subpart OOOOb. [40 CFR 60.5385b(b)]
- For conducting measurements on manifolded groups of reciprocating compressor affected facilities, determine the volumetric flow rate from reciprocating compressor rod packing vent as specified in 40 CFR 60.5385b(c)(1) and (2). Subpart OOOOb. [40 CFR 60.5385b(c)]
- As an alternative to complying with the GHG and VOC standards in 40 CFR 60.5385b(a) through (c), owners or operators can meet the requirements specified in 40 CFR 60.5385b(d)(1), (2), or (3). [40 CFR 60.5385b(d)]
- Demonstrate initial compliance with standards that apply to reciprocating compressor affected facilities as required by 40 CFR 60.5410b
- (e). [40 CFR 60.5385b(e)] Demonstrate continuous compliance with standards that apply to reciprocating compressor affected facilities as required by 40 CFR 60.5415b(g). Subpart OOOOb. [40 CFR 60.5385b(f)]
- Perform the reporting requirements as specified in 40 CFR 60.5420b(b)(1), (6), and (11) through (13), as applicable, and the recordkeeping requirements as specified in 40 CFR 60.5420b(c)(5) and (8) through (13), as applicable. Subpart OOOOb. [40 CFR 60.5385b(g)]
- Use one of the methods described in 40 CFR 60.5386b(a)(1) and (2) to screen for emissions or leaks from the reciprocating compressor rod packing when complying with 40 CFR 60.5385b(b)(1)(iii). Subpart OOOOb. [40 CFR 60.5386b(h)(a)]
- Determine natural gas volumetric flow rate using a rate meter which meets the requirement in Method 2D in appendix A-1 of this part.
- Rate meters must be calibrated on an annual basis according to the requirements in Method 2D. Subpart OOOOb. [40 CFR 60.5386b(b)]
- Use a high-volume sampler to measure emissions of the reciprocating compressor rod packing in accordance with 40 CFR 60.5386b(c)(1) through (7). Subpart OOOOb. [40 CFR 60.5386b(c)]
- As an alternative to a high-volume sampler, you may use any other method that has been validated in accordance with the procedures specified in Method 301 in appendix A in 40 CFR part 63, subject to Administrator approval, as specified in 40 CFR 60.8(b). Subpart OOOOb. [40 CFR 60.5386b(d)]
- To demonstrate initial compliance with the GHG and VOC standards for each reciprocating compressor affected facility as required by 40 CFR 60.5385b, comply with 40 CFR 60.5410b(e)(1) through (7). Subpart OOOOb. [40 CFR 60.5410b(e)]
- For each reciprocating compressor affected facility referenced to 40 CFR 60.5415b(g)(2), install monitoring systems as specified in 40 CFR 60.5417b, demonstrate continuous compliance according to 40 CFR 60.5415b(f)(1), maintain the records in 40 CFR 60.5415b(f)(2), and comply with the reporting requirements specified in 40 CFR 60.5415b(f)(3). Subpart OOOOb. [40 CFR 60.5415b(f)]
- For each reciprocating compressor affected facility complying with 40 CFR 60.5385b(a) through (c), demonstrate continuous compliance according to 40 CFR 60.5415b(g)(1), (5), and (6). For each reciprocating compressor affected facility complying with 40 CFR 60.5385b(d)(1) or (2), demonstrate continuous compliance according to 40 CFR 60.5415b(g)(2), (5) and (6). For each reciprocating compressor affected facility complying with 40 CFR 60.5385b(d)(3), demonstrate continuous compliance according to 40 CFR 60.5415b(g)(3) through (6). Subpart OOOOb. [40 CFR 60.5415b(g)]
- EQT 0056 - Process Controllers Subject to NSPS OOOOb**
- 459 [40 CFR 60.5415b(g)] Design and operate each process controller affected facility with zero methane and VOC emissions to the atmosphere, except as provided in 40 CFR 60.5390b(b). If you comply by routing the emissions to a process, emissions must be routed to a process through a closed vent system. If you comply by using a self-contained natural gas-driven process controller, design and operate each self-contained natural gas-driven process controller with no identifiable emissions, as demonstrated by 40 CFR 60.5416b(b). Subpart OOOOb. [40 CFR 60.5390b(a)]
- 460 [40 CFR 60.5390b(a)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### EQT 0056 - Process Controllers Subject to NSPS OOOOb

If you route process controller emissions to a process or a control device, route the process controller affected facility emissions through a closed vent system that meets the requirements of 40 CFR 60.5411b(a) and (c). Subpart OOOOb. [40 CFR 60.5390b(c)]  
Demonstrate initial compliance with standards that apply to process controller affected facilities as required by 40 CFR 60.5410b(f).

Subpart OOOOb. [40 CFR 60.5390b(d)]  
Demonstrate continuous compliance with standards that apply to process controller affected facilities as required by 40 CFR 60.5415b(h).

Subpart OOOOb. [40 CFR 60.5390b(e)]  
Perform the reporting as required by 40 CFR 60.5420b(b)(1), (7), and (11) through (13), as applicable, and the recordkeeping as required by 40 CFR 60.5420b(c)(6), (8), and (10) through (13), as applicable. Subpart OOOOb. [40 CFR 60.5390b(f)]

To demonstrate initial compliance with GHG and VOC emission standards for your process controller affected facility as required by 40 CFR 60.5390b, comply with 40 CFR 60.5410b(f)(1) through (5), as applicable. If you change compliance methods, perform the applicable compliance demonstrations of 40 CFR 60.5410b(f)(1) through (3) again for the new compliance method, note the change in compliance method in the annual report required by 40 CFR 60.5420b(b)(7)(iv), and maintain the records required by 40 CFR 60.5410b(f)(5) for the new compliance method. Subpart OOOOb. [40 CFR 60.5410b(f)]

To demonstrate continuous compliance with GHG and VOC emission standards for your process controller affected facility as required by 40 CFR 60.5590b, comply with 40 CFR 60.5415b(h)(1) through (4), as applicable. Subpart OOOOb. [40 CFR 60.5415b(h)]

### EQT 0057 - Pumps Subject to NSPS OOOOb

For each pump affected facility located at a site that does not have access to electrical power, but has three or more natural gas-driven diaphragm pumps, design and operate the pump affected facility with zero methane and VOC emissions to the atmosphere. If you comply by routing the pump affected facility emissions to a process, the emissions must be routed to the process through a closed vent system. Subpart OOOOb. [40 CFR 60.5393b(a)]  
For each pump affected facility located at a site that does not have access to electrical power and that also has fewer than three natural gas-driven diaphragm pumps, comply with 40 CFR 60.5393b(b)(2) or (3), except as provided in 40 CFR 60.5393b(b)(4) through (8). Subpart OOOOb. [40 CFR 60.5393b(b)]

If you use a control device or route to a process to reduce emissions, route the pump affected facility emissions through a closed vent system that meets the requirements of 40 CFR 60.5411b(a) and (c). Subpart OOOOb. [40 CFR 60.5393b(c)]  
Demonstrate initial compliance with standards that apply to pump affected facilities as required by 40 CFR 60.5410b(g). Subpart OOOOb.

[40 CFR 60.5393b(b)(4)]  
Demonstrate continuous compliance with the standards that apply to pump affected facilities as required by 40 CFR 60.5415b(e). Subpart OOOOb. [40 CFR 60.5393b(e)]  
Perform the reporting as required by 40 CFR 60.5420b(b)(1), (10), and (11) through (13), as applicable, and the recordkeeping as required by 40 CFR 60.5420b(c)(8), (10) through (13), and (15), as applicable. Subpart OOOOb. [40 CFR 60.5393b(f)]

To demonstrate initial compliance with the GHG and VOC standards for your pump affected facility as required by 40 CFR 60.5393b, comply with 40 CFR 60.5410b(g)(1) through (4), as applicable. If you change compliance methods, perform the applicable compliance demonstrations of 40 CFR 60.5410b(g)(1) and (2) again for the new compliance method, note the change in compliance method in the annual report required by 40 CFR 60.5420b(b)(10)(v)(C), and maintain the records required by 40 CFR 60.5410b(g)(4) for the new compliance method. Subpart OOOOb. [40 CFR 60.5410b(g)]

To demonstrate continuous compliance with the GHG and VOC standards for your pump affected facility as required by 40 CFR 60.5393b, comply with 40 CFR 60.5415b(e)(1) through (3). Subpart OOOOb. [40 CFR 60.5415b(e)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER20240001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### EQT 0057 - Pumps Subject to NSPS OOOOb

475 [40 CFR 60.5415b(f)]

For each pump affected facility referenced to 40 CFR 60.5415b(f) from 40 CFR 60.5415b(e)(1), install monitoring systems as specified in 40 CFR 60.5417b, demonstrate continuous compliance according to 40 CFR 60.5415b(f)(1), maintain the records in 40 CFR 60.5415b(f)(2), and comply with the reporting requirements specified in 40 CFR 60.5415b(f)(3). Subpart OOOOb. [40 CFR 60.5415b(f)]

### EQT 0064 - Sweetening Units Subject to NSPS OOOOb

476 [40 CFR 60.5423b(e)]

Keep, for the life of the facility, an analysis demonstrating that the facility's design capacity is less than 2 L/T/D of H<sub>2</sub>S expressed as sulfur. Subpart OOOOb. [40 CFR 60.5423b(e)]

### EQT 0065 - Storage Vessels Subject to NSPS OOOOb

477 [40 CFR 60.5395b(a)]

Comply with the requirements of 40 CFR 60.5395b(a)(1) and (2). After 12 consecutive months of compliance with 40 CFR 60.5395b(a)(2), you may continue to comply with 40 CFR 60.5395b(a)(2), or you may comply with 40 CFR 60.5395b(a)(3), if applicable. If you choose to meet the requirements of 40 CFR 60.5395b(a)(3), you are not required to comply with the requirements of 40 CFR 60.5395b(a)(2) except as provided in 40 CFR 60.5395b(a)(3)(i) and (ii). Subpart OOOOb. [40 CFR 60.5395b(a)]

478 [40 CFR 60.5395b(b)]

If you use a control device to reduce methane and VOC emissions from your storage vessel affected facility, meet all of the design and operational criteria specified in 40 CFR 60.5395b(b)(1)(i) through (iii). For storage vessel affected facilities that do not have flashing emissions and that are not located at well sites or centralized production facilities, you may use a floating roof to reduce emissions. If you use a floating roof to reduce emissions, meet the requirements of 40 CFR 60.112b(a)(1) or (2) and the relevant monitoring, inspection, recordkeeping, and reporting requirements in 40 CFR 60 Subpart Kb. Submit a statement that you are complying with 40 CFR 60.112b(a)(1) or (2) with the initial annual report specified in 40 CFR 60.5420b(b)(1) and (8). Subpart OOOOb. [40 CFR 60.5395b(b)]

479 [40 CFR 60.5395b(c)]

If you remove a storage vessel affected facility from service or remove a portion of a storage vessel affected facility from service, comply with 40 CFR 60.5395b(c)(1) through (4), as applicable. Subpart OOOOb. [40 CFR 60.5395b(c)]

Demonstrate initial compliance with standards as required by 40 CFR 60.5410b(j). Demonstrate continuous compliance with standards as required by 40 CFR 60.5415b(i). Perform the required reporting as required by 40 CFR 60.5420b(b)(1) and (8) and (b)(11) through (13), as applicable, and the recordkeeping as required by 40 CFR 60.5420b(c)(7) and (c)(8) through (13), as applicable. Subpart OOOOb. [40 CFR 60.5395b(d)]

480 [40 CFR 60.5395b(d)]

To achieve initial compliance with the GHG and VOC standards for each storage vessel affected facility as required by 40 CFR 60.5395b, comply with 40 CFR 60.5410b(j)(1) through (9). To achieve initial compliance with the GHG and VOC standards for each storage vessel affected facility that complies by using a floating roof in accordance with 40 CFR 60.5395b(b)(2), comply with 40 CFR 60.5410b(j)(1) and (10). Subpart OOOOb. [40 CFR 60.5410b(j)]

481 [40 CFR 60.5410b(j)]

For storage vessel affected facility referenced to 40 CFR 60.5415b(f) from 40 CFR 60.5415b(i)(5), install monitoring systems as specified in 40 CFR 60.5417b, demonstrate continuous compliance according to 40 CFR 60.5415b(f)(1), maintain the records in 40 CFR 60.5415b(f)(2), and comply with the reporting requirements specified in 40 CFR 60.5415b(f)(3). Subpart OOOOb. [40 CFR 60.5415b(f)]

482 [40 CFR 60.5415b(f)]

For each storage vessel affected facility, demonstrate continuous compliance with the requirements of 40 CFR 60.5395b according to 40 CFR 60.5415b(i)(1) through (10), as applicable. Subpart OOOOb. [40 CFR 60.5415b(i)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### EQT\_0066 - Control Devices Subject to NSPS OOOOb

484 [40 CFR 60.5412b(a)(1)]  
Each enclosed combustion device (e.g., thermal vapor incinerator, catalytic vapor incinerator, boiler, or process heater) must be designed and operated in accordance with 40 CFR 60.5412b(a)(1)(i), meet one of the operating limits specified in 40 CFR 60.5412b(a)(1)(ii) through (v), and except for boilers and process heaters meeting the requirements of 40 CFR 60.5412b(a)(1)(iii) and catalytic vapor incinerators meeting the requirements of 40 CFR 60.5412b(a)(1)(v), meet the operating limits specified in 40 CFR 60.5412b(a)(1)(vi) through (ix).

Subpart OOOOb. [40 CFR 60.5412b(a)(1)]

485 [40 CFR 60.5412b(a)(3)]  
Each flare must be designed and operated according to the requirements specified in 40 CFR 60.5412b(a)(3)(i) through (viii), as applicable.

Subpart OOOOb. [40 CFR 60.5412b(a)(3)]

486 [40 CFR 60.5412b(a)(3)]  
Each control device used to meet the emissions reduction standard in 40 CFR 60.5377b(d) or (f) for your associated gas well at a well affected facility, 40 CFR 60.5376b(g) for your well affected facility gas well that unloads liquids, 40 CFR 60.5385b(d)(2) for your reciprocating compressor affected facility, 40 CFR 60.5395b(a)(2) for your storage vessel affected facility; and 40 CFR 60.5393b(b)(3) for your pumps affected facility must be installed according to 40 CFR 60.5412b(a)(1) through (3). As an alternative to 40 CFR 60.5412b(a)(1), you may install a control device model tested under 40 CFR 60.5413b(d), which meets the criteria in 40 CFR 60.5413b(d)(11) and which meets the initial and continuous compliance requirements in 40 CFR 60.5413b(e). Subpart OOOOb. [40 CFR 60.5412b(a)] Operate each control device installed on your well, reciprocating compressor, storage vessel, process controller, or pump in accordance with the requirements specified in 40 CFR 60.5412b(b)(1) and (2). Subpart OOOOb. [40 CFR 60.5412b(b)]

487 [40 CFR 60.5412b(b)]  
Unless exempt from the requirements to conduct initial and periodic performance tests as described in 40 CFR 60.5413b(a), use the test methods and procedures specified in 40 CFR 60.5413b(b)(1) through (4), as applicable, for each performance test conducted to demonstrate that a control device meets the requirements of 40 CFR 60.5412b(a)(1). Conduct the initial and periodic performance tests according to the schedule specified in 40 CFR 60.5413b(b)(5). Each performance test must consist of a minimum of 3 test runs. Each run must be at least 1 hour long. Subpart OOOOb. [40 CFR 60.5413b(b)]

488 [40 CFR 60.5413b(c)(1)]  
Initial and continuous compliance for combustion control devices tested by the manufacturer in accordance with 40 CFR 60.5413b(d): Owners or operators must demonstrate that a control device achieves the performance criteria in 40 CFR 60.5413b(e)(1) through (10), maintaining the device tested under 40 CFR 60.5413b(d), complying with the criteria specified in 40 CFR 60.5417b(c) through (13). Subpart OOOOb. records specified in 40 CFR 60.5420b(c)(1) and submitting the report specified in 40 CFR 60.5420b(b)(1)(v) and (13). Subpart OOOOb. [40 CFR 60.5413b(e)]

489 [40 CFR 60.5413b(e)]  
For each control device used to comply with the emission reduction standard in 40 CFR 60.5377b(b) for well affected facilities, 40 CFR 60.5385b(d)(2) for reciprocating compressor affected facilities, 40 CFR 60.5393b(b)(3) for your pumps affected facility, or 40 CFR 60.5395b(a)(2) for your storage vessel affected facility, install and operate a continuous parameter monitoring system for each control device as specified in 40 CFR 60.5417b(c) through (h), except as provided in 40 CFR 60.5417b(b). If you install and operate a flare in accordance with 40 CFR 60.5412b(a)(3), you are exempt from the requirements of 40 CFR 60.5417b(f). If you operate an enclosed combustion device or flare using an alternative test method approved under 40 CFR 60.5412b(d), operate the control device as specified in 40 CFR 60.5417b(i) instead of using the procedures specified in 40 CFR 60.5417b(c) through (h). Keep records and report in accordance with 40 CFR 60.5417b(j). Subpart OOOOb. [40 CFR 60.5417b(a)]

490 [40 CFR 60.5417b(a)]  
Meet the specifications and requirements of 40 CFR 60.5417b(c)(1) through (4). Subpart OOOOb. [40 CFR 60.5417b(c)]

**SPECIFIC REQUIREMENTS**  
AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities  
Activity Number: PER20240001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

**EQT\_0066 - Control Devices Subject to NSPS OOOOb**

- 492 [40 CFR 60.5417b(d)]  
Install, calibrate, operate, and maintain a device equipped with a continuous recorder to measure the values of operating parameters appropriate for the control device as specified in 40 CFR 60.5417b(d)(1) through (8), as applicable. Instead of complying with the requirements in 40 CFR 60.5417b(d)(1) through (8), you may install an organic monitoring device equipped with a continuous recorder that measures the concentration level of organic compounds in the exhaust vent stream from the control device to demonstrate compliance with the applicable performance requirement specified in 40 CFR 60.5417b(a)(1). The monitor must meet the requirements of Performance Specification 8 or 9 of appendix B to part 60. Install, calibrate, and maintain the monitor according to the manufacturer's specifications and the requirements in Performance Specification 8 or 9. Subpart OOOOb. [40 CFR 60.5417b(d)]  
Calculate the value of the applicable monitored parameter in accordance with 40 CFR 60.5417b(e)(1) through (5). Subpart OOOOb. [40 CFR 60.5417b(e)]

For each operating parameter monitor installed in accordance with the requirements of 40 CFR 60.5417b(d), comply with 40 CFR 60.5417b(f)(1) for all control devices except flares operated in accordance with 40 CFR 60.5412b(a)(3). Subpart OOOOb. [40 CFR 60.5417b(f)]  
A deviation for a control device is determined to have occurred when the monitoring data or lack of monitoring data result in any one of the criteria specified in 40 CFR 60.5417b(g)(1) through (7) being met. Subpart OOOOb. [40 CFR 60.5417b(g)]  
For enclosed combustion devices and flares, in lieu of conducting a visible emissions observation using Method 22 of appendix A-7 to part 60, you may use a video surveillance camera to continuously monitor and record the flare flame according to the requirements in 40 CFR 60.5417b(h)(1) through (6). Subpart OOOOb. [40 CFR 60.5417b(h)]  
If you use an enclosed combustion device or flare using an alternative test method approved under 40 CFR 60.5412b(d), comply with 40 CFR 60.5417b(i)(1) through (6). Subpart OOOOb. [40 CFR 60.5417b(i)]  
Submit annual reports for control devices as required in 40 CFR 60.5420b(b)(1) and (11). Maintain records as specified in 40 CFR 60.5420b(c)(11). Subpart OOOOb. [40 CFR 60.5417b(j)]

**EQT\_0067 - Covers and Closed Vent Systems Subject to NSPS OOOOb**

- 499 [40 CFR 60.5398b(a)]  
If you choose to demonstrate compliance with the alternative GHG and VOC standards in either 40 CFR 60.5398b(b) or (c), notify the Administrator of adoption of the alternative standards in the first annual report following implementation of the alternative standards, as specified in 40 CFR 60.5424b(a). Once you have implemented the alternative standards, continue to comply with the alternative standards.  
\*\* See Subsection V.J for restrictions. \*\* Subpart OOOOb. [40 CFR 60.5398b(a)]  
You may choose to demonstrate compliance with continuous inspection and monitoring requirements for your covers and closed vent systems through periodic screenings using any methane measurement technology approved in accordance with 40 CFR 60.5398b(d). If you choose to demonstrate compliance using periodic screenings, comply with the requirements in 40 CFR 60.5398b(b)(1) through (5) and comply with the recordkeeping and reporting requirements in 40 CFR 60.5424b. Maintain records as specified in 40 CFR 60.5420b(c)(4) through (7), (14), and (15), and 40 CFR 60.5424b(c). Submit reports as specified in 40 CFR 60.5424b. \*\* See Subsection V.J for restrictions. \*\* Subpart OOOOb. [40 CFR 60.5398b(b)]  
You may choose to demonstrate compliance with continuous inspection and monitoring requirements for your covers and closed vent systems through continuous monitoring using a technology approved in accordance with 40 CFR 60.5398b(d). If you choose to demonstrate compliance using continuous monitoring, comply and develop a monitoring plan consistent with the requirements in 40 CFR 60.5398b(c)(1) through (9) and comply with the recordkeeping and reporting requirements in 40 CFR 60.5424b. \*\* See Subsection V.J for restrictions. \*\* Subpart OOOOb. [40 CFR 60.5398b(c)]

- 501 [40 CFR 60.5398b(c)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### EQT\_0067 - Covers and Closed Vent Systems Subject to NSPS 0000b

Closed vent system requirements:

- (1) Reciprocating compressor rod packing, process controllers, and pumps: Design the closed vent system to capture and route all gases, vapors, and fumes to a process.
- (2) Associated gas wells, centrifugal compressors, pumps complying with 40 CFR 60.5393b(b)(1), and storage vessels: Design the closed vent system to capture and route all gases, vapors, and fumes to a process or a control device that meets the requirements specified in 40 CFR 60.5411b(a) through (d). For pumps complying with 40 CFR 60.5393b(b)(3), design the closed vent system to capture and route all gases, vapors, and fumes to a control device that meets the requirements specified in 40 CFR 60.5411b(a) through (d).
- (3) Design and operate the closed vent system with no identifiable emissions as demonstrated by 40 CFR 60.5416b(a) and (b).
- (4) Bypass devices: Meet the requirements specified in 40 CFR 60.5411b(a)(4)(i) and (ii) if the closed vent system contains one or more bypass devices that could be used to divert all or a portion of the gases, vapors, or fumes from entering the control device or being routed to a process. Subpart OOOOb. [40 CFR 60.5411b(a)]

Cover requirements for storage vessels and centrifugal compressors, and reciprocating compressors:

- (1) The cover and all openings on the cover (e.g., access hatches, sampling ports, pressure relief devices and gauge wells) shall form a continuous impermeable barrier over the entire surface area of the liquid in the storage vessel or centrifugal compressor wet seal fluid degassing system, or reciprocating compressor rod packing emissions collection system.
- (2) Each cover opening shall be secured in a closed, sealed position (e.g., covered by a gasketed lid or cap) whenever material is in the unit on which the cover is installed except during those times when it is necessary to use an opening to add material to, or remove material from the unit (this includes openings necessary to equalize or balance the internal pressure of the unit following changes in the level of the material in the unit); inspect or sample the material in the unit; inspect, maintain, repair, or replace equipment located inside the unit; or vent liquids, gases, or fumes from the unit through a closed vent system designed and operated in accordance with the requirements of 40 CFR 60.5411b(a) to a control device or to a process.
- (3) Each storage vessel thief hatch shall be equipped, maintained and operated with a weighted mechanism or equivalent, to ensure that the lid remains properly seated and sealed under normal operating conditions, including such times when working, standing/breathing, and flash emissions may be generated. Select gasket material for the hatch based on composition of the fluid in the storage vessel and weather conditions.

- (4) Design and operate the cover with no identifiable emissions as demonstrated by 40 CFR 60.5416b(a) and (b), except when operated as provided in 40 CFR 60.5411b(b)(2)(i) through (iv). Subpart OOOOb. [40 CFR 60.5411b(b)]  
Conduct an assessment that the closed vent system is of sufficient design and capacity to ensure that all gases, vapors, and fumes from the affected facility are routed to the control device or process and that the control device or process is of sufficient design and capacity to accommodate all emissions from the affected facility. The assessment must be certified by a qualified professional engineer or an in-house engineer with expertise on the design and operation of the closed vent system in accordance with 40 CFR 60.5411b(c)(1)(i) and (ii). Subpart OOOOb. [40 CFR 60.5411b(c)]

Inspections for closed vent systems, covers, and bypass devices: If you install a control device or route emissions to a process, inspect each closed vent system according to the procedures and schedule specified in 40 CFR 60.5416b(a)(1) and (2), inspect each cover according to the procedures and schedule specified in 40 CFR 60.5416b(a)(3), and inspect each bypass device according to the procedures of 40 CFR 60.5416b(a)(4), except as provided in 40 CFR 60.5416b(b)(7) and (8). Subpart OOOOb. [40 CFR 60.5416b(a)]

No identifiable emissions test methods and procedures. If you are required to conduct an inspection of a closed vent system and cover as specified in 40 CFR 60.5416b(a)(1), (2), or (3) or 40 CFR 60.5398b(b), meet the requirements of 40 CFR 60.5416b(b)(1) through (9). Meet the requirements of 40 CFR 60.5416b(b)(1), (2), (4), and (9) for each self-contained process controller at your process controller affected facility as specified at 40 CFR 60.5390b(a)(2). Subpart OOOOb. [40 CFR 60.5416b(b)]

502 [40 CFR 60.5411b(a)]

504 [40 CFR 60.5411b(c)]

505 [40 CFR 60.5416b(a)]

506 [40 CFR 60.5416b(b)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER20240001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### EQT 0067 - Covers and Closed Vent Systems Subject to NSPS OOOOb

- 507 [40 CFR 60.5424b(a)] If you choose to comply with an alternative GHG and VOC standard as specified in 40 CFR 60.5398b, submit the notification in 40 CFR 60.5424b(a)(1). If you are required by 40 CFR 60.5398b(c)(8) to develop a mass emission rate reduction plan, submit the notification in 40 CFR 60.5424b(a)(2). Subpart OOOOb. [40 CFR 60.5424b(a)]
- If you comply with the periodic screening requirements of 40 CFR 60.5398b(b), submit the information in 40 CFR 60.5424b(b)(1) through (6) in the annual report required by 40 CFR 60.5420b(b)(4) through (11). Subpart OOOOb. [40 CFR 60.5424b(b)]
- If you comply with the periodic screening requirements of 40 CFR 60.5398b(b), maintain the records in 40 CFR 60.5424b(c)(1) through (11) in addition to the records as specified in 40 CFR 60.5420b(c)(3) through (9) and (c)(14) and (15). Subpart OOOOb. [40 CFR 60.5424b(c)]
- If you comply with the continuous monitoring system requirements of 40 CFR 60.5398b(c), submit the information in 40 CFR 60.5424b(d)(1) through (6) in the annual report required by 40 CFR 60.5420b(b)(4) through (11). Subpart OOOOb. [40 CFR 60.5424b(d)]
- If you comply with the continuous monitoring system requirements of 40 CFR 60.5398b(c), maintain the records in 40 CFR 60.5424b(e)(1) through (15). Subpart OOOOb. [40 CFR 60.5424b(e)]

### FUG 0005 - Fugitive Emissions Subject to NSPS OOOOb

- 512 [40 CFR 60.5397b(a)] Monitor all fugitive emissions components affected facilities in accordance with 40 CFR 60.5397b(b) through (g). Repair all sources of fugitive emissions in accordance with 40 CFR 60.5397b(h). Demonstrate initial compliance in accordance with 40 CFR 60.5397b(i). Keep records in accordance with 40 CFR 60.5397b(j) and report in accordance with 40 CFR 60.5397b(k). Meet the requirements for well closures in accordance with 40 CFR 60.5397b(l). Subpart OOOOb. [40 CFR 60.5397b(a)]
- Develop a fugitive emissions monitoring plan that covers all fugitive emissions components affected facilities within each company-defined area in accordance with 40 CFR 60.5397b(c) and (d). Subpart OOOOb. [40 CFR 60.5397b(b)]
- Your fugitive emissions monitoring plan must include the elements specified in 40 CFR 60.5397b(c)(1) through (8), at a minimum. Subpart OOOOb. [40 CFR 60.5397b(c)]
- Each fugitive emissions monitoring plan must include the elements specified in 40 CFR 60.5397b(d)(1) and (2), at a minimum, as applicable. Subpart OOOOb. [40 CFR 60.5397b(d)]
- Each fugitive emissions component, except buried yard piping and associated components (e.g., connectors), shall be observed or monitored for fugitive emissions during each monitoring survey. Subpart OOOOb. [40 CFR 60.5397b(e)]
- Conduct initial monitoring surveys according to the requirements specified in 40 CFR 60.5397b(f)(1) through (4). Subpart OOOOb. [40 CFR 60.5397b(f)]
- A monitoring survey of each fugitive emissions components affected facility must be performed as specified in 40 CFR 60.5397b(g)(1), with the exceptions noted in 40 CFR 60.5397b(g)(2) through (4). Monitoring for fugitive emissions components affected facilities located at well sites and centralized production facilities that have wells located onsite must continue at the specified frequencies in 40 CFR 60.5397b(g)(1)(i), (ii), (iii), (iv) and (vi) until the well closure requirements of 40 CFR 60.5397b(l) are completed. Subpart OOOOb. [40 CFR 60.5397b(g)]
- Each identified source of fugitive emissions shall be repaired in accordance with 40 CFR 60.5397b(h)(1) and (2). Subpart OOOOb. [40 CFR 60.5397b(h)]
- Demonstrate initial compliance with the standards that apply to fugitive emissions components affected facilities as required by 40 CFR 60.5410b(k). Subpart OOOOb. [40 CFR 60.5397b(i)]
- Demonstrate continuous compliance with the standards that apply to fugitive emissions components affected facilities as required by 40 CFR 60.5415b(l). Subpart OOOOb. [40 CFR 60.5397b(j)]

## SPECIFIC REQUIREMENTS

AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities

Activity Number: PER20240001

Permit Number: MSOG Master Gen Permit  
Air - Minor Gen Permit-Oil and Gas Mod

### FUG\_0005 - Fugitive Emissions Subject to NSPS OOOOb

Comply with the reporting requirements as specified in 40 CFR 60.5420b(b)(1) and (9), and the recordkeeping requirements as specified in 40 CFR 60.5397b(k).

522 [40 CFR 60.5397b(k)]  
Complete the requirements specified in 40 CFR 60.5397b(l)(X)1) through (4). Subpart OOOOb. [40 CFR 60.5397b(l)]

If you choose to demonstrate compliance with the alternative GHG and VOC standards in either 40 CFR 60.5398b(b) or (c), notify the Administrator of adoption of the alternative standards in the first annual report following implementation of the alternative standards, as specified in 40 CFR 60.5424b(a). Once you have implemented the alternative standards, continue to comply with the alternative standards.

\*\* See Subsection V.J for restrictions. \*\* Subpart OOOOb. [40 CFR 60.5398b(a)]

You may choose to demonstrate compliance for your fugitive emissions components affected facility through periodic screenings using any methane measurement technology approved in accordance with 40 CFR 60.5398b(d). If you choose to demonstrate compliance using periodic screenings, comply with the requirements in 40 CFR 60.5398b(b)(1) through (5) and comply with the recordkeeping and reporting requirements in 40 CFR 60.5424b. Maintain records as specified in 40 CFR 60.5420b(c)(4) through (7), (14), and (15), and 40 CFR 60.5424b(c). Submit reports as specified in 40 CFR 60.5424b. \*\* See Subsection V.J for restrictions. \*\* Subpart OOOOb. [40 CFR 60.5398b(b)]

You may choose to demonstrate compliance for your fugitive emissions components affected facility through continuous monitoring using a technology approved in accordance with 40 CFR 60.5398b(d). If you choose to demonstrate compliance using continuous monitoring, comply and develop a monitoring plan consistent with the requirements in 40 CFR 60.5398b(c)(1) through (9) and comply with the recordkeeping and reporting requirements in 40 CFR 60.5424b. \*\* See Subsection V.J for restrictions. \*\* Subpart OOOOb. [40 CFR 60.5398b(c)]

To achieve initial compliance with the GHG and VOC standards for fugitive emissions components affected facilities as required by 40 CFR 60.5397b, comply with 40 CFR 60.5410b(k)(1) through (5). Subpart OOOOb. [40 CFR 60.5410b(k)]

For each fugitive emissions components affected facility, demonstrate continuous compliance with the requirements of 40 CFR 60.5397b (a) according to 40 CFR 60.5415b(l)(X)1) through (4). Subpart OOOOb. [40 CFR 60.5415b(l)]

If you choose to comply with an alternative GHG and VOC standard as specified in 40 CFR 60.5398b, submit the notification in 40 CFR 60.5424b(a)(1). If you are required by 40 CFR 60.5398b(c)(8) to develop a mass emission rate reduction plan, submit the notification in 40 CFR 60.5424b(a)(2). Subpart OOOOb. [40 CFR 60.5424b(a)]

If you comply with the periodic screening requirements of 40 CFR 60.5398b(b), submit the information in 40 CFR 60.5424b(b)(1) through (6) in the annual report required by 40 CFR 60.5420b(b)(4) through (11). Subpart OOOOb. [40 CFR 60.5424b(b)]

If you comply with the periodic screening requirements of 40 CFR 60.5398b(b), maintain the records in 40 CFR 60.5424b(c)(1) through (11) in addition to the records as specified in 40 CFR 60.5420b(c)(3) through (9) and (c)(14) and (15). Subpart OOOOb. [40 CFR 60.5424b(c)]

If you comply with the continuous monitoring system requirements of 40 CFR 60.5398b(c), submit the information in 40 CFR 60.5424b(d)(1) through (6) in the annual report required by 40 CFR 60.5420b(b)(4) through (11). Subpart OOOOb. [40 CFR 60.5424b(d)]

If you comply with the continuous monitoring system requirements of 40 CFR 60.5398b(c), maintain the records in 40 CFR 60.5424b(e)(1) through (15). Subpart OOOOb. [40 CFR 60.5424b(e)]

### **PCS 0012 Gasoline Internal Combustion Engines <= 25 hp**

#### **EQT 0058 - Gasoline ICEs <= 25 hp - Engines Subject to NSPS JJJJ**

- 534 [40 CFR 60.4233(a)] Comply with the emission standards and other requirements for new nonroad SI engines in 40 CFR 1054. Subpart JJJJ. [40 CFR 60.4233(a)]
- 535 [40 CFR 60.4233(d)(1)] Comply with the emission standards and other requirements for new nonroad SI engines in 40 CFR 1054. Subpart JJJJ. [40 CFR 60.4233(d)(1)]
- 536 [40 CFR 60.4234] Operate and maintain stationary SI ICE to achieve the emission standards as required in 40 CFR 60.4233 over the entire life of the engine. Subpart JJJJ.
- 537 [40 CFR 60.4235] Use gasoline that meets the per gallon sulfur limit in 40 CFR 1090.205. Subpart JJJJ.
- 538 [40 CFR 60.4237] Operating time monitored by hour/time monitor continuously during operation, if the engine meets the standards applicable to emergency engines. Install a non-resettable hour meter upon startup of engine. Subpart JJJJ.
- 539 [40 CFR 60.4243(a)(1)(i)] Which Months: All Year Statistical Basis: None specified Either ensure engine is certified to the emission standards in 40 CFR 60.4233(f), as applicable, or conduct a performance test to demonstrate initial compliance with the emission standards according to the requirements specified in 40 CFR 60.4244. Conduct the test within 60 days after the engine commences operation after the modification or reconstruction. Subpart JJJJ. [40 CFR 60.4243(a)(1)(i)]
- 540 [40 CFR 60.4243(a)(1)] Meet the requirements as specified in 40 CFR 1068 Subparts A through D, as applicable. If the engine settings are adjusted, adjust according to and consistent with the manufacturer's instructions. Subpart JJJJ. [40 CFR 60.4243(a)(1)]
- 541 [40 CFR 60.4243(a)(2)] Conduct an initial performance test within 1 year of engine startup to demonstrate compliance, if the engine is not certified or the engine and control device are not operated and maintained according to the manufacturer's emission-related written instructions. Conduct subsequent performance testing every 8,760 hours or 3 years, whichever comes first, thereafter to demonstrate compliance, if the engine is greater than 500 HP. Subpart JJJJ. [40 CFR 60.4243(a)(2)]
- 542 [40 CFR 60.4243(a)(2)] Ensure that the engine is maintained and operated to the extent practicable in a manner consistent with good air pollution control practice for minimizing emissions, if the engine is not certified or the engine and control device are not operated and maintained according to the manufacturer's emission-related written instructions. Subpart JJJJ. [40 CFR 60.4243(a)(2)]
- 543 [40 CFR 60.4243(a)] Ensure engine is certified to the emission standards in 40 CFR 60.4231(a) through (c), as applicable, for the same engine class and maximum engine power. Subpart JJJJ. [40 CFR 60.4243(a)]
- 544 [40 CFR 60.4243(a)] Equipment/operational data recordkeeping by electronic or hard copy upon occurrence of event. Keep records of conducted maintenance to demonstrate compliance. If the engine is not certified or the engine and control device are not operated and maintained according to the manufacturer's emission-related written instructions, also keep a maintenance plan. Subpart JJJJ. [40 CFR 60.4243(a)]
- 545 [40 CFR 60.4243(c)] Demonstrate compliance with 40 CFR 60.4233(f) according to 40 CFR 60.4243(b)(2)(i) or (b)(2)(ii), except that for a non-certified engine complying according to 40 CFR 60.4243(b)(2)(i), demonstrate that the engine complies with the emission standards specified in 40 CFR 60.4233(f). Subpart JJJJ. [40 CFR 60.4243(c)]
- 546 [40 CFR 60.4243(d)(1)] There is no time limit on the use of emergency stationary ICE in emergency situations. Subpart JJJJ. [40 CFR 60.4243(d)(1)]
- 547 [40 CFR 60.4243(d)(2)(i)] Operate for maintenance checks and readiness testing for a maximum of 100 hours per calendar year, provided that the tests are recommended by the federal, state or local government; the manufacturer; the regional transmission organization or equivalent balancing authority and transmission operator; or the insurance company associated with the engine. LDEQ may be petitioned for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if records are maintained indicating that federal, state, or local standards require maintenance and testing of emergency ICE beyond 100 hours per calendar year. Subpart JJJJ. [40 CFR 60.4243(d)(2)(i)]

**EQT\_0058 - Gasoline ICEs <= 25 hp - Engines Subject to NSPS JJJ**

Operate for up to 50 hours per calendar year in non-emergency situations. Count the 50 hours of operation in non-emergency situations as part of the 100 hours per calendar year for maintenance and testing provided in 40 CFR 60.4243(d)(2). Do not use the 50 hours per calendar year for non-emergency situations for peak shaving or non-emergency demand response, or to generate income for a facility to an electric grid or otherwise supply power as part of a financial arrangement with another entity, except as provided in 40 CFR 60.4243(d)(3).

Subpart JJJ. [40 CFR 60.4243(d)(3)]  
Operate according to the requirements in 40 CFR 60.4243(d)(1), (d)(2)(i), and (d)(3). In order for the engine to be considered an emergency stationary ICE under 40 CFR 60 Subpart JJJ, any operation other than as described in 40 CFR 60.4243(d)(1), (d)(2)(i), and (d)(3) is prohibited. If the engine is not operated according to these requirements, the engine will not be considered an emergency engine under 40 CFR 60 Subpart JJJ and must meet all requirements for non-emergency engines. Subpart JJJ. [40 CFR 60.4243(d)]

550 [40 CFR 60.4243(f)]  
Perform initial performance testing as indicated in 40 CFR 60.4243, if the engine is either non-certified or is not operated or maintained, along with the control device, according to the manufacturer's written emission-related instructions. Conduct subsequent performance testing, if the engine is rebuilt or undergoes major repair or maintenance. Subpart JJJ. [40 CFR 60.4243(f)]  
Air-to-fuel ratio controller: Maintain and operate appropriately in order to ensure proper operation of the engine and control device to minimize emissions at all times. Subpart JJJ. [40 CFR 60.4243(g)]  
Conduct performance tests by following the procedures in 40 CFR 60.4244(a) through (g). Subpart JJJ.  
Equipment/operational data recordkeeping by electronic or hard copy at the approved frequency. Keep records of the information in 40 CFR 60.4245(a)(1) through (a)(4). Subpart JJJ. [40 CFR 60.4245(a)]  
Operating time recordkeeping by electronic or hard copy upon occurrence of event, if the engine meets the standards applicable to emergency engines. Keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. Document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. Subpart JJJ. [40 CFR 60.4245(b)]  
Submit performance test results: Due within 60 days after each test conducted according to 40 CFR 60.4244 has been completed. Subpart JJJ. [40 CFR 60.4245(d)]

**EQT\_0059 - All Gasoline ICEs <= 25 hp**

Opacity <= 20 percent, except that such emissions may have an average opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes.

Which Months: All Year Statistical Basis: Six-minute average  
Opacity <= 20 percent, except emissions may have an average opacity in excess of 20 percent for not more than one six-minute period in any 60 consecutive minutes.

Which Months: All Year Statistical Basis: Six-minute average

**EQT\_0060 - All Gasoline ICEs <= 25 hp for Which Construction or Reconstruction Commenced On or After June 12, 2006**

558 [40 CFR 63.6590(c)]  
Meet the requirements of 40 CFR 60 Subpart JJJ for spark ignition engines. Subpart ZZZZ. [40 CFR 63.6590(c)]

**EQT\_0061 - Gasoline ICEs <= 25 hp for Which Construction or Reconstruction Commenced Before June 12, 2006**

559 [40 CFR 63.6603(a)]  
Change oil and filter every 1,440 hours of operation or annually, whichever comes first. Subpart ZZZZ. [40 CFR 63.6603(a)]

**SPECIFIC REQUIREMENTS**  
**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**  
**Activity Number: PER2024001**

**Permit Number: MSOG Master Gen Permit**  
**Air - Minor Gen Permit-Oil and Gas Mod**

**EQT 0061 - Gasoline ICES <= 25 hp for Which Construction or Reconstruction Commenced Before June 12, 2006**

560 [40 CFR 63.6603(a)]  
Equipment/operational data monitored by visual inspection/determination annually or every 1,440 hours of operation, whichever comes first. Inspect all hoses and belts, and replace as necessary. Subpart ZZZZ. [40 CFR 63.6603(a)]

561 [40 CFR 63.6603(a)]  
Equipment/operational data monitored by visual inspection/determination annually or every 1,440 hours of operation, whichever comes first. Inspect spark plugs, and replace as necessary. Subpart ZZZZ. [40 CFR 63.6603(a)]

562 [40 CFR 63.6603(a)]  
Which Months: All Year Statistical Basis: None specified  
Minimize the engine's time spent at idle and minimize the engine's startup time at startup to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. Subpart ZZZZ. [40 CFR 63.6603(a), 40 CFR 63.6625(h)]

563 [40 CFR 63.6605(a)]  
Be in compliance with the applicable emission limitations, operating limitations and other requirements in 40 CFR 63 Subpart ZZZZ at all times. Subpart ZZZZ. [40 CFR 63.6605(a)]

564 [40 CFR 63.6605(b)]  
Operate and maintain at all times in a manner consistent with safety and good air pollution control practices for minimizing emissions. Subpart ZZZZ. [40 CFR 63.6605(b)]

565 [40 CFR 63.6625(e)]  
Operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop a maintenance plan which provides to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions. Subpart ZZZZ. [40 CFR 63.6625(e)]

566 [40 CFR 63.6625(j)]  
Utilize an oil analysis program in order to extend the specified oil change requirement in 40 CFR 63 Subpart ZZZZ, Tables 2c and 2d.

Perform the oil analysis at the same frequency specified for changing the oil in 40 CFR 63 Subpart ZZZZ, Table 2c or 2d. Ensure that the analysis program, at a minimum, analyzes the following three parameters: Total Acid Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Acid Number increases by more than 3.0 milligrams of potassium hydroxide (KOH) per gram from Total Acid Number of the oil when new; viscosity of the oil has changed by ore than 20 percent from the viscosity of the oil when new, or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, an oil change is not required. If any of the limits are exceeded, change the oil within 2 business days of receiving the results of the analysis. If the engine is not in operation when the results of the analysis are received, change the oil within 2 business days or before commencing operation, whichever is later. Keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. Ensure that the analysis program is part of the maintenance plan for the engine. Subpart ZZZZ. [40 CFR 63.6625(j)]

567 [40 CFR 63.6635(b)]  
Monitor continuously at all times that the stationary RICE is operating, except for monitor malfunctions, associated repairs, required performance evaluations, and required quality assurance or control activities. A monitor malfunction is any sudden, infrequent, not reasonably preventable failure of the monitoring to provide valid data. Monitoring failures that are caused in part by poor maintenance or careless operation are not malfunctions. Subpart ZZZZ. [40 CFR 63.6635(b)]

568 [40 CFR 63.6640(a)]  
Do not use data recorded during monitoring malfunctions, associated repairs, and required quality assurance or control activities in data averages and calculations used to report emissions or operating levels. Use all valid data collected during all other periods. Subpart ZZZZ. [40 CFR 63.6635(c)]

569 [40 CFR 63.6640(a)]  
Demonstrate continuous compliance with each applicable emission limitation, operating limitation, and other requirements in 40 CFR 63 Subpart ZZZZ. Tables 1a and 1b, Tables 2a and 2b, Table 2c, and Table 2d according to methods specified in 40 CFR 63 Subpart ZZZZ Table 6. Subpart ZZZZ. [40 CFR 63.6640(a)]

Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.6655(a) through (f), as applicable. Subpart ZZZZ.

**SPECIFIC REQUIREMENTS**  
**AI ID: 158873 - Minor Source Air General Permit for Crude Oil & Natural Gas Production Facilities**

Activity Number: PER2024001

Permit Number: MSOG Master Gen Permit  
Air -Minor Gen Permit-Oil and Gas Mod

**UNF 0001 - Entire Facility**

571 [40 CFR 63.760(c)]

Any source that determines it is not a major source but has actual emissions of 5 tons per year or more of a combination of HAP (i.e., 50 percent of the major source thresholds), shall update its major source determination within 1 year of the prior determination or October 15, 2012, whichever is later, and each year thereafter, using gas composition data measured during the preceding 12 months. [40 CFR 63.760(c)]

572 [LAC 33:III.1103]

Emissions of smoke which pass onto or across a public road and create a traffic hazard by impairment of visibility as defined in LAC 33:III.111 or intensify an existing traffic hazard condition are prohibited.

573 [LAC 33:III.1109.B]

Outdoor burning of waste material or other combustible material is prohibited.

574 [LAC 33:III.1303.B]

Emissions of particulate matter which pass onto or across a public road and create a traffic hazard by impairment of visibility or intensify an existing traffic hazard condition are prohibited.

575 [LAC 33:III.2113.A]

Maintain best practical housekeeping and maintenance practices at the highest possible standards to reduce the quantity of organic compounds emissions. Good housekeeping shall include, but not be limited to, the practices listed in LAC 33:III.2113.A.1-5.

576 [LAC 33:III.219]

Failure to pay the prescribed application fee or annual fee, as provided herein, within 90 days after the due date, will constitute a violation of these regulations and shall subject the person to applicable enforcement actions under the Louisiana Environmental Quality Act including, but not limited to, revocation or suspension of the applicable permit, license, registration, or variance.

577 [LAC 33:III.501.C.6]

Total volume of crude oil/condensate and natural gas processed by the facility shall be monitored and recorded each month. These records shall be kept on site and available for inspection by the Office of Environmental Compliance, Surveillance Division.

578 [LAC 33:III.5101.B]

Facility-wide (facilities which were a major source of LAC 33:III.Chapter 51-regulated toxic air pollutants (TAP) as of December 20, 1991, but which have achieved minor source status through reduction of emissions and potential to emit): Comply with the provisions of LAC 33:III.5105.A. 1, 3, and 4, and 5113. Pursuant to LAC 33:III.905, use and diligently maintain in proper working order control equipment installed to reduce the facility's potential to emit below the major source threshold whenever any emissions are being made which can be controlled by the facilities, even though the ambient air quality standards in affected areas are not exceeded.

579 [LAC 33:III.5611.A]

Submit standby plan for the reduction or elimination of emissions during an Air Pollution Alert, Air Pollution Warning, or Air Pollution Emergency. Due within 30 days after requested by the administrative authority.

During an Air Pollution Alert, Air Pollution Warning or Air Pollution Emergency, make the standby plan available on the premises to any person authorized by the department to enforce these regulations.

580 [LAC 33:III.5611.B]

When required by Section XI of this general permit, Submit Emission Inventory (EI)/Annual Emissions Statement : Due annually, by the 30th of April to the Office of Environmental Services, for the reporting period of the previous calendar year that coincides with period of ownership or operatorship, unless otherwise directed by DEQ. Submit both an emissions inventory and the certification statement required by LAC 33:III.919.F.1.c, separately for each AI, in a format specified by DEQ. Include the information specified in LAC 33:III.919.F.1.a through F.1.d.